



Proudly Serving Rural Routt County * City of Steamboat Springs * Town of Hayden * Town of Oak Creek * Town of Yampa * Routt County School Districts

Date: 07/16/2021

Address: 1859 RIVER QUEEN LN, STEAMBOAT	Property Use: VAC
Owner: SUNSHINE STEAMBOAT, LLC	Lot Area: 0
Parcel ID: 313400003	Year Built: 0
Zoning: TOWN	Book Page: SPECIAL



Building

TB-21-755

To: Bradley Bartels

Design information:

Occupancy Classification: R3, U

Character and Use: Two-Family Residence w/ Detached Garage under TB-21-835

Number of Stories: 2 w/Basement

Type of Construction: Type V-B

Occupant Load: <10

**RCRBD Record Set
T.A.**

08/24/2021

The following items and questions below will need to be addressed prior to the Building Permit being issued. Please make all necessary corrections and resubmit the corrected plans for review. Corrections shall be “ballooned” if made on the plans and a narrative that specifically references the items on this list shall be included with the resubmittal.

1. This project is in the concurrent review process with the other Departments. Review comments in Viewpermit as applicable, when available.
2. Based on the submittal Work Description – Duplex- Unit A and Unit B under permit TB-21-834 makes this a single building, however will these units will be divided with a property line between units?
If solely by a property line, the party wall shall separate into two buildings with more flexibility with common or condominium ownership. Either way, shall be separated by fire-resistance-rated wall assemblies meeting the requirements of Section R302 for exterior walls (two one-hour walls).
Other items that shall be met include extent of rating and be tight against the exterior wall, and wall assemblies shall extend from the foundation to the underside of the roof sheathing. Projections of exterior walls of dwellings and accessory buildings shall comply with Table R302.1(1) as per R302.1 Exterior walls with 1 hour on the underside. Gas piping installed downstream of the point of delivery shall not extend through any unit other than the unit served by such piping. G2415.3 (404.3) Prohibited locations.
3. The insulation values appear out of compliance for Zone 7. Building sections for this project shall include the information per prescriptive energy path as per attached Energy Code Compliance chart for reference below

Routt County Regional Building Department

136 6th Street, Ste 201, Steamboat Springs, CO 80487 PH: 970-870-5566 Fax 970-870-5489 Email: Building@co.routt.co.us

for values and distances. Building sections should incorporate all items and corrected to show following specific items:

- a. While 1/A3.04 shows F-1 with R-21 insulation under Entry, however a minimum of R-10 insulation as required from the top of concrete downward 48" (vertical and/or horizontal) for slab on grade.
- b. Similarly, the garage appears to have similar conditions at slab on grade. Please specify how each element is to be insulated with minimum R-values and attention to minimum distances (if applicable).

Either could be traded off in REScheck.

4. Appendix F Radon Mitigation: This appendix was adopted with the 2018 IRC, please submit plans showing how and where you intend to install under slab radon mitigation piping, and the location where this pipe will rise vertically above the slab. Our adoption only requires the under slab portion of the work to be done in accordance with Appendix F, then you may cap the pipe and label it above the slab. You also must provide an outlet or junction box for a future power for a fan within a close proximity of the capped pipe or future fan location.
5. Provide missing structural connections referenced in details on Sheet A5.10
6. Provide complete plans with structural and insulation details for detached garage and trash storage if taller than 6-feet (permit will be required).

✓ **Items noted below do not require a response or comment back during the Plan Review in order for us to approve this permit. The Items below are required and will be checked by field inspectors. Please take time to review these items in advance of starting any work to ensure your project is ready for inspection.**

1. Separate Electrical Plumbing Permits must be applied for and obtained prior to any work being done within these trades. Note Electrical and Plumbing trades are protected by the State, Licensed Contractors must apply and perform this work on all Commercial Properties, and additionally their employees working on these projects must be registered or licensed with the State of Colorado and work directly under Licensed Individual managing the project.
 - On Residential Properties owners are allowed to apply for the permit and perform their own Electrical and Plumbing work if this is their primary residence and they sign and complete our Home Owner Agreement form.
2. Separate Mechanical Permits must be applied for and obtained prior to any work being done within this trade. Mechanical Contractors must be registered and approved by the Routt County Regional Building Department.
3. Deferred Submittal Required: Heat Load Calculations and heating information for the new construction must be submitted prior to Electrical, Plumbing, and Mechanical Permits being issued.
7. Deferred Submittal Required: Stamped Truss Drawings to be provided for review and approval by RCRBD prior to trusses being set and inspections being done.
8. Deferred Submittal: Applicant to provide information on how Whole House Ventilation requirements will be met in accordance with IECC R403.6 and 403.6.1 and IRC M1507.3.
9. Deferred Blower Door Test Certificate of Compliance: The building or dwelling unit (except within the Town of Hayden) must complete a Blower Door Test with a passing score of Equal/Less than 3 air changes per hour (3ACH), this certificate must be present for our Inspectors prior to approval of a Temporary Certificate of Occupancy/ Certificate of Occupancy. Please also upload this Blower Door Certificate to the Building Department Permit Record, or email this to our staff and they will upload the document.
10. The Routt County Building Department has developed the Residential Private Garage Floor Drain Policy. This Policy outlines the regulations per Jurisdiction on private residential garage floor drains throughout Routt County, ask Routt County personnel for policy.
11. R308 Glazing. Except as indicated in Section R308.1.1, each pane of glazing installed in hazardous locations as defined in Section R308.4 shall be provided with a manufacturer's or installer's label, designating the type and thickness of glass and the safety glazing standard with which it complies, which is visible in the final

Routt County Regional Building Department

136 6th Street, Ste 201, Steamboat Springs, CO 80487 PH: 970-870-5566 Fax 970-870-5489 Email: Building@co.routt.co.us

installation. The label shall be acid etched, sandblasted, ceramic-fired, embossed mark, or shall be of a type which once applied cannot be removed without being destroyed. Exceptions: Tempered spandrel glass may be identified by the manufacturer with a removable paper label.

12. Fenestration U-factors windows and doors less than or equal to 0.30 will be required. This will apply for all glazing in windows and doors. The builder shall leave the National Fenestration Rating Council (NFRC) labels on all windows and doors with glazing at time of rough inspections so inspectors can verify the glazing requirements. Also provide documentation that the garage doors have a maximum U-factor of 0.32.
13. Bath Exhaust ducts if ran in unconditioned space must be done in insulated duct.
14. R321.1 Premises identification. Approved numbers or addresses shall be provided for all new buildings in such a position as to be plainly visible and legible from the street or road fronting the property.
15. SECTION R314 SMOKE ALARMS

R314.1 General. Smoke alarms shall comply with NFPA 72 and Section R314.

R314.1.1 Listings. Smoke alarms shall be listed in accordance with UL 217. Combination smoke and carbon monoxide alarms shall be listed in accordance with UL 217 and UL 2034.

R314.2 Where required. Smoke alarms shall be provided in accordance with this section.

R314.2.1 New construction. Smoke alarms shall be provided in dwelling units.

R314.3 Location. Smoke alarms shall be installed in the following locations:

1. In each sleeping room.
2. outside each separate sleeping area in the immediate vicinity of the bedrooms.
3. on each additional story of the dwelling, including basements and habitable attics and not including crawl spaces and uninhabitable attics. In dwellings or dwelling units with split levels and without an intervening door between the adjacent levels, a smoke alarm installed on the upper level shall suffice for the adjacent lower level provided that the lower level is less than one full story below the upper level.
4. Smoke alarms shall be installed not less than 3 feet (914 mm) horizontally from the door or opening of a bathroom that contains a bathtub or shower unless this would prevent placement of a smoke alarm required by Section R314.3.

SECTION R315

CARBON MONOXIDE ALARMS

R315.1 General. Carbon monoxide alarms shall comply with Section R315.

R315.1.1 Listings. Carbon monoxide alarms shall be listed in accordance with UL 2034. Combination carbon monoxide and smoke alarms shall be listed in accordance with UL 2034 and UL 217.

R315.2 Where required. Carbon monoxide alarms shall be provided in accordance with Sections R315.2.1 and R315.2.2.

R315.2.1 New construction. For new construction, carbon monoxide alarms shall be provided in dwelling units where either or both of the following conditions exist.

1. The dwelling unit contains a fuel-fired appliance.
2. The dwelling unit has an attached garage with an opening that communicates with the dwelling unit.

R315.3 Location. Carbon monoxide alarms in dwelling units shall be installed outside of each separate sleeping area in the immediate vicinity of the bedrooms. Where a fuel-burning appliance is located within a bedroom or its attached bathroom, a carbon monoxide alarm shall be installed within the bedroom.


R315.4 Combination alarms. Combination carbon monoxide and smoke alarms shall be permitted to be used in lieu of carbon monoxide alarms.

R315.5 Power source. Carbon monoxide alarms shall receive their primary power from the building wiring where such wiring is served from a commercial source and, where primary power is interrupted, shall receive power from a battery. Wiring shall be permanent and without a disconnecting switch other than those required for overcurrent protection.

Exceptions:

1. Carbon monoxide alarms shall be permitted to be battery operated where installed in buildings without commercial power.
2. Carbon monoxide alarms installed in accordance with Section R315.2.2 shall be permitted to be battery powered.

Reviewed by: Ted Allen Date: July 16, 2021




440 S. Lincoln Ave, Suite 4A
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointsse.com

[illegible]

**LOT 3, EAGLE'S VISTA
SUBDIVISION**

**1859 RIVER QUEEN LANE
STEAMBOAT SPRINGS, CO 80487**



CSMP & ECP

SHEET #

3

Steamboat Springs Alpine House

1859 River Queen Lane,
Steamboat Springs, CO 80487

PJ4979-1
PJ4980-1
PJ4981-1
Fire Prevention
In: 07/14/2021
Out: 07/15/2021

City of Steamboat Springs
Planning and Community Development
APPROVED
August 04, 2021

CIVIL

- 1 SITE PLAN & PROFILE
2 DETAILS

DESIGN

- A0.00 SCOPE OF WORK
A0.01 NOTES & ASSEMBLIES LEGEND
A1.00 SITE PLAN
C2.00 FOUNDATION PLAN
A2.00 FLOOR PLAN - LOWER
A2.01 FLOOR PLAN - MAIN
A2.02 FLOOR PLAN - UPPER
A2.03 ROOF PLAN
A3.01 BUILDING SECTIONS
A3.02 BUILDING SECTIONS
A3.03 BUILDING SECTIONS
A3.04 BUILDING SECTIONS
A3.05 BUILDING SECTIONS
A4.01 EAST ELEVATION
A4.02 SOUTH ELEVATION
A4.03 WEST ELEVATION
A4.04 NORTH ELEVATION
A4.05 EXTERIOR MATERIALS LEGEND
A4.06 EXTERIOR STREET VIEW
A5.10 WALL SECTION
A5.11 WALL SECTION
A9.00 WINDOW DOOR SCHEDULE

STRUCTURAL

- S1 FOUNDATION PLAN
S2 DETAILS
S3 MAIN FLOOR FRAMING
S4 UPPER FLOOR FRAMING
S5 ROOF FRAMING

DESIGN

SCOTT&SCOTT
299 E19TH AVENUE
VANCOUVER BC
V5V 1J3

DAVID SCOTT MAIBC MRAIC
604 737 2541
DAVID@SCOTTANDSCOTT.CA

SUSAN SCOTT MAIBC
604 788 7990
SUSAN@SCOTTANDSCOTT.CA

STRUCTURAL ENGINEER

ENGINEERING DESIGNWORKS, INC.
1855 SKI TIME SQUARE, UNIT E2C
STEAMBOAT SPRINGS, CO
80487



Contact: Carl Warnke
p. 970-879-4890
email: carl@engineeringdesignworks.com

CIVIL ENGINEER

FOUR POINTS SURVEYING AND ENGINEERING
440 S LINCOLN AVE #4A
STEAMBOAT SPRINGS, CO
80487

Contact: Walter Magill
p. 970-871-6772
email: walterm@fourpointsse.com

ATMOS ENERGY CORPORATION
2# Systems will not be allowed unless proof of an appliance
requiring a MINIMUM of over 7" W.C. is provided to Atmos
Energy Corporation personnel for review.
Meter location must be approved by an Atmos Energy
Corporation employee during a mandatory site visit to be
scheduled after foundation is in place.
Meters will not be allowed under a shedding roofline or
where overhanging snow is a danger to the meter set.
Any work being performed in utility easements must be
approved by Atmos Energy Corp.



SCOTT & SCOTT

604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

ISSUED FOR BUILDING PERMIT

23 JUNE 2021

Scope of Work

The following is a preliminary overview for schematic level costing.
Structural information is preliminary and subject to finalization.

GENERAL CONDITIONS	
1	<p><i>Site Prep / Planning</i></p> <p>Site preparation for foundation, service connections and rainwater management to be provided inc. backfill, sub slab and perimeter gravel and drain tile, base and driveway to garage (Area TBD on Site).</p>
2	<p><i>Services</i></p> <p>200 amp min. Electrical services to be provided inc. sub panel to garage. Services to be underground from client specified pole location to garage. Sanitary plumbing to Grinder Pump. Underground to dwelling units and perimeter drain/ rock pits as req'd. 1" water line for each dwelling unit. Cable and data lines to client specified mast and underground to dwelling units. Propane service (gas if available)</p>
3	<p><i>Foundation/ Slabs</i></p> <p>8" CIP concrete foundation to frost protection depth.</p> <p>Visible face to be formed with first use forming and considered for appearance (Windows to be 1/2" reveal to window frame with A Grade form blockouts at locations) :</p> <p>Option A- To be board form EZ strip forming with ties between boards Option B- To be standard D.Fir form plywood with cone or button ties.</p> <p>Bituminous Waterproof membrane to exterior of concrete forms to 6" below grade + Mirror Drain (Dorken Delta or Equiv.) Silane sealer to concrete above.</p> <p>All slabs/ stairs and associated flat work to be placed and finished to +/- 1/8"- 10' with square cornered inside and outside corners. Cut lines to confirmed with Design Consultant and completed w./ circular (Skil) saw with diamond blade and straightedge. All finished trowelled slabs to be (interior) smooth troweled w./ silane sealer and no sheen janitorial wax. Exterior slab work to be float finished w./ 1-2 passes of power trowel to traction finish. All interior topping slabs to be 3" thickness typ. c/w mesh reinforcement and heating tubing where applicable.</p>
4	<p><i>Framing (prelim. to be confirmed)</i></p> <p>Exterior walls as noted to be 2x6 stud per Structural on 2x6 plate (c/w R-21 cavity insulation with continuous 1" XPS outslution) All 6x10 Roof/ Wall Framing exterior walls as noted to be SPF per Structural (visible) with 2x tongue and groove decking, c/w 1/2" plywood sheathing. All interior walls to be 2x4/6 as per romm dimension requirments as noted. Main floor framing to be TJI or LVL per Structural c/w Ply subfloor to receive concrete topping Upper floor framing to be 6x10 per Strucutral with 2x tongue and groove decking, c/w 1/2" plywood sheathing. Floor assembly to c/w. 1 1/2" furring strips for mineral wool sound insulation through out and dropped @ bathroom for flush tile and shower pan installation. 1" subfloor for 3/4" wood flooring. All 6x10 Roof/ Wall Framing as noted to be SPF (visible) per Structural with 2x tongue and groove decking, c/w 1/2" plywood sheathing. C/w with outslution.</p>
5	<p><i>Thermal and Moisture Protection (ACH <0.6)-provide blower door test prior to interior finish installation and pre-occupancy.</i></p> <p>Wall moisture barrier (ext) to be Solitex Adhero c/w Tescon Vana Tape Air barrier (int) to be Proclima Intello Plus c/w Tescon Vana Tape Roofing Underlayment to be fully adhered Soprema Lastobond Shield HT. (to be returned 8-10" down top of wall exterior moisture barrier as perimeter sub flashing. Insulation to be rockwool for cavity fill and exterior above grade board Basement to be XPS with mineral wool cavity (c/w 2lb. closed cell spray foam as req'd for air barrier continuity at joist pockets) Roof insulation to be: 2 lb. closed cell spray foam insulation, min. R-49. Provide Rock wool sound insulation for all interior walls and floor cavities (and rockwool board for upper floor framing) Roofing to be metal - 7/8" corrugated steel siding (22ga/ Weathering Steel finish), with 18 ga. flashing to match.</p>
6	<p><i>Exterior</i></p> <p>Windows and sliding doors to be metal (clear anodized aluminum, or color to match Weathering steel.) max. U-30 as req'd. Wall Cladding to be: Where indicated 7/8" corrugated steel siding (22ga/ Weathering Steel finish), with flashing to match. Douglas Fir T&G Boards where indicated (3-1/4" face w/ 1/8" shadowline) where indicated - C Clear or better T&G Soffit/ Wall Cladding. Flashing to be square back hem returned 3/4" @ windows and doors, 2" at eave, and 4" at top of wall/ roof transition.</p>

NOTES:
+ All new construction as per 2018 IRC and 2018 IECC.
+ All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
+ Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

7 Interior

Wall and Ceiling Finishes:

Lower Level T&G Ceiling Cladding throughout to match visible 2X decking.
T&G Wall Cladding where noted to match visible 2X decking.
Hallway Walls- GWB * tile and backer board in bathroom.

Main Floor Inside face of exterior wall- Visible 6x10 Rafters/ 2X decking.
Interior Walls- GWB * tile and backer board in bathrooms.
Upper Floor Inside face of exterior wall - Visible 6x10 Rafters/ 2X decking.
Interior Walls- GWB * tile and backer board in bathrooms.
Garage Exposed Framing.

All GWB to #4 finish typ. and #5 within 6' of adjacent wall or ceiling where perpendicular to glass.
All GWB to be painted with washable flat paint.
All GWB walls to finished to the edges have a 1/2" shadow trim bead (Flannery, Fry Reglet or Gordon) or 1/8" shadow edge or L bead where abutting a dissimilar material or frame.

All tile to be preped with cement or schuler backing panel w./ fabric reinforces liquid waterproofing for all shower/ tub deck and skirt and base transitions.
tile TBD@ +/- 3-4" square or rect.- assume 1/16" grout lines and bullnose edge tiles on corners and edges.

Interior doors to be 1 3/4" solid core wood painted with frames bevel prepped for mud into adjacent GWB wall w./ confil and feather. To be supplied with stainless steel or brushed nickel hinges and levers to be supplied by Design Consultant (mortice prep req'd). Sliding doors to be Slid Retrac or Hawa Junior with track recessed for door to be pocketed or 1/8" off of ceiling face.

Flooring:

Basement, main floor, and garage to be smooth trowelled concrete- protected during construction, all hairline cracks filled with a malpai or flextile unsanded tile grout of matching colour, cleaned with a light pass of 180 grit on a hand orbital sander or janitorial screen, sealed with a silane sealer and a low sheen janitorial floor wax.

Upper floor to be a T&G flooring to match visible 2X decking, finished with Salcos hardwax oil finish. To be engineered if over radiant and C-Clear mixed grain 3.25"W x 6-8' L with min 30% over 10' and max 30% under 4'.

Stair treads to be Jointed 90' L caps from C-Clear 2x12 and 2x8 stock to match upper level flooring.

8 Millwork

Casework to be exposed edge GIS D.Fir Plywood where back of panel not visible and marine grade D.fir plywood for all doors and visible panel. To be finished in a rubbing linseed or hardwax oil of the design consultant's colour selection. rods to be 1- 1/2" Hem fir dowel or 1 1/4" stainless steel ornamental tube. Drawer boxes to be prefabricated maple dovetail boxes or b.birch plywood construction. All shelves below 4" to have 1.5" upstands and be pullout. all shelves above 4" to be pin adjustable. Full height pantry pullout units to be Hafele or Richelieu supplied w./ chrome baskets. Allow for panels for fridge and dishwashers and hardware installation. All drawers to be softclose, typ.

Millwork to include vanities, kitchens, and closets (2 drawer bases w./ shelf and rod).
Counter tops TBD. Cost per solid surface, stone, quartz or stainless steel.

8 Appliances

Fixtures TBD- \$20,000 Budget allowance for GC or owner supply.
Allow for installation, connections and coordination of panel ready fridge and DW. Allow for water RI to fridges.

9 Electrical


Rough in wiring to be supplied and installed.
Fixtures TBD- \$20,000 Budget allowance for electrician or owner supply.
A Lighting and device plan will be provided by the design consultant.
Lights are semi-recessed wallmount (TBD) for most applications (no potlights) and to be wired for trade supplied dimmers for all locations.
Allow for pendant light above dining tables. 4 aluminum round floor outlets in the living areas and stainless steel (or white painted steel) device covers with white decora devices.
All tel data locations to be in a partitioned multigang single plate with adj. line volt power.
Provide data ports in each floor level and suite w./ homerun to garage.
Provide option for Security.
If central heating is not hydronic provide for undertile heating mats in each bathroom.

10 Plumbing

Rough-in plumbing to be supplied and installed.
All wastelines to be wrap insulated or cast iron in partition walls.
Fixtures TBD- \$20,000 Budget allowance for plumber or owner supply. Plumber to supply chrome stops, escutcons and Ptraps where visible. (no visible plastic inwall pipe).
Allow for 4 frost free hosebibbs and 1 landscape water termination.
Provide cost option for shop sink in garage and floor drain.
Provide cost option for Hydronic boiler heating system with domestic water heating component.
Provide cost option for water filtration/ softner.
Provide cost option for gas cooktops.

11 HVAC

Concrete toppings/ slab on grade to have radiant infloor heating.
Provide cost option for radiant infloor heating for upper levels (Warmboard, or equiv).
Kitchen cooktops to have downdraft vent.
All vents to be coordinated in existing wall or ceiling framing (no bulkheads) head positions to be provided +/- 4" tin mark up for design consultant to return specific location in drawings.


















SCOTT & SCOTT

604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

Steamboat Springs
Alpine House
Steamboat Springs, Co

A0.00

Scope of Work

TYPE	PARTITION TYPE DESCRIPTION	TYPE	EXTERIOR WALL TYPE DESCRIPTION	TYPE	FLOOR TYPE DESCRIPTION		
P1	 <p>Partition Type Assembly 1 + 1/2" GWB, Level 4/5 finish. + 2x4 studs @ 16" o.c. + acoustic batt in cavity + 1/2" GWB, Level 4/5 finish.</p>	W1	 <p>Exterior Wall Assembly 1 (Basement) (R-20) + 6" min. clean gravel backfill below grade + Foundation dampproofing below grade + Reinforced concrete wall per Structural (CIP - Boardform Architectural Grade) + 1" continuous XPS rigid insulation (R-5) + 2x4 stud wall @ 16" O.C. (min. R-4 insulated headers) + 3 1/2" Rockwool Comfortbatt insulation in cavity (R-15) + 6 mil poly VB/AB (seal all joints) + 3/4" Vertical T&G wall cladding to match Decking</p>	F1	 <p>Exterior Floor Assembly 1 - R-21 + 5" reinforced concrete slab on grade (in floor radiant) per Structural + 3/4" plywood sheathing per Structural + 3" 2 lb. closed cell sprayfoam insulation (Vapor/ Air barrier) (R-21) + 6" min. 1/4" clean gravel fill</p>	F4	 <p>Exterior Floor Assembly 4 (Deck) + 1-1/2" Cedar Deck Boards (gapped 1/4") + Joists per Structural</p>
P2	 <p>Partition Type Assembly 2 + 3/4" Vertical Pine T&G to match Decking. + 2x6 studs @ 16" o.c. + acoustic batt in cavity + 1/2" GWB, Level 4/5 finish.</p>					TYPE	EXTERIOR ROOF TYPE DESCRIPTION
P3	 <p>Partition Type Assembly 3 + 3/4" Vertical Pine T&G to match Decking. + 2x6 studs @ 16" o.c. + acoustic batt in cavity + 3/4" Vertical Pine T&G to match Decking.</p>	W2	 <p>Exterior Wall Assembly 2 (R-26) + 3/4" Vertical Douglas Fir T&G Cladding + 3/4" cedar strapping (airspace) + Vapour Permeable Weather Barrier + 1" continuous XPS rigid insulation (R-5) + Plywood sheathing per Structural + 2x6 stud wall @ 16" O.C. (min. R-4 insulated headers) + 5 1/2" Rockwool Comfortbatt insulation in cavity (R-21) + 6 mil poly VB/AB (seal all joints) + 1/2" GWB, PTD, Level 4/5 finish, or interior finish as noted.</p>	F2	 <p>Exterior Floor Assembly 2 (R-38) + 3" concrete topping (in floor radiant) per Structural + 3/4" plywood sheathing per Structural + Joists per Structural + 9-1/2" Rockwool comfortbatt insulation in cavity (R-38) + 5/8" plywood sheathing + Vapour Permeable Weather Barrier + 3/4" Douglas Fir T&G Cladding</p>	R1	 <p>Exterior Roof Assembly 1 (R-50.75) + 7/8" corrugated steel siding (22ga/ Weathering Steel finish) + Roofing underlayment (Soprema Lastobond Shield HT or equiv.) + 1/2" plywood sheathing + 7-1/4" 2lb. closed cell spray foam (R-7/ inch=R-50.75) attached with 2x8s per Structural (fixing centers to be aligned with rafters for no visible fasteners on exposed decking) + Fully adhered Peel & Stick Air/Vapour Barrier + 1/2" plywood sheathing per Structural + 2x6 T&G Decking per Structural + Rafters per Structural (Visible)</p>
P4	 <p>Partition Type Assembly 4 + 3/4" Vertical Pine T&G to match Decking. + 2x4 studs @ 16" o.c. + acoustic batt in cavity + 1/2" tile backer board in wet areas + Wall tile</p>						
P5	 <p>Partition Type Assembly 5 + 1/2" GWB, Level 4/5 finish. + 2x4 studs @ 16" o.c. + acoustic batt in cavity + 1/2" tile backer board in wet areas + Wall tile</p>	W3	 <p>Exterior Wall Assembly 3 (R-50.75) + Vertical 7/8" corrugated steel siding (22ga/ Weathering Steel finish) + Vapour Permeable Weather Barrier + 1/2" plywood sheathing + 7-1/4" 2lb. closed cell spray foam (R-7/ inch=R-50.75) attached with 2x8s per Structural (fixing centers to be aligned with rafters for no visible fasteners on exposed decking) + Fully adhered Peel & Stick Air/Vapour Barrier + 1/2" plywood sheathing per Structural + 2x6 T&G decking per Structural + Columns per Structural (Visible)</p>	F2b	 <p>Interior Floor Assembly 2b + 3" concrete topping (in floor radiant) per Structural + 3/4" plywood sheathing per Structural + Joists per Structural + Acoustic Insulation in cavity + 5/8" plywood sheathing + 3/4" Pine T&G Cladding to match Decking</p>	R2	 <p>Exterior Roof Assembly 2 (R-50.75) + 1/8" Weathering Steel Plate + Roofing underlayment (Soprema Lastobond Shield HT or equiv.) + 1/2" plywood sheathing + 7-1/4" 2lb. closed cell spray foam (R-7/ inch=R-50.75) attached with 2x8s per Structural (fixing centers to be aligned with rafters for no visible fasteners on exposed decking) + Fully adhered Peel & Stick Air/Vapour Barrier + 1/2" plywood sheathing per Structural + 2x6 T&G Decking per Structural + Rafters per Structural (Visible)</p>
P6	 <p>Partition Type Assembly 6 + 1/2" GWB, Level 4/5 finish. + 2x4 studs @ 16" o.c. + acoustic batt in cavity + 1" Marine Grade Plywood to Match Millwork</p>						
ENERGY COMPLIANCE SUMMARY:							
METHOD OF ANALYSIS:	Prescriptive Envelope						
CLIMATE ZONE:	7						
BUILDING TYPE:	Two Family Residential						
PRESCRIPTIVE REQUIREMENTS (Building Thermal Envelope R402) :							
	REQ'D PERFORMANCE	PROPOSED					
Wood Framed Wall (2x6):	R-20/ 5	R-26					
Basement Wall:	R-15/19	R-20					
Flat Ceilings:	R-49						
Roof Without Attic Space:	R-49	R-50.75					
Slab on Grade:	R-10	R-21					
Floor Insulation:	R-38						
Windows:	U-.30						
Skylights:	U-0.55	U-0.55					

1 Exterior Assemblies Legend
1-1/2" = 1" (@24"x36" plot)

GENERAL NOTES:

1. General notes are an aid to the Contractor in understanding the work and should not be construed to be complete in every detail. It is the specific and explicit responsibility of the Contractor to visit the site, verify the existing conditions, familiarize him/herself thoroughly with the scope of work, and report all discrepancies between the drawings and the assumed or actual conditions to the attention of the Design Consultant.

2. It is the specific and explicit responsibility of the Contractor to examine the contract documents in their entirety, to report all discrepancies encountered therein to the attention of the Design Consultant and await resolution before proceeding with any work affected by those discrepancies. No one drawing or specification shall "govern"; Contractor shall coordinate between design drawings and specifications.
3. All lines, symbols, notes, poche, and other graphic devices contained in the contract documents and specifications carry specific or inferential meaning and are all part of the Contractor's scope of work, whether or not they have been included in the original estimate. Any items for which the Contractor requires further clarification shall be brought to the attention of the Design Consultant before commencement of any work.

4. Design work is the responsibility of the Design Consultant. The Contractor shall assume all responsibility and design liability for changes in the scope of work not brought to the attention of the Design Consultant.
5. Contractor to secure and pay for all licenses, permits, and other applicable fees necessary for the performance, completion, inspection and approval of all work.

6. Contractor shall coordinate the work of all sub-contractors, including those under separate contract with the Owner.

7. Contractor shall maintain a clean and safe project site at all times.

8. Contractor shall provide all necessary barricades and other forms of protection to prevent injury to Owner, employees and the General Public during the period of construction.
9. Alternates and Substitutions to specified items are to be submitted to the Design Consultant/ Engineer for review and approval.

10. Contractor to provide structural backing/ blocking for all wall-mounted fixtures, finishes, and equipment.

11. Contractor to install all materials and equipment as per manufacturer's written instructions and/or recommendations.

12. Contractor is responsible for all means and methods of construction, including temporary shoring, bracing, or other protection as required. Engineering specifies finished condition only, without assuming knowledge nor responsibility for how the Contractor will achieve the result.

NOTES:
+ All new construction as per 2018 IRC and 2018 IECC.
+ All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
+ Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

SCOTT & SCOTT

604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3


Steamboat Springs
Alpine House
Steamboat Springs, Co

A0.01

Notes & Assemblies Legend

ZONING SUMMARY	
Lot Area:	20,287 sf
Zone District:	Residential Neighborhood - 2
Maximum Principal Building Height:	40'
Proposed Principal Building Height:	39'-11"
Maximum Accessory Building Height:	28'
Proposed Accessory Building Height:	20'-2 3/8"
Maximum Lot Coverage:	35%
Proposed Lot Coverage:	17.2%
Maximum Accessory Building Lot Coverage:	20%
Proposed Accessory Building Lot Coverage:	2.6%
Building Type:	Two Family Residential

BUILDING AREA	
Living Total:	3889.5 sf
Lower Level:	991.9 sf
Main Level:	1971.6 sf
Upper Level:	926 sf
Exterior Porches (Front and Rear)	693.6 sf



1 Site Plan
1/8" = 1' (@24"x36" plot)



S&S


SCOTT & SCOTT
604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

Steamboat Springs
Alpine House
Steamboat Springs, Co

A1.00

Site Plan

23 JUNE 2021



NOTES:

- + All new construction as per 2018 IRC and 2018 IECC.
- + All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
- + Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.


Steamboat Springs Alpine House

Steamboat Springs, Co

C2.00_{R1}

Foundation Plan

27 JULY 2021



MATERIAL SCHEDULE

- ②.1 Solid DF Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4\" face with 1/8\" shadow
- ②.2 Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen
- ③.1 Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel
- ③.2 18 ga. Clear Anodized Aluminum flashing or to match Window System.
- ③.3 Solid Wood Entry Doors - Copper Plate Exterior Finish.

- ④.1 Concrete - Board Shuttered Concrete
- ④.2 Concrete - Round Pier
- ④.3 Concrete - Polished Floor
- ⑤.1 GWB, PTD, Level 4/5 finish.
- ⑤.2 Floor/ Wall Tile TBC
- ⑥.4 1-1/2\" Cedar Deck Boards (gapped 1/4\")
- ⑥.5 T&G Flooring/ Cladding to Match Decking
- ⑥.6 Millwork/ Doors - Marine Grade Plywood, Finish TBC.

- ⑦.1 7/8\" Corrugated Roofing/ Wall Weathering Steel 20 ga. - Western States Metal Roofing, or other.

- ⑦.2 Flashing/ Dormer Cladding - 1/8\" Steel Plate and 18 ga. Weathering Steel flashing - Western States Metal Roofing, or other.

- ⑦.3 Hot Dipped Galvanized Metalwork Steel Plate, Guardrail - Linear Bar Grating- McNichols or other.

NOTES:
+ All new construction as per 2018 IRC and 2018 IECC.
+ All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
+ Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

S&S


SCOTT & SCOTT

604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

Steamboat Springs
Alpine House
Steamboat Springs, Co

A2.00

Floor Plan - Lower Level



MATERIAL SCHEDULE

②.1 Solid DF - Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4" face with 1/8" shadow

②.2 Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen

③.1 Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel

③.2 18 ga. Clear Anodized Aluminum flashing or to match Window System.

③.3 Solid Wood Entry Doors - Copper Plate Exterior Finish.

④.1 Concrete - Board Shuttered Concrete

④.2 Concrete - Round Pier

④.3 Concrete - Polished Floor

⑤.1 GWB, PTD, Level 4/5 finish.

⑤.2 Floor/ Wall Tile TBC

⑥.4 1-1/2" Cedar Deck Boards (gapped 1/4")

⑥.5 T&G Flooring/ Cladding to Match Decking

⑥.6 Millwork/ Doors - Marine Grade Plywood, Finish TBC.

⑦.1 7/8" Corrugated Roofing/ Wall Weathering Steel 20 ga. - Western States Metal Roofing, or other.

⑦.2 Flashing/ Dormer Cladding - 1/8" Steel Plate and 18 ga. Weathering Steel flashing - Western States Metal Roofing, or other.

⑦.3 Hot Dipped Galvanized Metalwork Steel Plate, Guardrail - Linear Bar Grating- Mcnichols or other.

NOTES:

+ All new construction as per 2018 IRC and 2018 IECC.

+ All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.

+ Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:

All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:

Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:

It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.


AUTHORITIES' REQUIREMENTS AND APPROVALS:

All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

Steamboat Springs
Alpine House
Steamboat Springs, Co

A2.01R1
Floor Plan - Main Level



MATERIAL SCHEDULE

- | | | |
|--|---|---|
| ②.1 Solid DF Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4" face with 1/8" shadow | ④.1 Concrete - Board Shuttered Concrete | ⑦.1 7/8" Corrugated Roofing/ Wall Weathering Steel 20 ga. - Western States Metal Roofing, or other. |
| ②.2 Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen | ④.2 Concrete - Round Pier | ⑦.2 Flashing/ Dormer Cladding - 1/8" Steel Plate and 18 ga. Weathering Steel flashing - Western States Metal Roofing, or other. |
| ③.1 Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel | ④.3 Concrete - Polished Floor | ⑦.3 Hot Dipped Galvanized Metalwork Steel Plate, Guardrail - Linear Bar Grating- McNichols or other. |
| ③.2 18 ga. Clear Anodized Aluminum flashing or to match Window System. | ⑤.1 GWB, PTD. Level 4/5 finish. | |
| ③.3 Solid Wood Entry Doors - Copper Plate Exterior Finish. | ⑤.2 Floor/ Wall Tile TBC | |
| | ⑥.4 1-1/2" Cedar Deck Boards (gapped 1/4") | |
| | ⑥.5 T&G Flooring/ Cladding to Match Decking | |
| | ⑥.6 Millwork/ Doors - Marine Grade Plywood, Finish TBC. | |

NOTES:
+ All new construction as per 2018 IRC and 2018 IECC.
+ All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
+ Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.



SCOTT & SCOTT


604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

Steamboat Springs
Alpine House
Steamboat Springs, Co

A2.02

Floor Plan - Upper Level

23 JUNE 2021



MATERIAL SCHEDULE

- 1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994


995

996

997

998

999
- NOTES:
+ All new construction as per 2018 IRC and 2018 IECC.
+ All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
+ Provide power and service requirements to equipment shown in the equipment schedule.
- DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.
- SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.
- DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.
- AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.
- Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.
- SCOTT & SCOTT
- 604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3
- Steamboat Springs
Alpine House
Steamboat Springs, Co
- A2.03
- Roof Plan
- 23 JUNE 2021



MATERIAL SCHEDULE

- ① Solid DF Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4" face with 1/8" shadow
- ② Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen
- ③ Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel
- ④ 18 ga. Clear Anodized Aluminum flashing or to match Window System.
- ⑤ Solid Wood Entry Doors - Copper Plate Exterior Finish.

NOTES:

- + All new construction as per 2018 IRC and 2018 IECC.
- + All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
- + Provide power and service requirements to equipment shown in the equipment schedule.

- ④ Concrete - Board Shuttered Concrete
- ⑤ Concrete - Round Pier
- ⑥ Concrete - Polished Floor
- ⑦ GWB, PTD. Level 4/5 finish.
- ⑧ Floor/ Wall Tile TBC
- ⑨ 1-1/2" Cedar Deck Boards (gapped 1/4")
- ⑩ T&G Flooring/ Cladding to Match Decking
- ⑪ Millwork/ Doors - Marine Grade Plywood, Finish TBC.

DIMENSIONS:

All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:

Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:

It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:

All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

2 Unit 1 - Cross Section B
1/4" = 1' (@24"x36" plot)

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

3 Unit 1 - Cross Section C
1/4" = 1' (@24"x36" plot)

SCOTT & SCOTT


604 737 2541

299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

**Steamboat Springs
Alpine House**
Steamboat Springs, Co

A3.01

Building Sections



MATERIAL SCHEDULE

- ②.1 Solid DF Boards - C Clear or better, T&G Soffit & Wall Cladding - 3 1/4\" face with 1/8\" shadow
- ②.2 Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen
- ③.1 Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel
- ③.2 18 ga. Clear Anodized Aluminum flashing or to match Window System.
- ③.3 Solid Wood Entry Doors - Copper Plate Exterior Finish.

NOTES:

- + All new construction as per 2018 IRC and 2018 IECC.
- + All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
- + Provide power and service requirements to equipment shown in the equipment schedule.

- ④.1 Concrete - Board Shuttered Concrete

- ④.2 Concrete - Round Pier

- ④.3 Concrete- Polished Floor

- ⑤.1 GWB, PTD. Level 4/5 finish.

- ⑤.2 Floor/ Wall Tile TBC

- ⑥.4 1-1/2\" Cedar Deck Boards (gapped 1/4\")

- ⑥.5 T&G Flooring/ Cladding to Match Decking

- ⑥.6 Millwork/ Doors - Marine Grade Plywood, Finish TBC.

DIMENSIONS:

All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:

Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

- ⑦.1 7/8\" Corrugated Roofing/ Wall Weathering Steel 20 ga. - Western States Metal Roofing, or other.

- ⑦.2 Flashing/ Dormer Cladding - 1/8\" Steel Plate and 18 ga. Weathering Steel flashing - Western States Metal Roofing, or other.

- ⑦.3 Hot Dipped Galvanized Metalwork Steel Plate, Guardrail - Linear Bar Grating- McNichols or other.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:

It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:

All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

S&S

SCOTT & SCOTT


604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

**Steamboat Springs
Alpine House**
Steamboat Springs, Co

A3.02

Building Sections

23 JUNE 2021



MATERIAL SCHEDULE

- | | | |
|--|---|---|
| ① Solid DF Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4" face with 1/8" shadow | ④ Concrete - Board Shuttered Concrete | ⑦ 7/8" Corrugated Roofing/ Wall Weathering Steel 20 ga. - Western States Metal Roofing, or other. |
| ② Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen | ⑤ Concrete - Round Pier | ⑧ Flashing/ Dormer Cladding - 1/8" Steel Plate and 18 ga. Weathering Steel flashing - Western States Metal Roofing, or other. |
| ③ Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel | ⑥ Concrete - Polished Floor | ⑨ Hot Dipped Galvanized Metalwork Steel Plate, Guardrail - Linear Bar Grating- McNichols or other. |
| ④ 18 ga. Clear Anodized Aluminum flashing or to match Window System. | ⑦ GWB, PTD. Level 4/5 finish. | |
| ⑤ Solid Wood Entry Doors - Copper Plate Exterior Finish. | ⑧ Floor/ Wall Tile TBC | |
| | ⑨ 1-1/2" Cedar Deck Boards (gapped 1/4") | |
| | ⑩ T&G Flooring/ Cladding to Match Decking | |
| | ⑪ Millwork/ Doors - Marine Grade Plywood, Finish TBC. | |

NOTES:

- + All new construction as per 2018 IRC and 2018 IECC.
- + All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
- + Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:

All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:

Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:

It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:

All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

S&S

SCOTT & SCOTT



604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

Steamboat Springs
Alpine House
Steamboat Springs, Co

A3.03

Building Sections

23 JUNE 2021



MATERIAL SCHEDULE

- | | | |
|--|---|---|
| ②.1 Solid DF Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4" face with 1/8" shadow | ④.1 Concrete - Board Shuttered Concrete | ⑦.1 7/8" Corrugated Roofing/ Wall Weathering Steel 20 ga. - Western States Metal Roofing, or other. |
| ②.2 Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen | ④.2 Concrete - Round Pier | ⑦.2 Flashing/ Dormer Cladding - 1/8" Steel Plate and 18 ga. Weathering Steel flashing - Western States Metal Roofing, or other. |
| ③.1 Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel | ④.3 Concrete- Polished Floor | ⑦.3 Hot Dipped Galvanized Metalwork Steel Plate, Guardrail - Linear Bar Grating- Monichols or other. |
| ③.2 18 ga. Clear Anodized Aluminum flashing or to match Window System. | ⑤.1 GWB, PTD. Level 4/5 finish. | |
| ③.3 Solid Wood Entry Doors - Copper Plate Exterior Finish. | ⑤.2 Floor/ Wall Tile TBC | |
| | ⑥.4 1-1/2" Cedar Deck Boards (gapped 1/4") | |
| | ⑥.5 T&G Flooring/ Cladding to Match Decking | |
| | ⑥.6 Millwork/ Doors - Marine Grade Plywood, Finish TBC. | |

NOTES:
+ All new construction as per 2018 IRC and 2018 IECC.
+ All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
+ Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

S&S

SCOTT & SCOTT


604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

**Steamboat Springs
Alpine House**
Steamboat Springs, Co

A3.04

Building Sections

23 JUNE 2021



MATERIAL SCHEDULE

- | | | |
|--|---|---|
| ②.1 Solid DF Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4" face with 1/8" shadow | ④.1 Concrete - Board Shuttered Concrete | ⑦.1 7/8" Corrugated Roofing/ Wall Weathering Steel 20 ga. - Western States Metal Roofing, or other. |
| ②.2 Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen | ④.2 Concrete - Round Pier | ⑦.2 Flashing/ Dormer Cladding - 1/8" Steel Plate and 18 ga. Weathering Steel flashing - Western States Metal Roofing, or other. |
| ③.1 Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel | ④.3 Concrete - Polished Floor | ⑦.3 Hot Dipped Galvanized Metalwork Steel Plate, Guardrail - Linear Bar Grating- McNichols or other. |
| ③.2 18 ga. Clear Anodized Aluminum flashing or to match Window System. | ⑤.1 GWB, PTD. Level 4/5 finish. | |
| ③.3 Solid Wood Entry Doors - Copper Plate Exterior Finish. | ⑤.2 Floor/ Wall Tile TBC | |
| | ⑥.4 1-1/2" Cedar Deck Boards (gapped 1/4") | |
| | ⑥.5 T&G Flooring/ Cladding to Match Decking | |
| | ⑥.6 Millwork/ Doors - Marine Grade Plywood, Finish TBC. | |

NOTES:

- + All new construction as per 2018 IRC and 2018 IECC.
- + All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
- + Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:

All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:

Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:

It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:

All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

S&S

SCOTT & SCOTT


604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

**Steamboat Springs
Alpine House**
Steamboat Springs, Co

A3.05

Building Sections

23 JUNE 2021



NOTES:
+ All new construction as per 2018 IRC and 2018 IECC.
+ All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
+ Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

S&S


SCOTT & SCOTT
604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3


Steamboat Springs
Alpine House
Steamboat Springs, Co

A4.01

Exterior Elevations

23 JUNE 2021





MATERIAL SCHEDULE

- ②.1 Solid DF Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4" face with 1/8" shadow
- ②.2 Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen
- ③.1 Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel
- ③.2 18 ga. Clear Anodized Aluminum flashing or to match Window System.
- ③.3 Solid Wood Entry Doors - Copper Plate Exterior Finish.
- ④.1 Concrete - Board Shuttered Concrete
- ④.2 Concrete - Round Pier
- ④.3 Concrete- Polished Floor
- ⑤.1 GWB, PTD. Level 4/5 finish.
- ⑤.2 Floor/ Wall Tile TBC
- ⑥.4 1-1/2" Cedar Deck Boards (gapped 1/4")
- ⑥.5 T&G Flooring/ Cladding to Match Decking
- ⑥.6 Millwork/ Doors - Marine Grade Plywood, Finish TBC.

NOTES:

- + All new construction as per 2018 IRC and 2018 IECC.
- + All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
- + Provide power and service requirements to equipment shown in the equipment schedule.

DIMENSIONS:

All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:

Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:

It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:

All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

S&S

SCOTT & SCOTT

604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3


**Steamboat Springs
Alpine House**

Steamboat Springs, Co

A4.03

Exterior Elevations

23 JUNE 2021



MATERIAL SCHEDULE

- ②.1 Solid DF Boards - C Clear or better; T&G Soffit & Wall Cladding - 3 1/4" face with 1/8" shadow
- ②.2 Solid DF - C Clear or better - Balcony Support and 2x6 Studs at Sauna Screen
- ③.1 Windows - U-30 as req'd/ Clear Anodized Aluminum or Color to Match Weathering Steel
- ③.2 18 ga. Clear Anodized Aluminum flashing or to match Window System.
- ③.3 Solid Wood Entry Doors - Copper Plate Exterior Finish.

NOTES:

- + All new construction as per 2018 IRC and 2018 IECC.
- + All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
- + Provide power and service requirements to equipment shown in the equipment schedule.

- ④.1 Concrete - Board Shuttered Concrete
- ④.2 Concrete - Round Pier
- ④.3 Concrete- Polished Floor
- ⑤.1 GWB, PTD. Level 4/5 finish.
- ⑤.2 Floor/ Wall Tile TBC
- ⑥.4 1-1/2" Cedar Deck Boards (gapped 1/4")
- ⑥.5 T&G Flooring/ Cladding to Match Decking
- ⑥.6 Millwork/ Doors - Marine Grade Plywood, Finish TBC.

DIMENSIONS:

All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:

Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.

- ⑦.1 7/8" Corrugated Roofing/ Wall Weathering Steel 20 ga. - Western States Metal Roofing, or other.
- ⑦.2 Flashing/ Dormer Cladding - 1/8" Steel Plate and 18 ga. Weathering Steel flashing - Western States Metal Roofing, or other.
- ⑦.3 Hot Dipped Galvanized Metalwork Steel Plate, Guardrail - Linear Bar Grating- McNichols or other.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:

It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:

All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.

S&S


SCOTT & SCOTT

604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

**Steamboat Springs
Alpine House**
Steamboat Springs, Co

A4.04

Exterior Elevations



NOTES:
+ All new construction as per 2018 IRC and 2018 IECC.
+ All device locations as shown in architectural drawings. If
Building regulations require alternate location it is to be approved
by Design Consultant prior to placement.
+ Provide power and service requirements to equipment shown in
the equipment schedule.

DIMENSIONS:
All dimensions must be verified on site. Do not scale off
drawings. Plans take precedent over elevations. In the
absence of dimensions, or if discrepancies exist,
consult Designer. All minimum dimensions are to
comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for
approval prior to manufacture of prefabricated elements
of the building.

DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to
seek prior written approval for materials and workmanship which
deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the
requirements of all authorities having jurisdiction over
the work. It is the Builder's responsibility to gain
necessary approval from all relevant Authorities.

Scott & Scott is registered in the Province of British
Columbia. All aspects of work completed outside of
British Columbia is conceptual in nature and where
required an Architect of record is to be engaged by
the client for the completion of work.

S&S

SCOTT & SCOTT

604 737 2541
299 19th AVENUE EAST
VANCOUVER CANADA
V5V1J3

Steamboat Springs
Alpine House
Steamboat Springs, Co



A4.05

Exterior Materials





08/24/2021




Steamboat Springs
Alpine House
Steamboat Springs, Co

A5.11R1


Wall Section

27 JULY 2021


08/24/2021



GA FILE NO. WP 3605	GENERIC	1 HOUR FIRE	30 to 34 STC SOUND
GYPSUM WALLBOARD, WOOD STUDS			
One layer 5/8" type X plain or predecorated gypsum wallboard, water-resistant gypsum backing board, or gypsum veneer base applied parallel or at right angles to each side of 2 x 4 wood studs 16" o.c. with 6d coated nails, 17/8" long, 0.0915" shank, 1/4" heads, 7" o.c. Joints of square edge, bevel edge or predecorated wallboard may be left exposed. Joints staggered 16" on opposite sides. (LOAD-BEARING)			
		Thickness: 47/16"	
		Approx. Weight: 7 psf	
		Fire Test:	UL R1319-4, -6, 6-17-52; UL R2717-39, 1-20-66; UL R3501-52, 3-15-66, UL Design U305; ULC Design W301
		Sound Test:	OR 64-8, 2-4-64



1 Unit 2 Window/ Door Elevations
1/4" = 1' (@24"x36" plot)



2 Sauna Window/ Door Elevations
1/4" = 1' (@24"x36" plot)

GENERAL NOTES:

1. The sizes indicated are rough openings, it is the Contractor's responsibility to determine finished frame sizes.
2. All window dimensions in this drawing to be verified in field prior to fabrication.
3. Provide window and door shop drawings for review prior to fabrication, showing all sizes, hardware types, and assembly details.
4. All windows and doors to meet 2018 IRC, 2018 IECC, and local requirements for security and tempered glazing locations.
5. TG indicates Tempered Glazing.
6. Refer to Floor Plans for door swing directions.
7. All windows and doors in this drawing are shown viewed from the outside unless otherwise indicated.
8. Operable windows are to open outward unless otherwise indicated.
9. Window exterior to be Clear anodized Aluminum, or color to match weathering steel.
10. Windows and Sliding Doors to have a maximum U-value of 0.30
11. Skylights to have a maximum U-value of 0.55

NOTES:

- + All new construction as per 2018 IRC and 2018 IECC.
- + All device locations as shown in architectural drawings. If Building regulations require alternate location it is to be approved by Design Consultant prior to placement.
- + Provide power and service requirements to equipment shown in the equipment schedule.


DIMENSIONS:
All dimensions must be verified on site. Do not scale off drawings. Plans take precedent over elevations. In the absence of dimensions, or if discrepancies exist, consult Designer. All minimum dimensions are to comply with the International Residential Code.

SHOP DRAWINGS:
Submit shop drawings to the Design Consultant and Engineer for approval prior to manufacture of prefabricated elements of the building.




DESIGN CONSULTANT REQUIREMENTS AND APPROVALS:
It is the Builder's responsibility to notify Design Consultant and to seek prior written approval for materials and workmanship which deviates from instructions provided by the Design Consultant.

AUTHORITIES' REQUIREMENTS AND APPROVALS:
All materials and workmanship must comply with the requirements of all authorities having jurisdiction over the work. It is the Builder's responsibility to gain necessary approval from all relevant Authorities.


Scott & Scott is registered in the Province of British Columbia. All aspects of work completed outside of British Columbia is conceptual in nature and where required an Architect of record is to be engaged by the client for the completion of work.



3 Garage Door Elevations
1/4" = 1' (@24"x36" plot)



4 Unit 1 Window/ Door Elevations
1/4" = 1' (@24"x36" plot)



Steamboat Springs
Alpine House
Steamboat Springs, Co

A9.00
Window Door Schedule

GENERAL

1. DESIGN LIVE LOADS: Snow=85psf, Floor=40psf, Wind 90mph (3 Second Gust), Seismic Zone B
2. RESPONSIBILITY: The contractor is responsible for cross referencing all plans and inspecting work placement at the site to assure that no omissions or discrepancies exist that might adversely affect construction or the integrity of the finished product. Job site and construction safety are not addressed in these plans and are the responsibility of the contractor. These responsibilities are industry standard.
3. These plans are intended to be in accordance with 2018 IBC and IRC codes. All construction to be in conformance with these codes.

FOUNDATION

1. Foundation designed in accordance with NWCC Site Specific Soils Report with a Maximum allowable soil bearing pressure = 3000 psf, 700 min. Proper authorization for use of the report or its recommendations are the responsibility of the owner.
2. We recommend the soils engineer verify during excavation (and before construction of any part of the foundation) that soil types and conditions match those described in the pit log(s) of the above mentioned soils report.
3. Remove topsoils, organic material, and any questionable material below pads and footers. All pads and footings exposed to frost must maintain the required 48" frost depth. Minimum pad thickness = 12". The footing elevations of this design are indicated in economical relation to architectural elements. Proper soil bearing and/or the soil report may require lower footings.
4. Drainage and grading details to divert surface drainage at least 10' away from the structure. Do not backfill against any foundation or retaining wall until all supporting floor and slab systems are in place and securely anchored, or other adequate wall support is provided.
5. Where exterior backfill rises above any adjacent floor, use granular free draining backfill from drain tile up. Exterior backfill may be native inorganic material where final grade is below lowest floor (UNO). Before placing finish topsoil, we recommend capping backfill with a Mirafi fabric under 12"-24" of water impermeable material (e.g. clay).
6. Provide 4" diameter perforated PVC drain tile in a 12" by 12" gravel envelope at lowest levels of and perimeter of excavation sloped a minimum of 1/8" per foot to an adequate daylighting drain. Provide cleanouts and screen end. Mirafi or other filter barriers will help prevent drain clogging. Test drain tile before and after backfilling.
7. All construction and materials to conform with ACI 318.
8. Reinforcing bar to be deformed 60 ksi steel (per ASTM A-615). Lap all rebar splices and corners 38 bar diameters minimum.
9. Concrete supplier to provide mixes that replace 20% of portland cement with recycled fly ash from local coal burning power plants.
10. Minimum concrete 28 day compressive strength = 3500psi for walls, footers, and pads, and 4000psi for slabs.
11. Concrete cover: Concrete cast against and permanently exposed to earth: footing, pad = 3". Concrete exposed to earth or weather: walls, slabs = 1.5"
12. Consolidate concrete per ACI 309. Cast in place concrete shall be poured continuously so as to prevent cold joints.
13. Provide 1/2" diameter by 10"min anchor bolts at 24" on center with an embedment of 7" to connect framing to foundation (UNO). Anchor bolts to be located not more than 12" from foundation corner (TYP). Use galvanized anchor bolts with pressure treated plates. Finish all concrete wall tops to within 1/8" of specified elevations.
14. Foundation insulation and waterproofing to be specified and installed in accordance with the above mentioned soils report, IRC, local codes, and accepted construction practice.
15. Do not use foam form systems without approval of Engineer.
16. Provide slab shrinkage reinforcement of 6x6xW1.4 welded wire mesh with 2" laps, or a poly fiber mesh per manufacturer's instructions.
17. Slab surfaces to be left free from trowel marks, uniform in appearance, and with a surface plane tolerance not exceeding 1/8" in 10'0" when tested with a 10' straightedge.
18. Provide 1" deep tooled (or cut) control joints at approximately 10' on center in each direction.
19. Provide 1/2" expansion joint material at all slab to wall, footing, or column interfaces. Provide a 6 mil poly barrier under all interior slabs for moisture protection and as a bond breaker. Provide an approved hardener and sealer to the surface of all slabs.
20. If foundation is to sit through winter without complete framing, we recommend the building achieve enough backfill, framing, and floor sheathing to protect foundation bearing soils from moisture accumulation and frost heave.

WOOD FRAMING


1. Framing plans show structural requirements only. Additional members may be required for blocking, nailers and code requirements.
2. Use Douglas Fir or Hem Fir "stud grade" (S4S) 2x4/2x6 at 16"o.c. for all wall studs(UNO). Use DF#2 (S4S) or better for all multi-stud posts, joists, rafters, headers, posts, beams and plates. Sill plates and any other lumber in direct contact with concrete- California Foundation Grade Redwood or Species Group B Pressure Treated Lumber. Use galvanized anchor bolts with pressure treated plates.
3. Glulams (GL)- 24F-V8 manufactured in accordance with AITC 117-84, fb=2400psi. OK to use 24F-V4 for simple span applications only. All Glulams used in exterior applications must be sealed and protected from moisture with an appropriate preservative.
4. Laminated Veneer Lumber (LVL)- manufactured in accordance with APA criteria. fb=2600psi.(or X-Beam Equiv.)
5. Timbers- Douglas Fir (DF) Grade specified on plan- #1 Fb>1300psi, #2 Fb>850psi.
6. Exterior Wall Ply- 7/16" OSB APA rated 24/16 min with 8d's @6"oc edge, 12" oc field. Manufactured in conformance with APA PS 1-83. Floor Ply- 3/4" T&G OSB APA rated 24/0 minimum, 8d's @6"oc edge, 10"oc field. Glue to joists. Roof Ply - 5/8" OSB APA rated 40/20 minimum, 8d's @6"oc edge, 12"oc field. OK to use 1 1/2" Zip wall system in lieu of 7/16" OSB. 1 1/2" Zip wall system nailing: 16d sinkers (0.131" dia.) 3"oc Edge and 12"oc Field.
7. Roof Trusses- 85 psf snow load, 24"oc. Truss design and fabrication by others. No drop top gable truss adjacent to scissor truss without approval of Engineer.
8. Rigid insulation decking- 9 1/2" Insulium or equal. Attach with 10 1/2" deck screws @12"oc each way.
9. Maintain 6" clearance between untreated wood or siding and soils at finish grade.
10. 1/2" Sheath 100% all exterior frame. Ply to lap floor rim, top plates and sill plate.
11. All floor and roof plywood place with 8' dimension perpendicular to framing with end joints staggered.
12. Typical headers unless noted otherwise on plans: All load bearing headers in 2x6 wall (2)2x10; in 2x4 wall (2)2x10, (UNO).
13. Provide 2 studs under each end of all load bearing beams or headers >38"(UNO). (1)King stud min.(UNO)
14. Multiple stud posts anticipate 2'min wall sections preventing buckling. Verify new adjacent openings with engineer.
15. Studs removed for doors and windows shall be placed equally at the end of headers, up to (2)king (full height) studs each end.
16. Posts to stack over equal below (UNO). Trusses spanning >18' to stack over studs below (UNO). Provide end joist where studs above do not stack over studs below.
17. Solid block all bearing walls and posts for continuity to foundation.
18. Block all trusses, outlookers, rafters and joists at all bearing points.
19. Where full height foundation wall parallel to joists, block 1st joist space @24"oc.
20. Wall studs to be continuous from floor to floor, or floor to roof. Balloon frame all gable walls. Provide firestop blocking at 10' max intervals in any wall with studs over 10' height.
21. Connect joists to blocking with a minimum of (2)10d nails and connect joists to plate or beam below with a minimum of (3)10d toenails. Connect rim to plate below with 10d toenails @6"oc.
22. Nail exterior wall sole plate to joists below with (3)10d and to blocking, rim or end joist with 10d's @4"oc.
23. Connect all TJI rafters to blocking with (3)10d nails, and to plate or beam below with (4) 10d nails. Provide beveled bearing plate at interior bearing, birdsmouth cut at exterior bearing. Provide beveled web stiffeners at birdsmouth and regular web stiffeners at interior bearing. Strip TJI rafters across ridge with LSTA 18. Connect blocking to plate below with (3)16d toenails minimum. Refer to TJI Specifiers Guide roof details.
24. Connect all 2x rafters to blocking with (3)10d nails, and to plate or beam below with (4) 10d nails. Provide birdsmouth or seat cut bearing at all beams and wall plates UNO.
25. Connect common trusses to all bearing points with Simpson H2.5 connectors (UNO). Scissor trusses connect one end with Simpson TC26. Connect to blocking with (3)16d nails.
26. Ventilate roof framing per local codes.
27. Nailing, blocking, and all other construction details per 2018 IBC and IRC, such as Table R602.3(1). (UNO)
28. All connector callouts to be Simpson Strong-Tie or equal by Simpson Strong-Tie Company, Inc. Install per manufacturer's instructions.
29. TJI and MicroLam (ML) are products by Trus Joist MacMillan. Install per manufacturer's instructions.
30. Steel beams pack out per detail where noted. Where not otherwise noted, provide 2x full width nailer on top with 1/2" Thru bolt at 24"oc staggered side to side of beam web. Where frame wall pocket prevents beam rolling, connect steel beam base to post or beam below with (2)5/8" Lags. Otherwise connect beam to bearing via welded "ears" i.e., flanges similar to Simpson CC. Provide 1/4" fitted web stiffeners at steel beam point loads and bearing points (UNO).
31. If slab on grade is placed on expansive soils (i.e. minimum soil bearing required, see foundation note 1 above) all portion walls framed on slab to be slip jointed per soils report.

STRUCTURAL STEEL

1. All structural steel shall conform to ASTM specifications A36 except pipe columns which shall conform to ASTM A53 Grade B, and steel tube columns which shall conform to ASTM A500 Grade B. Steel to steel member connection bolts shall be A325 steel and miscellaneous wood embedded items shall be A36 steel.
2. Steel column base plates shall bear evenly to concrete below via 4000 psi non shrink grout.
3. Minimum welds to be per AWS and/or AWS, but not less than 3/16" continuous fillet unless otherwise noted. Welding quality control shall be per AWS. All welders shall have evidence of passing the American Welding Society Standard Qualifications Test as detailed in AWS D1.1.

TYPICAL ABBREVIATIONS

BOCB = bottom of grade beam
BRG = bearing
CL = center line
E.E. = each end
E.M. = each member
E.S. = each side
E.W. = each way
GL = Glulam
HDR = header
LVL = Laminated veneer lumber
OC = on center
OF = overframe
OH = overhang
OPP SIM = opposite similar
PL = plate
PT = pressure treated
PSL = parallum
R.O. = Rough opening
SOG = slab on grade
STR = Structural
TOBL = top of brick ledge
TOF = top of footing
TOGB = top of grade beam
TOS = top of slab
TOSB = top of steel beam
TOW = top of wall
TYP = typical
UNO = Unless noted otherwise
WS = steel web stiffeners



ENGINEERING DESIGNWORKS, INC.
1855 Skyline Square, Unit 12C
Steamboat Springs, CO 80487
P.O. Box 775729
Steamboat Springs, CO 80477
cnd@engineeringdesignworks.com
PHONE: (970)879-4890

These plans are intended to be used by the original owner and are the property of Engineering Designworks, Inc. S108000 are not to be reproduced, copied, or used in any way without the written consent of Engineering Designworks, Inc.

DATE: 6-23-2021
JOB #: 202153
DRAWN: EDW
ENG: CW
REVISED: ----
REVISED: ----

ISSUE: PERMIT

FOUNDATION PLAN for the proposed:
STEAMBOAT SPRINGS ALPINE HOUSE
1859 RIVER QUEEN LANE
STEAMBOAT SPRINGS, COLORADO

08/24/2021
















ENGINEERING DESIGNWORKS, INC.
1855 Sky Tower Square, Unit 12C
Steamboat Springs, CO 80487
P.O. Box 775729
Steamboat Springs, CO 80477
cud@engineeringdesignworks.com
PHONE: (970) 879-4890

DATE: 6-23-2021
JOB #: 202153
DRAWN: EDW
ENG: CW
REVISED: :
REVISED: :

ISSUE: PERMIT

DETAILS for the proposed:
STEAMBOAT SPRINGS ALPINE HOUSE
1859 RIVER QUEEN LANE
STEAMBOAT SPRINGS, COLORADO





These plans are intended for use by the original owner at the indicated site only. Beyond this intended use these plans are the property of Engineering Designworks, Inc. \$1000.00 charge for copying or other use of this page or its designs, without written authorization.

Steamboat Springs, CO 80487
P.O. Box 775729
Steamboat Springs, CO 80477
eurl@engineeringdesignworks.com
PHONE: (970)879-4890

-23-2021
 02153
 N: EDW
 W
 D: ----
 D: ----

PERMIT

STEAMBOAT SPRINGS ALPINE HOUSE
1859 RIVER QUEEN LANE
STEAMBOAT SPRINGS, COLORADO

S3




ENGINEERING DESIGNWORKS, INC.
1855 Sky Tower Square, Unit E2C
Steamboat Springs, CO 80487
P.O. Box 775729
Steamboat Springs, CO 80477
enr@engineeringdesignworks.com
PHONE: (970) 879-4890

These plans are intended for use by the original owner at the site. No other use, reproduction, or distribution of these plans is permitted without the written consent of Engineering Designworks, Inc. © 2021


DATE: 6-23-2021
JOB #: 202153
DRAWN: EDW
ENG: CW
REVISED: ---
REVISED: ---


ISSUE: PERMIT

UPPER FLOOR FRAMING for the proposed:
STEAMBOAT SPRINGS ALPINE HOUSE
1859 RIVER QUEEN LANE
STEAMBOAT SPRINGS, COLORADO



1
S4 UPPER FLOOR FRAMING
Scale: 1/4"=1'-0"







DATE: 6-23-2021
JOB #: 202153
DRAWN: EDW
ENG: CW
REVISED: ----
REVISED: ----

ISSUE: PERMIT

ROOF FRAMING PLAN for the proposed:
STEAMBOAT SPRINGS ALPINE HOUSE
1859 RIVER QUEEN LANE
STEAMBOAT SPRINGS, COLORADO

PAGE
S5
#202153 of 5





GENERAL NOTES:

- OWNER: SUNSHINE STEAMBOAT, LLC
- FIELD SURVEYING COMPLETED BY LANDMARK, INC.
- TOPOGRAPHIC DATA GENERATED FROM 2018 LIDAR DATA.
- PROPERTY CORNERS WERE FOUND AS INDICATED HEREON PER FIELD SURVEY.
- NO BENCHMARK HAS BEEN SET.
- DIMENSIONS ARE IN FEET UNLESS OTHERWISE NOTED.
- REFER TO GEO-TECHNICAL ENGINEERING STUDY AND REPORT FOR ALL GRADING, DRAINAGE, AND FINAL STABILIZATION RECOMMENDATIONS AND SPECIFICATIONS.
- ALL FINISHED BARE GROUND SURFACES SHALL RECEIVE A MINIMUM OF 6" OF NATIVE TOPSOIL FOR FINAL GRADING AND SHALL BE RELATIVELY FREE OF STONES, CLODS, STICKS, AND OTHER DEBRIS.
- ALL FINISHED GROUND SHALL BE PROPERLY SEEDED, FERTILIZED, MULCHED AND VEGETATION ESTABLISHED WITHIN ONE CONSTRUCTION SEASON.
- ALL DETAILS PROVIDED SHALL BE ADHERED TO UNLESS OTHERWISE APPROVED BY CIVIL ENGINEER OR RECORD.
- CONTRACTOR SHALL VERIFY THE LOCATION OF ALL UTILITIES. CALL THE UTILITY NOTIFICATION CENTER OF COLORADO (UNCC) AT 1-800-922-1987 AND ANY NECESSARY PRIVATE UTILITY TO PERFORM LOCATES PRIOR TO CONDUCTING ANY SITE WORK.
- SEE SHEET 2 FOR UTILITY INSTALLATION NOTES AND SPECIFICATIONS.

ANNOTATIONS:

- BOW BOTTOM OF WALL
- CL CENTERLINE
- COMMS COMMUNICATIONS
- EL ELEVATION
- ELEC ELECTRICAL
- EDA EDGE OF ASPHALT
- EX EXISTING
- FES FINISHED FLOOR ELEVATION
- LF LINEAR FEET/FOOT
- LPS LOW PRESSURE SEWER
- INV INVERT
- P/A PLANTING AREA
- R RADIUS
- ROW RIGHT OF WAY
- PR PROPOSED
- TOW TOP OF WALL
- TYP TYPICAL

LEGEND

- PROPERTY BOUNDARY
- ADJACENT PROPERTY BOUNDARY
- EXISTING EASEMENT
- BUILDING ENVELOPE
- EXISTING 2 FT CONTOUR
- EXISTING 10 FT CONTOUR
- PROPOSED 2 FT CONTOUR
- PROPOSED 10 FT CONTOUR
- EXISTING WATER LINE
- CENTER LINE OF DITCH/SWALE
- EXISTING EDGE OF GRAVEL
- EXISTING CULVERT
- PROPOSED ROCK PAVERS
- PROPOSED ASPHALT DRIVEWAY
- RPA RECEPTION AREA
- PROPOSED CONCRETE
- FLOW ARROW
- PROPOSED 1" WATER SERVICE LINE
- PROPOSED LPS SERVICE LINE
- PR ELECTRICAL SERVICE LINE
- PR COMBINED ELEC AND COMMS
- WATER/SEWER SERVICE MARKERS
- ELECTRICAL & COMMS REESTALS
- SPOT GRADE
- PROPOSED TREES & SHRUBS
- PROPOSED HOUSE OUTLINE
- PROPOSED PATIO OUTLINE
- PROPOSED DECK OUTLINE

PROJECT TOTAL EARTHWORK QUANTITIES:


AREA OF DISTURBANCE	10,000	SQ. FT.
TOPSOIL STRIPPING	200	CU. YDS.
TOTAL CUT	240	CU. YDS.
TOTAL FILL	450	CU. YDS.
NET (FILL)	210	CU. YDS.

MATERIAL QUANTITIES

DRIVEWAY, CLASS 1/2 SUB-BASE	33	CU. YDS.
DRIVEWAY, CLASS 6 ROAD BASE	17	CU. YDS.
DRIVEWAY, HOT-MIX ASPHALT	17	CU. YDS.
STONE PAVERS & STAIRS	25	CU. YDS.
STONE PAVES SUB-BASE	25	CU. YDS.

NOTES:

- TOPSOIL STRIPPING VOLUME ASSUMES AN AVERAGE TOPSOIL DEPTH OF 1.0 FEET. ACTUAL TOPSOIL DEPTH MAY VARY ACROSS THE ENTIRE AREA OF DISTURBANCE.
- THE TOTAL CUT VOLUME INCLUDES TOPSOIL STRIPPING.
- A FILL FACTOR OF 1.10 WAS USED FOR CUT-FILL VOLUME CALCULATIONS.



RCRBD Record Set
T.A.

08/24/2021

B-21-755

LOT 3, EAGLE'S VISTA
SUBDIVISION
1859 RIVER QUEEN LANE
STEAMBOAT SPRINGS, CO 80487

Horizontal Scale



Contour Interval = 2 ft


DATE: 6-15-2021
JOB #: 1998-001
DRAWN BY: JLW
DESIGN BY: JLW
REVIEW BY: RL

SITE PLAN &
PROFILE

DRAWING:

SHEET #

1



Checklist #1 for Building Permit Applications



City of
Steamboat Springs

**RCRBD Record Set
T.A.**

08/24/2021

This list is provided to help speed up your plan review by making sure the basic required information is shown on your submittal. **Plans will not be accepted if the required information is not shown or if an item marked as "N/A" is deemed to be applicable for this type of project.** Additional information may be required based on site-specific conditions or to respond to City development review comments. Please call the appropriate City department if you have any questions related to a specific requirement. The applicant is required to review and sign the affidavit on the bottom of this checklist, accepting responsibility for any incomplete submittal and thus possible result of a delayed review time. For additional information regarding a particular requirement, see the Routt County Building Department website.

City Water/Sewer- 871-8200

Fire Prevention- 879-7170

Engineering- 871-8200

Planning- 871-8258

Applicant Name:

Bradley Bartels
(Please Print)

Permit #: TB - 21 - 755

Important: Any project required to submit Civil Construction Plans and/or Documents to Public Works must include the approved Civil Construction Plans (w/ approval block signed by departments) as part of the Building Permit submittal. See development approval conditions or contact Planning staff. If the Building Department verifies this has been attached, then only the CSMP and SWMP requirements need be verified.

	Yes	No
Building Permit has associated grading and drainage Civil Construction Documents on record with Public Works?		<input checked="" type="checkbox"/>

Site Plan Information	Check	
	Yes	No
North Arrow Indicator, Scale, and Benchmark	<input checked="" type="checkbox"/>	
Legal Description, Property Address, Owner's Name, Lot Size in Square Feet	<input checked="" type="checkbox"/>	
Existing and Proposed Topography: Contour Lines at 2 foot Intervals, Source of Topography	<input checked="" type="checkbox"/>	
Location and Dimensions of all Roads on or Adjacent to the Subject Property. Show Location of Adjacent and Opposing Driveways.	<input checked="" type="checkbox"/>	
Location and Dimensions of Right-of-Way and all Easements- No Landscaping or Structural Improvements in the ROW or Easement	<input checked="" type="checkbox"/>	
Location and Dimension of Lot Lines, Building Envelopes and Setbacks	<input checked="" type="checkbox"/>	
Location and Dimensions of all Buildings on the Lot (Existing and Proposed). Include decks, patios, roof overhangs, etc.	<input checked="" type="checkbox"/>	
Building and Garage Finish Floor Elevation	<input checked="" type="checkbox"/>	
Alignment and Pipe Type of <u>ALL</u> Existing and Proposed Utilities, Including Meters (Water, Sewer, Gas). The Plan must clearly identify changes in bury depth to all existing utilities.	<input checked="" type="checkbox"/>	
Show <u>ALL</u> Above Surface Public Appurtenances Identified in	<input checked="" type="checkbox"/>	

Relationship to any Proposed Improvement (i.e. Fire hydrants)	✓	
Driveway Location, Width, Grade. Size and Length of any Culverts.	✓	
Location and Dimensions of Sidewalks, Parking Areas, and Paving	✓	
Existing Water Bodies, Drainages, Floodplain (limit and elevation), or Wetland Areas	✓	
Existing and Proposed Storm Water Systems (swales, ditches, culverts, etc.); Arrow showing proposed drainage direction.	✓	
Existing and Proposed Culverts w/ Invert Elevations, Size, and Flared End Sections or Headwalls Indicated	✓	
Extent of Soil Disturbance and Phasing Plan; Show all proposed Erosion & Sedimentation Control Measures; Plans should indicate the total expected disturbed area in acres (to include all excavation, soil stockpile, and project access areas)	✓	
Details for any Permanent Storm Water Quality feature (i.e. % slope for grass buffers, level spreader designs, grass swale cross-sections, etc.)	✓	
Add Note: All Disturbed Areas to be Re-vegetated	✓	
Location and Elevations (top and bottom) of any Retaining Walls; Provide a Cross-Section Design with Engineer's Stamp for any Retaining Wall greater than 4 feet.	✓	
Floor Area Ratio Calculations		

Building Plan Information

Existing and Finished Grades on Building Elevation Drawings- Including Building Height(s).	✓	
Provide a Detailed Code Analysis- Contact Fire Prevention w/ Questions	✓	
Soils Report- See RCBD informational materials for when required.	✓	

Stormwater Management Plan/Construction Site Management Plan


Construction Site Management Plan (CSMP)- see additional checklist on City of Steamboat Springs Engineering documents website	
Stormwater Management Plan (SWMP) if area of disturbance is greater than 1 acre - see additional checklist on City of Steamboat Springs Engineering documents website	

Historic Preservation

Exterior work on a property that is 50 years or older and may be eligible to an historic register will be reviewed by the Historic Preservation Commission. To find out if the property is eligible contact the Historic Preservation Division at 970-871-8258.	✓	
Staff Review By:		

I Bradley Bartels accept responsibility for the accuracy and completeness of the contents of this Building Permit application and accept responsibility for any associated delays in City review due to incompleteness.


Applicant:



Phone #: 970-846-8026

(Applicant Signature)

2/19/2018



Checklist #2 for Building Permit Applications



City of
Steamboat Springs

RCRBD Record Set
T.A.

08/24/2021

This list is provided to help speed up your plan review by making sure the basic required information is shown on your submittal. **Plans will not be accepted if the required information is not shown or if an item marked as "N/A" is deemed to be applicable for this type of project.** Additional information may be required based on site specific conditions or to respond to City development review comments. Please call the appropriate City department if you have any questions related to a specific requirement. The applicant is required to review and sign the affidavit on the bottom of this checklist, accepting responsibility for any incomplete submittal and thus possible result of a delayed review time. For additional information regarding a particular requirement, see the Routt County Building Department website.

City Water/Sewer- 871-8200

Fire Prevention- 879-7170

Engineering- 871-8200

Planning- 871-8258

Applicant Name:

Bradley Bardels
(Please Print)

Permit #: TB - 21 - 755

Site Plan Information	Check	
	Yes	No
Existing Conditions and Proposed Conditions Site Plan- can be printed off http://maps.steamboatsprings.net/ss/map.aspx for certain permits.	✓	
North Arrow Indicator and Scale	✓	
Legal Description, Property Address, Owner's Name, Lot Size in Square Feet	✓	
Existing and Proposed Topography: Contour Lines at 2 foot Intervals, indicated source of topography information - applicable if any work is proposed outside the existing building footprint.	✓	
Location and Dimensions of all Roads on or Adjacent to the Subject Property. Show Location of Adjacent and Opposing Driveways.	✓	
Location and Dimensions of Right-of-Way and all Easements- No Landscaping or Structural Improvements in the ROW or Easement	✓	
Location and Dimension of Lot Lines, Building Envelopes and Setbacks	✓	
Location and Dimensions of all Buildings on the Lot (Existing and Proposed). Include Decks, Patios, Roof overhangs, etc.	✓	
Building and Garage Finish Floor Elevation	✓	
Alignment and Pipe Type of <u>ALL</u> Existing and Proposed Utilities, Including Meters (Water, Sewer, Gas).	✓	
Show <u>ALL</u> Above Surface Public Appurtenances Identified in Relationship to any Proposed Improvement (i.e. Fire hydrants)	✓	
Location and Dimensions of Sidewalks, Parking Areas, and Paving impacted by scope of work	✓	
Existing and Proposed Storm Water Systems Impacted by Work (swales, ditches, culverts, etc.); Arrow showing proposed drainage direction.	✓	
Existing Water Bodies, Drainages, Floodplain (limit and elevation), or Wetland Areas impacted by scope of work	✓	
Location and Elevations (top and bottom) of any Retaining Walls;	✓	

2/19/2018

Provide a Cross-Section Design with Engineer's Stamp for any Retaining Wall greater than 4 feet.	<input checked="" type="checkbox"/>	
Floor Area Ratio Calculations	<input checked="" type="checkbox"/>	


Building Plan Information

Existing and Finished Grades on Building Elevation Drawings- Including Building Height(s).	<input checked="" type="checkbox"/>	
Provide Code Information- Contact Fire Prevention w/ Questions	<input checked="" type="checkbox"/>	

Historic Preservation

Exterior work on a property that is 50 years or older and may be eligible to an historic register will be reviewed by the Historic Preservation Commission. To find out if the property is eligible contact the Historic Preservation Division at 970-871-8258.	<input checked="" type="checkbox"/>	
Staff Review By:		

I Bradley Barfels accept responsibility for the accuracy and completeness of the contents of this Building Permit application and accept responsibility for any associated delays in City review due to incompleteness.

Applicant : 

Phone #: 970.846.8026

(Applicant Signature)

Construction Site Management Plan Checklist *B-21-755*

08/24/2021

Prior to the approval of a building/ROW permit, any commercial, multi-family, or applicable single-family/duplex project must complete an approved Construction Site Management Plan (CSMP). Below are the required items to be included in the CSMP. Please check "yes" if the item is included, "no" if it is not, and "N/A" if not-applicable. Please provide an explanation for any "No" answers at the bottom of the checklist.

Project Name: *Steamboat Springs Alpine House* Date: *7-4-21*

Estimated Construction Start Date: *8-15-21* End Date: *8-15-22*

Individual responsible for CSMP monitoring and compliance

Name: *Bradley Bardels* Phone # (local): *970-846-8026*

	Yes	No	N/A
1. General			
a. CSMP is shown on the proposed site plan	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
b. Schedule Pre-Construction Meeting (required only for commercial, industrial, and multifamily projects)	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
c. Right of Way permit (i.e. work or obstruction within ROW). If required, describe below and include estimated start and stop dates.	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
2. Erosion and Sedimentation Control Plan showing			
a. Topographic Information – including sufficient detail to characterize the site	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
b. Areas and extent of soil disturbance (show any phasing)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
c. Location of all on site and adjacent water bodies, wetlands, drainages, and storm water systems	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
d. Vehicle tracking control measures (vehicle track pad, vehicle wash station, etc.)	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
e. Inlet protection	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
f. Perimeter control measures (BMPs)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
g. Standard details for all proposed control measures	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3. Site Construction Facilities (Identify the following):			
a. Staging areas	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
b. Stockpile areas	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
c. Dumpsters and trash receptacles	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
d. Material recycling (wood, metal, plastics, etc.)	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
e. Sanitary facilities	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
f. Loading/Unloading areas	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
g. Trailers and field offices (show access)	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
4. Parking:			
a. Location and number of onsite and any offsite stabilized parking areas	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
b. Is project located downtown or at ski resort base area? If so, describe below where contractor parking will occur: <i>on site & on cul de sac</i>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>


**SUBSOIL AND FOUNDATION INVESTIGATION
LOCKHART SUBDIVISION
RIVER QUEEN LANE
STEAMBOAT SPRINGS, COLORADO**

**RCRBD Record Set
T.A.**

07/16/2021

Prepared by

NWCC, Inc.
2580 Copper Ridge Drive
Steamboat Springs, CO 80487



Prepared for

Kokee Kokee, LLC
Ty Lockhart
830 Lincoln Avenue
Steamboat Springs, CO 80847

NWCC Project NO. 17-10640

September 5, 2017

TABLE OF CONTENTS

1.0	CONCLUSIONS.....	1
2.0	PURPOSE AND SCOPE OF WORK.....	1
3.0	PROPOSED CONSTRUCTION.....	1
4.0	SITE CONDITIONS.....	1
5.0	FIELD INVESTIGATION.....	2
6.0	LABORATORY INVESTIGATION.....	2
7.0	SUBSURFACE CONDITONS.....	2
8.0	FOUNDATION RECOMMENDATIONS.....	3
9.0	FLOOR SLAB RECOMMENDATIONS.....	4
10.0	PERIMETER DRAINAGE SYSTEM RECOMMENDATIONS.....	6
11.0	FOUNDATION WALL AND RETAINING STRUCTURE RECOMMENDATIONS.....	6
12.0	SITE DRAINAGE RECOMMENDATIONS.....	7
13.0	SITE GRADING RECOMMENDATIONS.....	8
14.0	PAVEMENT RECOMMENDATIONS.....	8
15.0	LIMITATIONS.....	10

List of Figures, Tables and Appendices.

Figure #1	Vicinity Map
Figure #2	Site Plan/Test Pit Locations
Figures #3 & #4	Logs of Exploratory Test Pits with Legend and Notes
Figures #5 - #7	Swell-Consolidation Test Results
Figure #8	Bearing Capacity Chart
Figure #9	Hung Partition Wall Detail
Figure #10	Perimeter/Underdrain Detail
Table 1	Summary of Laboratory Test Results

1.0 CONCLUSIONS

Based on results of the field and laboratory investigations, NWCC, Inc. (NWCC) recommends the proposed single-family residences and garages to be constructed within this subdivision be founded on footings placed on the natural sands and clays and/or natural sands and gravels encountered beneath the existing fill materials and the topsoil and organic materials.

2.0 PURPOSE AND SCOPE OF WORK

This report presents the results of the Subsoil and Foundation Investigation completed for the Lockhart Subdivision to be constructed within a vacant parcel of land located at the southwest end of River Queen Lane in Steamboat Springs, Colorado. The approximate location of the project site is shown in Figure #1.

The scope of our work included obtaining data from a visual inspection of the site; the excavation of seven (7) test pits; sampling of the soils and the laboratory testing of the samples obtained. This report summarizes the results of the field investigation and the laboratory test results, as well as our recommendations for foundation design, floor slabs, foundation walls, site grading and pavement sections based on the proposed construction and the subsurface conditions encountered.

3.0 PROPOSED CONSTRUCTION

NWCC understands the proposed construction will consist of six (6) single family residences within the subdivision. The lot sizes will range from 0.23 to 0.48 acres in size. NWCC has assumed the residences will consist of 1 to 2 story wood framed structures constructed with attached garages and walkout basement levels. NWCC has assumed the lower levels of the residences and garages will be constructed with concrete slab-on-grade floor systems. We have assumed the loads generated by the proposed building structures will be variable and range from light to moderate, typical of this type of residential construction.

Some overlot site grading, roadway and utility construction will be required. The majority of the grading will occur at the end of the existing cul-de-sac; at the west end of the property for the water quality detention pad; and cut and fill placement within a majority of the lot entrances. NWCC has assumed that the remaining cuts and fills constructed within each of the individual lots will be on the order of 5 to 15 feet or less to bring the sites to the finish grades.

4.0 SITE CONDITIONS

The project site is located at the southwest end of River Queen Lane in Steamboat Springs, Colorado. The site is bordered on the north, south and west by developed single and multi-family homes and on the east by existing townhomes.

A majority of the site consists of vacant, undisturbed land that is vegetated with native grasses, weeds, scrub oaks and sage brush. Previous site grading, which appears to consist of fill placement on the order of 5 to 10 feet in depth, has occurred at and around the existing cul-de-sac.

The topography of the project site is variable and the central portion of the lot, where the road and pond will be constructed, sits on a ridgeline that slopes gently to strongly down to the west. The remainder of the property, proposed building lots and greenbelt area, generally slope moderately to steeply down to the south, southwest and northwest at 5 to 25 percent. Steeper natural slopes, greater than 30%, are situated along the southern and northern edges of the property. A maximum elevation difference of approximately 25 to 60 feet appears to exist at each of the lots.

5.0 FIELD INVESTIGATION

The field investigation for this project was conducted on August 18, 2017. Seven (7) test pits were advanced at the approximate locations shown in Figure #2. The test pits were excavated with a PC 138 trackhoe. The test pits were logged and samples were obtained at the time of excavation by an engineer from NWCC. Graphic logs of the exploratory test pits are shown in Figure #3 and #4 along with the associated Legend and Notes.

6.0 LABORATORY INVESTIGATION

Samples obtained from the test pits were examined and classified in the laboratory by the project engineer. Laboratory testing included standard index property tests including natural densities and moisture contents, dry unit weights, grain size analyses and liquid and plastic limits. Swell-consolidation testing was also conducted on relatively undisturbed samples of the natural sands and clays. Swell-consolidation test results are shown in Figures #5 to #7 and the results are discussed in the following section. The results of the laboratory testing are summarized in the Table #1 that follows the figures. Laboratory testing was conducted in general accordance with applicable ASTM specifications.

7.0 SUBSURFACE CONDITIONS

The subsurface conditions encountered in the test pits excavated across the proposed subdivision were highly variable and generally consisted of a layer of natural topsoil and organic materials or existing fill materials overlying natural sands and clays or sands and gravels to the maximum depth investigated, 12 feet beneath existing ground surface (bgs).

Natural topsoil and organic materials were encountered at the ground surface or beneath the existing fill materials in all of the test pits. The layers of topsoil and organic materials were approximately 1 ½ to 3 feet in thickness. The natural topsoil and organic materials were silty dry to moist and dark brown to black in color.

Sand and gravel fill materials were encountered at the ground surface in the central portion of the site (Test Pits 3 and 4) and beneath the proposed roadway and pond. The fill materials ranged from 4 ½ to 9 feet in thickness. The sand and gravel fill materials were silty to clayey, fine to coarse grained with cobbles and boulders, non to very low plastic, medium dense, slightly moist and brown in color. Samples of the fill materials classified as SM and GM soils in accordance with the Unified Soil Classification System (USCS).

Natural sands and clays were encountered below the natural topsoil and organic material and natural sands and gravels in all but two of the test pits. The sands and clays were fine to coarse grained with gravels, low plastic, very stiff to dense, moist to slightly moist and brown in color. Samples of the natural sands and clays classified as SC to CL soils in accordance with the USCS.

Sands and gravels were also encountered below the natural topsoil and organic materials and existing fill materials. The sands and gravels were clayey, fine to coarse grained with cobbles and boulders, low plastic, dense, dry to moist and brown to gray in color.

Swell-consolidation testing conducted on relatively undisturbed samples of the natural sands and clays indicate that the materials tested will exhibit a low swell potential when wetted under a constant load. The swell-consolidation test results are shown in Figures #5 through #7, and all of the other test results are summarized in the associated Table 1.

Groundwater seepage was not encountered in any of the test pits at the time of excavation and no signs of a seasonal high groundwater table were observed. It should be noted that the groundwater conditions at this site can be expected to fluctuate with precipitation and seasonal runoff.

Based on the subsurface conditions encountered at the site, the laboratory test results and our review of the available literature, NWCC recommends that a Site Class C be used for the foundation designs in accordance with Table 20.3-1 in Chapter 20 of ASCE 7-10.

8.0 FOUNDATION RECOMMENDATIONS

Based on the subsurface conditions encountered in the test pits, the results of the field and laboratory investigations and our assumptions regarding the proposed building construction, NWCC believes an economically feasible and safe type of foundation system is spread footings or individual pads with grade beams founded on the natural sand and clays and/or sands and gravels encountered below the topsoil and organic materials and any existing fill materials. The precautions and recommendations itemized below will not prevent the movement beneath the foundation if the underlying sands and clays swell. However, they should reduce the amount of differential movement beneath the foundation system.

- 1) Footings placed on the undisturbed natural sands and clays and/or sands and gravels should be designed using an allowable soil bearing pressure of 3,000 psf. Based on the swell-potential of

the natural sands and clays, the footings should also be designed for a minimum dead load pressure of at least 700 psf. Increasing minimum dead load pressures will help reduce differential foundation movement if the sands and clays become wetted and swell.

- 2) Footings or pad sizes should be computed using the above soil pressures and placed on the natural undisturbed sands and clays and/or sands and gravels found beneath the existing topsoil and fill materials and any fill materials.
- 3) Any topsoil, as well as any existing fill materials or loose and soft natural soils encountered within the foundation excavations should be removed and the excavations extended to competent natural soils prior to concrete placement. The footings may have to be narrow or interrupted to maintain the minimum dead load. The foundation design should be closely checked to assure that it distributes the loads per the allowable pressures given.
- 4) Foundation walls should be designed and reinforced to span an unsupported distance of 10 feet or the length between pads, whichever is greater.
- 5) Footings or pads should be placed well enough below final backfill grades to protect them from frost heave. Forty-eight (48) inches is typical for this location considering normal snow cover and other winter factors.
- 6) Based on experience, we estimate the total settlement for footings and pads designed and constructed as discussed in this section will be approximately 1 inch. Additional bearing capacity values along with the associated settlements are presented in Figure #8.
- 7) We strongly recommend that the client retain NWCC to observe the foundation excavations when they are near completion to identify the bearing soils and confirm the recommendations in this report.

9.0 FLOOR SLAB RECOMMENDATIONS

NWCC has assumed the proposed residences and garages will be constructed with concrete slab-on-grade floor systems placed at varying depths across the site. The on-site soils, apart from the existing topsoil and organic materials, are capable of supporting slab-on-grade construction. However, floor slabs present a very difficult problem where swelling materials are present near floor slab elevation because sufficient dead load cannot be imposed on them to resist the uplift pressure generated when the materials are wetted and expand. Based on the moisture-volume change characteristics of the sands and clays encountered at this site, we recommend that structural floor systems over well-ventilated crawlspaces or void form be used in the proposed residences.

If the client elects to construct concrete slab-on-grade floor systems, we recommend the following special design and construction precautions be followed so that the amount of movement in the floor slabs can be reduced, if the sands and clays become wetted.

- 1) Floor slabs should be separated from all bearing walls, columns and their foundation supports with a positive slip joint. We recommend the use of ½-inch thick cellotex or impregnated felt.
- 2) Interior non-bearing partition walls resting on the floor slabs should be provided with a slip joint, preferably at the bottom, so that in the event the floor slab moves, this movement is not transmitted to the upper structure. This detail is also important for wallboard and doorframes and is shown in Figure #9.
- 3) A minimum 6-inch gravel layer should be provided beneath all floor slabs to act as a capillary break and to help distribute pressures. Prior to placing the gravel, the excavation should be shaped so that if water does get under the slab, it will flow to the low point of the excavation. In addition, all of the topsoil and organic materials should be removed prior to placement of the underslab gravels or new structural fill materials.
- 4) Floor slabs should be provided with control joints placed a maximum of 12 feet on center in each direction to help control shrinkage cracking. The location of the joints should be carefully checked to assure that the natural, unavoidable cracking will be controlled. The depth of the control joints should be a minimum of ¼ the thickness of the slab.
- 5) Underslab soils should be kept as close as possible to their in-situ moisture content. Excessive wetting or drying of these soils prior to placement of the floor slab could result in differential movement after the slabs are constructed.
- 6) It has been our experience that the risk of floor slab movement can be reduced by removing at least 2 feet of the expansive materials and replacing them with a well compacted, non-expansive fill. If this is done, or if fills are required to bring the underslab soils to the desired grade, the fill should consist of non-expansive, granular materials. The fill should be uniformly placed and compacted in 6 to 8 inch lifts to at least 95% of the maximum standard Proctor density at or near the optimum moisture content, as determined by ASTM D-698/AASHTO T-99.

The above precautions and recommendations will not prevent floor slab movement in the event the sands and clays beneath the floor slabs undergo moisture changes. However, they should reduce the amount of damage if such movement occurs. The only way to eliminate the risk of all floor slab movement is to construct a structural floor over a well-vented crawl space or void form materials.

10.0 PERIMETER DRAINAGE SYSTEM RECOMMENDATIONS

Any floor levels or crawl space areas constructed below the existing or finished ground surfaces and the foundations should be protected by underdrain systems to help reduce the problems associated with surface and subsurface drainage during high runoff periods.

Localized perched water or runoff can infiltrate the lower levels of the structures at the foundation levels. This water can be one of the primary causes of differential foundation and slab movement. Especially, when expansive soils are encountered. Excessive moisture in crawl space areas or lower levels can also lead to rotting and mildewing of wooden structural members and the formation of mold and mold spores. Formation of mold and mold spores could have detrimental effects on the air quality in these areas, which in turn can lead to potential adverse health effects.

Drains should be located around entire perimeter of the lower levels and be placed and at least 12 inches below any floor slab or crawl space levels and at least 6 inches below the foundation voids and bottom of the foundation walls or footings. NWCC recommends the use of perforated PVC pipe for the drainpipe, which meets or exceeds ASTM D-3034/SDR 35 requirements, to minimize potential for pipe crushing during backfill operations. Holes in the drainpipe should be oriented down between 4 o'clock and 8 o'clock to promote rapid runoff of water. Drainpipe should be surrounded with at least 12 inches of free draining gravel and should be protected from contamination by a filter covering of Mirafi 140N subsurface drainage fabric or an equivalent product. Drains should have a minimum slope of 1/8 inch per foot and be daylighted at positive outfalls protected from freezing, or be led to sumps from which water can be pumped. The use of interior laterals, multiple daylights or sumps may be required for the proposed structure. Caution should be taken when backfilling so as not to damage or disturb the installed underdrains. NWCC recommends the drainage systems include a cleanout every 100 feet, be protected against intrusion by animals at outfalls and be tested prior to backfilling. NWCC also recommends the client retain our firm to observe the underdrain systems during construction to verify that they are being installed in accordance with recommendations provided in this report and observe a flow test prior to backfilling the system.

In addition, NWCC recommends an impervious barrier be constructed to keep water from infiltrating through the voided areas and/or under the foundation footings. Barrier should be constructed of an impervious material, which is approved by this office and placed below the perimeter drain and up against the sides of the foundation walls. A typical perimeter/underdrain detail is shown in Figure #10.

Placement of and impervious membrane and/or properly compacted clays in crawl space areas to the top of the footings or at least 12 inches above the top of the foundation voids or bottom of the foundation walls should help reduce the moisture problems in these areas.

11.0 FOUNDATIONS WALLS AND RETAINING STRUCTURE RECOMMENDATIONS

Foundation walls and retaining structures, which are laterally supported and can be expected to undergo only a moderate amount of deflection (at rest), may be designed for a lateral earth pressure computed on

the basis of an equivalent fluid unit weight of 45 pcf for imported, free draining granular backfill and 55 pcf for the on-site soils.

Cantilevered retaining structures on the site can be expected to deflect sufficiently to mobilize the full active earth pressure condition. Therefore, cantilevered structures may be designed for a lateral earth pressure computed on the basis of an equivalent fluid unit weight of 35 pcf for imported, free draining granular backfill and 45 pcf for the on-site soils.

Foundation walls and retaining structures should be designed for appropriate hydrostatic and surcharge pressures such as adjacent buildings, traffic and construction materials. An upward sloping backfill and/or natural slope will also increase the earth pressures on foundation walls and retaining structures.

NWCC recommends imported granular soils for backfilling foundation walls and retaining structures because their use results in lower lateral earth pressures. The imported granular materials should be placed to within 2 to 3 feet of the ground surface. Imported granular soils should be free draining and have less than 7 percent passing the No. 200 sieve. The granular soils behind foundation and retaining walls should be sloped from the base of the wall at an angle of at least 45 degrees from the vertical. The upper 2 to 3 feet of fill should be a relatively impervious soil or pavement structure to prevent surface water infiltration into the backfill.

Wall backfill should be carefully placed in uniform lifts and compacted to at least 95 % of the maximum standard Proctor density and within 2% of the optimum moisture content. Care should be taken not to overcompact the backfill since this could cause excessive lateral pressure on the walls. Some settlement of deep foundation wall backfill materials will occur even if the material is placed correctly.

12.0 SITE DRAINAGE RECOMMENDATIONS

Proper surface drainage at these lots is of paramount importance for minimizing the infiltration of surface drainage into the wall backfill and bearing soils, which could result in increased wall pressures, differential foundation and slab movement. The following drainage precautions should be observed during construction and at all times after the structures have been completed:

- 1) Ground surface surrounding the structures should be sloped (minimum of 1.0 inch per foot) to drain away from the structure in all directions to a minimum of 10 feet. Ponding must be avoided. If necessary, raising the top of foundation walls to achieve a better surface grade is advisable.
- 2) Non-structural backfill placed around the structures should be compacted to at least 95% of the maximum standard Proctor density at or near the optimum moisture content in order to minimize future settlement of the fill. Backfill should be placed immediately after the braced foundation walls are able to structurally support the fill. Puddling or sluicing must be avoided.
- 3) Top 2 to 3 feet of soil placed within 10 feet of the foundations should be impervious in nature to minimize infiltration of surface water into the wall backfill.

- 4) Roof downspouts and drains should discharge well beyond the limits of all backfill. Roof overhangs, which project two to three feet beyond the foundations, should be considered if gutters are not used.
- 5) Landscaping, which requires excessive watering and lawn sprinkler heads, should be located a minimum of 10 feet from the foundation walls of the structures.
- 6) Plastic membranes should not be used to cover the ground surface adjacent to foundation walls.

13.0 SITE GRADING RECOMMENDATIONS

All fill materials placed beneath the interior floor slabs, exterior flat work, pavement areas, underground utilities and within the proposed pond should be compacted to at least 95 percent of the maximum standard Proctor density and within 2 percent of the optimum moisture content as determined in accordance with ASTM D698/AASHTO T99. The fills placed in these areas should not contain boulders, topsoil, organics or other deleterious substances. The fill materials placed in the landscaped areas should be compacted to at least 90 percent of the maximum standard Proctor density. The materials not suitable for use under the buildings and pavement areas should be placed in the bottom of the fills in landscaped areas, where some settlement can be tolerated.

Site grading should be carefully planned to provide positive surface drainage away from all the buildings and pavement areas. The buildings and pavement areas should be placed as high as possible on the sites so that positive drainage away from these structures can be provided. Surface diversion features should be provided around the paved areas to prevent surface runoff from flowing across the paved surfaces.

Although site grading plans for each of the lots were not available at the time of this report, we have assumed that cuts and fills of up to 5 to 15 feet in depth may be required to develop the individual lots. We recommend that the final fill slopes not exceed 2 (H) to 1 (V) configuration if they are properly compacted and drained. Positive surface drainage should be provided around all permanent cut and fill slopes to direct surface drainage away from the slope faces. All cut and fill slopes and other stripped areas should be protected against erosion by revegetation or other methods.

14.0 PAVEMENT RECOMMENDATIONS

Pavement section alternatives presented below are based on laboratory test results, assumed traffic loadings indicated below, pavement design procedures presented in the AASHTO Guide for Design of Pavement Structures and our experience with similar sites and conditions in the Steamboat Springs area. AASHTO pavement design procedures have been adopted and are used by the Colorado Department of Transportation (CDOT).

Based on the results of the field and laboratory investigations and our understanding of the proposed construction, it appears the materials to be encountered at proposed pavement subgrade elevations along

River Queen Lane will likely consist of existing sand and gravel fill materials. These materials generally classified as SC to GC soils in accordance with the Unified Soil classification system and as A-4 to A-6 soils in accordance with the AASHTO classification system. These materials are generally considered to provide adequate to fair support for pavement structures. Using these classifications and our experience with similar soils, NWCC has correlated the soil classification to a modulus of subgrade reaction of 3,750 psi, which was used in the pavement design calculations.

NWCC recommends the pavement areas subjected to both automobile and truck traffic, such as the new along River Queen Lane be constructed with a composite pavement section consisting of at least 4 inches of asphalt placed over 4 inches of Class 6 aggregate base course and 8 inches of subbase materials consisting of Class 2 aggregate base course. Pavements for driveways and other areas subjected to automobile traffic only should receive a composite pavement section consisting of at least 3 inches of asphalt placed over 4 inches of Class 6 aggregate base course and 8 inches of subbase materials.

NWCC recommends the areas subjected to heavy truck traffic turning movements, such as in the apron areas in front of the trash dumpster approach areas be paved with a rigid pavement section consisting of at least 7 inches of Portland cement concrete (PCC). Sidewalks subjected to pedestrian traffic should be paved using at least 4 inches of PCC and 5 inches in areas where occasional emergency or snow removal vehicle traffic is anticipated.

Prior to placement of subbase materials, NWCC recommends the exposed subgrade soils be uniformly mixed, moisture treated to within 2 % of the optimum moisture content and then be recompact to at least 95 % of the maximum standard Proctor density. Depending on the time of year when subgrade preparation is considered, moisture conditioning including drying and/or moistening of subgrade materials will most likely be required in order to attain uniform compaction. NWCC also recommends that the properly moisture conditioned and recompact subgrade soils be proofrolled with a loaded tandem dump truck prior to placing the subbase gravels. Areas exhibiting deflection and rutting will most likely require deeper stabilization. The depth and type of stabilization should be determined at the time of construction.

NWCC recommends the asphalt pavement material consist of an approved "Superpave" mix designed by a qualified, registered engineer. The mix design should be designed using the SX gradation and mixed with PG 58-28 oil or other performance graded asphaltic materials. The mix should be produced and placed by a qualified contractor and should be compacted to between 92 and 96 percent of the maximum theoretical (Rice) density. Quality control activities should be conducted on paving materials at the time of placement.

Base course materials should consist of a well-graded aggregate base course material that meets CDOT Class 6 ABC grading and durability requirements. Base course and subbase materials (Class 2 ABC) should be uniformly placed and compacted in 4 to 6-inch loose lifts to at least 95 % of the maximum modified Proctor density and within +/- 2 % of the optimum moisture content as determined by ASTM D1557.

Concrete pavement materials shall be based on a mix design established by a qualified engineer. Concrete should have a minimum 28-day compressive strength of 4,500 psi, be air entrained with approximately 6 percent air and have a maximum water/cement ratio of 0.42. Concrete should have a maximum slump of 4 inches and should contain control joints not greater than 12 feet on centers. The depth of the control joints should be at least $\frac{1}{4}$ of the slab thickness.

The collection and diversion of surface and subsurface drainage away from the paved areas is extremely important to satisfactory performance of the pavement. The design of the surface and subsurface drainage features should be carefully considered to remove all water from paved areas and to prevent ponding of water on and adjacent to paved areas. NWCC recommends subgrade areas be graded to drain if feasible so that surface runoff is not allowed to pond on the subgrade surface.

15.0 LIMITATIONS

The recommendations given in this report are based on the subsurface conditions encountered in the test pits advanced across the project site, our assumptions regarding the proposed construction and the behavior of structures at neighboring, similar sites. We believe that this information gives a high degree of reliability for anticipating the behavior of the proposed structures; however, our recommendations are professional opinions and cannot control nature, nor can they assure the soils profiles beneath those or adjacent to those observed. No warranties expressed or implied are given on the content of this report.

Swelling soils were encountered throughout the subdivision. These soils are stable at their natural moisture content but can shrink or swell with changes in moisture. The behavior of swelling soils is not fully understood. The swell potential of any particular site can change erratically both in lateral and vertical extent. Moisture changes also occur erratically, resulting in conditions, which cannot always be predicted. The recommendations presented in this report are based on the current state of the art for foundations and floor slabs on swelling soils. The owner should be aware that there is a risk in construction on these types of soil. Performance of the structures will depend on following the recommendations and in proper maintenance after construction is complete. As water is the main cause for volume change in these soils, it is necessary that the changes in moisture content be kept to a minimum. This requires judicious irrigation and providing positive surface drainage away from the structures. Any distress noted in the structures should be brought to the attention of this office.


This report is based on the investigation at the described site and on the specific anticipated construction as stated herein. If either of these conditions is changed, the results would also most likely change. Therefore, we strongly recommend that our firm be contacted prior to finalizing the construction plans so that we can verify that our recommendations are being properly incorporated into the construction plans. Man-made or natural changes in the conditions of a property can also occur over a period of time. In addition, changes in requirements due to state of the art knowledge and/or legislation do from time to time occur. As a result, the findings of this report may become invalid due to these changes. Therefore, this report is subject to review and not considered valid after a period of 3 years or if conditions as stated above are altered. It is the responsibility of the owner or his representative to insure that the information in this report is incorporated into the plans and/or specifications and construction of the project. It is

advisable that a contractor familiar with construction details typically used to dealing with the local subsoils and climatic conditions be retained to build the structures.

If you have any questions regarding this report or if we may be of further service, please do not hesitate to contact us.

Sincerely,
NWCC, Inc.

Brian D. Len, P.E.
Principal Engineer




**RCRBD Record Set
T.A.**


07/16/2021


Reviewed by Timothy S. Travis, P.E.
Sr. Project Engineer


cc: Erik Griepentrog – Landmark Consultants



NOT TO SCALE



Title: SITE PLAN - TEST HOLE LOCATIONS		Date: 9/5/2017	
Job Name: Lockhart Subdivision		Job No. 17-10640	
Location: River Queen Lane, Steamboat Springs, CO		Figure #2	



LEGEND:

- Topsoil and Organics: Silty, dry to moist, and dark brown to black.
- FILL: Sand and gravel, silty to clayey, fine to coarse grained with cobbles and boulders, non to very low plastic, medium dense, slightly moist and brown.
- SANDS AND GRAVELS: Clayey, fine to coarse grained with cobbles and boulders, low plastic, dense, dry to moist and brown to gray.
- SANDS AND CLAYS: Fine to coarse-grained with gravels, low plastic, very stiff to dense, moist to slightly moist and brown.
- Small Disturbed Bag Sample.
- Small Disturbed Bag Sample.

Indicates depth of practical rig refusal on cobbles and boulders.

NOTES:

- 1) Test pits were excavated on August 18, 2017 with a Komatsu PC 138 trackhoe.
- 2) Test pit locations were determined by pacing from existing site features.
- 3) Elevations of the test pits were not measured and the logs are drawn to the depths investigated.
- 4) The lines between materials shown on the test pit logs represent the approximate boundaries between material types and transitions may be gradual.

Title: LOGS, LEGEND AND NOTES


Date: 9/5/2017


Job Name: Lockhart Subdivision

Job No. 17-10840







Location: River Queen Lane, Steamboat Springs, CO

Figure #3






LEGEND:


-  Topsoil and Organics: Silty, dry to moist, and dark brown to black.
-  FILL: Sand and gravel, silty to clayey, fine to coarse grained with cobbles and boulders, non to very low plastic, medium dense, slightly moist and brown.
-  SANDS AND GRAVELS: Clayey, fine to coarse grained with cobbles and boulders, low plastic, dense, dry to moist and brown to gray.
-  SANDS AND CLAYS: Fine to coarse-grained with gravels, low plastic, very stiff to dense, moist to slightly moist and brown.
-  Small Disturbed Bag Sample.
-  Small Disturbed Bag Sample.

↑ Indicates depth of practical rig refusal on cobbles and boulders.

NOTES:

- 1) Test pits were excavated on August 18, 2017 with a Komatsu PC 138 trackhoe.
- 2) Test pit locations were determined by pacing from existing site features.
- 3) Elevations of the test pits were not measured and the logs are drawn to the depths investigated.
- 4) The lines between materials shown on the test pit logs represent the approximate boundaries between material types and transitions may be gradual.

Title: LOGS, LEGEND AND NOTES	Date: 9/5/2017	 <p>NWCC North West Colorado Consultants, Inc. Geotechnical / Environmental Engineering - Materials Testing (970) 879-7888 • Fax (970) 879-7881 2580 Copper Ridge Drive Steamboat Springs, Colorado 80427</p>
Job Name: Lockhart Subdivision	Job No. 17-10640	
Location: River Queen Lane, Steamboat Springs, CO	Figure #4	



Title: SWELL-CONSOLIDATION TEST RESULTS


Date: 9/5/17


Job Name: Lockhart Subdivision

Job No. 17-10640

Location: River Queen Lane, Steamboat Springs, CO

Figure #5





Title: **SWELL-CONSOLIDATION TEST RESULTS**

Date: **9/5/17**


Job Name: **Lockhart Subdivision**

Job No. **17-10640**


Location: **River Queen Lane, Steamboat Springs, CO**

Figure **#6**







Title: SWELL-CONSOLIDATION TEST RESULTS		Date: 9/5/17
Job Name: Lockhart Subdivision		Job No. 17-10640
Location: River Queen Lane, Steamboat Springs, CO		Figure #7




North West Colorado Consultants, Inc.
 Geotechnical / Environmental Engineering / Materials Testing
 (970) 878-7145 • Fax (970) 878-7151
 1583 Copper Ridge Drive
 Steamboat Springs, Colorado 80487



Note: These values are based on footing widths of 1 to 4 feet. If the footing width is to be greater than 4 feet in width, then we should be notified to re-evaluate these recommendations.

Title: BEARING CAPACITY CHART		Date: 9/5/17	 NWCC <small>(North West Colorado Consultants, Inc.)</small> <small>Geotechnical / Environmental Engineering - Materials Testing</small> <small>(970) 879-7833 • Fax (970) 879-7831</small> <small>2580 Copper Ridge Drive</small> <small>Steamboat Springs, Colorado 80413</small>
Job Name: Lockhart Subdivision		Job No. 17-10640	
Location: River Queen Lane, Steamboat Springs, CO		Figure #8	



Title: **HUNG PARTITION WALL DETAIL**

Job Name: **Lockhart Subdivision**



Location: **River Queen Lane, Steamboat Springs, CO**


Date: **9/5/17**

Job No. **17-10640**

Figure **#9**





Title: PERIMETER/UNDERDRAIN DETAIL	Date: 9/5/17	
Job Name: Lockhart Subdivision	Job No. 17-10840	
Location: River Queen Lane, Steamboat Springs, CO	Figure #10	

NWCC, Inc.

TABLE 1
SUMMARY OF LABORATORY TEST RESULTS

SAMPLE LOCATION		NATURAL MOISTURE CONTENT (%)	NATURAL DRY DENSITY (pcf)	ATTERBERG LIMITS		GRADATION		PERCENT PASSING No. 200 SIEVE	UNCONFINED COMPRESSIVE STRENGTH (psf)	SOIL or BEDROCK DESCRIPTION	UNIFIED SOIL CLASS.
TEST PIT	DEPTH (feet)			LIQUID LIMIT (%)	PLASTICITY INDEX (%)	GRAVEL (%)	SAND (%)				
1	6	8.7	110.1	28	15	20	42	38		Gravelly Clayey Sand	SC
2	5	10.3		24	11	21	48	31		Gravelly Clayey Sand	SC
3	1-2	4.0		21	5	41	39	20		Silty Sand and Gravel Fill	GM
4	2-3	5.3		NP	NP	36	47	17		Silty Sand and Gravel Fill	SM
4	9	19.5	101.5	35	20	3	14	83		Sandy Clay	CL
5	3	10.8		32	19	0	24	76		Sandy Clay	CL
6	6	8.7	108.8	25	10	0	10	90		Slightly Sandy Clay	CL
7	6	5.3		20	5	21	53	26		Gravelly Clayey Sand	SC



Ph: 970-871-6772 • Fax: 970-879-8023 • P.O. Box 775966 • Steamboat Springs, Colorado 80477

**RCRBD Record Set
T.A.**

08/24/2021

Date: July 23, 2021

City of Steamboat Springs Planning Department
137 10th Street
Steamboat Springs, CO

RE: Lot 3 Eagle's Vista Duplex, 1859 River Queen Lane, Final Drainage Letter

Dear Engineering Department:

Introduction

This drainage letter presents an analysis of storm water runoff and stormwater management for the proposed duplex on Lot 3 Eagle's Vista Subdivision. Lot 3 parcel is 0.47 acres in size. The primary areas of focus is drainage into an existing designated receiving pervious area or RPA and maintaining drainage patterns per the Eagle's Vista Final Drainage Study.

Referenced Drainage Reports:

- Final Drainage Study and Stormwater Quality Plan for Eagle's Vista, Landmark Consultants, June 21, 2018.

Existing Conditions

Lot 3 is vacant/undeveloped land with native vegetation. The existing conditions of the lot is considered to be 2% impervious. Topography is variable, with moderate (10%-30%) to steep (30+%) grades on the majority of the site and transitioning to steep 2:1 and greater slopes to the northwest within the RPA. In general, all runoff from Lot 3 sheet flows into the designated RPA. There is no stormwater infrastructure currently present on the lot. A 12" HDPE culvert is located just in front of Lot 3 that manages ditch flow around the cul-de-sac. A defined outfall point was not identified from field surveying. Flows are tributary to the Yampa River.

Proposed Conditions

The proposed use of Lot 3 is a residential duplex with a detached garage and paved parking, paved access, and landscaping features. The disturbed area will be approximately 0.25 acres and proposed imperviousness will be approximately 35%. Grass lined swales are proposed along the east and west property lines within the 10-foot wide drainage/utility easements. These swales will convey runoff from Lot 3 northerly into the RPA. The swale outlets shall be tapered to a level grade approximately 8-10 feet wide at the outfall point into the RPA in order to disperse concentrated flows. Decorative cobble or rip-rap shall be utilized to reduce flow velocity and disperse runoff. A driveway trench drain will collect driveway sheet flows and outfall into the westerly swale. Swale flows are not anticipated to be significant given the relatively small drainage area so no drainage basin peak flows or swale capacity calcs were performed.

Proposed Conditions (Continued)

The driveway entrance off the Queen Lane cul-de-sac was designed to meet the intent of the Eagle's Vista Drainage Study and Eagle's Vista Civil Construction Drawings in order to capture and convey runoff within the right-of-way in front of Lot 3 to the permanent treatment facility located just southwest of Lot 3.

Conclusions

In conclusion:

- Drainage from Lot 3 will be conveyed and dispersed into the RPA on site.
- The driveway entrance was designed to conform with the Final Drainage Study and Civil Construction Drawings for the Eagle's Vista Subdivision.
- The site complies with City of Steamboat Springs engineering drainage criteria.

References

City of Steamboat Springs Engineering Standards, Section 5.0 Drainage Criteria. Prepared for City of Steamboat Springs, Department of Public Works, September 2007, updated July 2019.

Final Drainage Study and Stormwater Quality Plan for Eagle's Vista, Landmark Consultants, June 21, 2018.

Note

City of Steamboat Springs plan review and approval is only for general conformance with City design criteria and City code. The City is not responsible for the accuracy and adequacy of the design, dimensions, and elevations that shall be confirmed and correlated at this job site. The City of Steamboat Springs assumes no responsibility for the completeness or accuracy of this document.

Certification Statement

I, hereby affirm that this drainage letter and plan for Lot 2 Airport Meadows Subdivision was prepared by me (or under my direct supervision) for the owners thereof and is, the best of my knowledge, in accordance with the provisions of the City of Steamboat Springs Drainage Criteria and approved variances. I understand that the City of Steamboat Springs does not and will not assume liability for drainage facilities designed by others.



Joe Wiedemeier, PE,
License No. 0054959, State of Colorado
Four Points Surveying and Engineering

Attachments

- Standard Form No. 1 Checklist
- Proposed Conditions Grading and Drainage Plan

**RCRBD Record Set
T.A.**

08/24/2021