

NOTES:

1. THIS SYSTEM MUST HAVE WRITTEN APPROVAL FROM MULE-HIDE TECHNICAL DEPARTMENT.
2. TPO SHEETS MAY NOT END ON FASTENER PLATES.

OPTION B: MEMBRANE PARALLEL TO SLOPE

RHINO-BOND PLATE AND
APPROVED FASTENER
CENTERED ON
STRUCTURAL PURLINS.
SPACED 6 INCHES ON
CENTER

12' WIDE TPO MEMBRANE

MULE-HIDE 3"
STRESS PLATE AND
APPROVED FASTENER
— 5 FASTENERS PER
4'X8' BOARD

APPROVED COVERBOARD

FLUTE FILLER TO MATCH
HEIGHT OF EXISTING STANDING
SEAMS

MINIMUM 3" LAP WITH
MINIMUM 1½" WIDE HOT
AIR WELD

WOOD NAILERS REQUIRED
BETWEEN RIBS AT ALL EAVES.
ADDITIONAL NAILERS AS
REQUIRED TO MATCH HEIGHT OF
NEW INSULATION.

**MULE-HIDE
PRODUCTS CO., INC.**

**RHINO-BOND MECHANICALLY ATTACHED
WINDS ZONES 101-120 MPH**

**SYSTEMS:
RHINO-BOND METAL RETROFIT
TPO MECHANICALLY FASTENED**

DETAIL NO.:

MMRR-305RT

REVISION DATE: 02/2018