

3500 S. LINCOLN AVENUE
STEAMBOAT SPRINGS, CO 80487



CIVIL PLANS

LANDSCAPE PLANS

PROJECT OWNER

PROJECT ARCHITECT

CIVIL ENGINEER

The seal is circular with a double-lined border. The outer ring contains the text "COLORADO REGISTERED PROFESSIONAL ENGINEER" in a clockwise direction. The inner circle contains the name "WALTER N. MAGALLON" at the top and the number "13448" at the bottom. A stylized signature is written across the center of the seal.



SHEET #

C1

Project Summary Table - Lot 2 (Hotel B)			
Zoning	CS		
Frontage (US HWY 40)	213 LF		
Gross Site Area	1,808 Acres (78,770 SF)		
Use Breakdown	Description	Square Footage (Net Floor Area)	# of Rooms
Principal Use	Commercial Lodging		73
Standards	Zone District Requirements	Proposed	Variance? (Y/N)
Lot Area	No Min, No Max	1.808 Acres (78,770 SF)	N
Lot Coverage	No Max		N
Floor Area Ratio	No Max		N
Building Height	63' Max		N
Frontage Building Height	26' min		N
Front Setback	5' Min, 20' Max (with conds.)	114.0'	N (note 2 CS Zoning)
Side Setback	7.5' Min	12.0'	N
Rear Setback	7.5' Min	> 100.0'	N
Second Story Intensity	50% Min	100%	N
Parking (9'X18')	66 Stalls	66	N
Snow Storage	14,490 SF	15,330 SF	N
Lot Width	25' Min	160'	N
Open Space Square Footage	15% Min	34%	N
Frontage Parking Lot Placement	30' Min	75.0'	N

1. BENCHMARK = FOUND RED PLASTIC CAP ON #5 REBAR IN THE NORTHWEST PROPERTY CORNER. ELEVATION = 6765.29 (SEE EXISTING CONDITIONS PLAN).
2. EXISTING CONDITIONS SURVEYED BY FOUR POINTS SURVEYING & ENGINEERING. TOPOGRAPHY GENERATED FROM A COMBINATION OF FIELD SURVEY DATA AND 2018 ROUTT COUNTY GIS LIDAR DATA.
3. CITY OF STEAMBOAT SPRINGS REVIEW AND APPROVAL IS ONLY FOR GENERAL CONFORMANCE WITH CITY OF STEAMBOAT SPRINGS ENGINEERING AND CDD DESIGN CRITERIA AND CODE. THE CITY IS NOT RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF THE DRAWINGS, DESIGN, DIMENSIONS, AND ELEVATIONS SHALL BE CONFIRMED AND CORRELATED AT THE JOB SITE.
4. ONE COPY OF THE APPROVED CONSTRUCTION PLANS AND SPECIFICATIONS SHALL BE KEPT ON THE JOB SITE AT ALL TIMES. PRIOR TO THE START OF CONSTRUCTION, CONTRACTOR TO VERIFY WITH PROJECT ENGINEER THE LATEST REVISION DATE OF THE APPROVED CONSTRUCTION PLANS.
5. CONTRACTOR SHALL NOTIFY THE LOCATION OF ALL UTILITIES. CALL THE UTILITY NOTIFICATION CENTER OF COLORADO (UNCC) AT 1-800-922-1987 AND ANY NECESSARY PRIVATE UTILITY TO PERFORM LOCATES PRIOR TO CONDUCTING ANY SITE WORK.
6. ALL INFRASTRUCTURE CONSTRUCTION AND RELATED WORK SHALL CONFORM TO THE CITY OF STEAMBOAT SPRINGS STANDARD SPECIFICATIONS, LATEST REVISION.
7. ALL WATER AND SANITARY SEWER CONSTRUCTION AND RELATED WORK SHALL CONFORM TO MOUNT WERNER WATER STANDARD SPECIFICATIONS, LATEST EDITION.
8. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND APPROVALS REQUIRED TO PERFORM THE WORK SUCH AS RIGHT-OF-WAY PERMIT, GRADING AND EXCAVATION PERMIT, CONSTRUCTION DIVERGING PERMIT, STORM WATER QUALITY PERMIT, ARMY CORP OF ENGINEER PERMIT, ETC. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN A COPY OF ALL APPLICABLE CODES, LICENSES, SPECIFICATIONS, AND STANDARDS NECESSARY TO PERFORM THE WORK, AND BE FAMILIAR WITH THEIR CONTENTS PRIOR TO COMMENCING ANY WORK.
9. PRIOR TO ANY WORK IN THE RIGHT-OF-WAY INCLUDING STREET CLOSURE, CONTACT ROUTT COUNTY ROAD AND BRIDGE FOR PERMIT REQUIREMENTS.
10. PRIOR TO START OF CONSTRUCTION CONTRACTOR SHALL COORDINATE WITH PROJECT ENGINEER TO IDENTIFY PROJECT INSPECTION AND TESTING REQUIREMENTS. CONTRACTOR SHALL PROVIDE FOR INSPECTIONS AND TESTING AT AN ADEQUATE FREQUENCY FOR THE PROJECT ENGINEER TO DOCUMENT THAT PROJECT IS CONSTRUCTED IN CONFORMANCE WITH THE APPROVED PLANS AND SPECIFICATIONS. PRIOR TO MAKING ANY CHANGES TO THE
11. CONTRACTOR IS RESPONSIBLE FOR ALL NECESSARY TRAFFIC CONTROL. TRAFFIC CONTROL SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD), LATEST EDITION.
12. CONTRACTOR SHALL PROVIDE ALL NECESSARY TRAFFIC CONTROL (SIGNS, BARRICADES, FLAGMEN, LIGHTS, ETC) IN ACCORDANCE WITH THE MUTCD, CURRENT EDITION.
13. CONTRACTOR MUST SUBMIT A CONSTRUCTION SITE MANAGEMENT PLAN (CSMP) AND EROSION CONTROL PLAN (ECP) FOR REVIEW AND APPROVAL BY ROUTT COUNTY PLANNING PRIOR TO START OF CONSTRUCTION. THE CSMP AND ECP MUST BE MAINTAINED ON-SITE AND UPDATED AS NEEDED TO REFLECT CURRENT CONDITIONS.
14. THE FOLLOWING PRIVATE IMPROVEMENTS REQUIRE CONSTRUCTION OBSERVATION PER THE CITY OF STEAMBOAT SPRINGS ENGINEERING SERVICES SPECIFICATION OR AS REQUIRED BY THE CITY: WATER, SEWER, AND STORM SEWER.
15. RECORD DRAWINGS ARE REQUIRED FOR: PUBLIC AND PRIVATE WATER AND SEWER.
16. ALL STORMWATER PIPE OUTFALLS REQUIRE FLARED END SECTIONS AND RIPRAP.
17. EXISTING ASPHALT PAVEMENT SHALL BE STRAIGHT SAW CUT WHEN ADJOINING WITH NEW ASPHALT PAVEMENT OR WHEN ACCESS TO UNDERGROUND UTILITIES IS REQUIRED. TACK COAT SHALL BE APPLIED TO ALL EXPOSED SURFACES INCLUDING SAW CUTS, POTHOLES, TRENCHES, AND ASPHALT OVERLAY. ASPHALT PATCHES IN THE RIGHT-OF-WAY SHALL BE PER ROUTT COUNTY ROAD AND BRIDGE SPECIFICATIONS.

1. EXISTING UTILITY LOCATIONS WERE OBTAINED FROM FIELD LOCATES AND FIELD SURVEYING AND HAVE NOT BEEN VERIFIED WITH ANY ADDITIONAL UNDERGROUND POTHOLING. POTHOLING AND VERIFICATION OF LINE LOCATIONS SHALL BE REQUIRED AT ALL EXISTING UTILITY CROSSINGS.
2. MINIMUM SEPARATION BETWEEN PARALLEL WATER AND SEWER MAINS AND SERVICES IS TEN (10') FEET. MINIMUM SEPARATION BETWEEN PARALLEL WATER AND SEWER SERVICE LINES IS TEN (10') FEET.
3. ALL WORK SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF MOUNT WERNER WATER STANDARDS AND SPECIFICATIONS, LATEST EDITION.
4. MINIMUM COVER FROM FINISHED GRADE TO TOP OF WATER MAIN LINE IS SEVEN (7) FEET UNLESS OTHERWISE NOTED. ALL WATER SERVICE LINES SHALL BE TYPE "K" COPPER AND SEAMLESS BETWEEN FITTINGS.
5. MINIMUM SEPARATION BETWEEN UTILITY PEDESTALS AND FIRE HYDRANTS IS FIFTEEN (15') FEET. MINIMUM SEPARATION BETWEEN FIRE HYDRANTS, WATER OR SEWER MAINS, AND ENDS OF CULVERTS IS FIVE (5) FEET. MINIMUM SEPARATION BETWEEN WATER AND SEWER SERVICE LINES IS TEN (10') FEET. NO RIP-RAP IS PERMITTED WITHIN TEN (10') FEET OF A SEWER MAIN.
6. ALL SHALL BE OPERATED BY UTILITY PERSONNEL ONLY.
7. SEWER SERVICES ARE ANTICIPATED TO BE FOUR (4") INCH DIAMETER, SDR 35 PVC. MINIMUM SLOPE OF 2%, UNLESS NOTED OTHERWISE.
8. WATER SERVICES ARE ANTICIPATED TO BE ONE (1") INCH DIAMETER, COPPER TYPE K, UNLESS NOTED OTHERWISE.
9. DISINFECTION, BACTERIOLOGICAL, AND HYDROSTATIC TESTING IS REQUIRED FOR THE 8" DIP WATER/FIRE SERVICE PIPE.
10. ALL MECHANICAL JOINTS, RESTRAINT, THRUST BLOCKS AND CROSSING MUST BE OBSERVED BY THE ENGINEER PRIOR TO THE PLACEMENT OF BACKFILL.
11. MECHANICAL RESTRAINTS AND THRUST BLOCKS ARE REQUIRED AT ALL BENDS, TEES, REDUCERS AND DEAD ENDS.
12. ALL FITTINGS ASSOCIATED WITH UTILITY INSTALLATION WILL BE ON-SITE PRIOR TO WATER LINE SHUT DOWN.

**REVIEWED
FOR
CODE
COMPLIANCE**
01/12/2024




**410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointsse.com**

No.	DATE	REVISIONS	INT
1	9/13/23	CURR INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE CHECK VALVE SPECS, EARTHWORK CALCS	
2	11/8/23	CSMP REVISIONS	RS

**HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS**

**INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487**

HORIZONTAL SCALE



CONTOUR INTERVAL = 2FT

DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/WNM
REVIEW BY: FPSE


IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36", THE
GRAPHIC SCALE SHOULD BE UTILIZED.

EXISTING CONDITIONS PLAN

DRAWING:

SHEET NO.

C2



GENERAL NOTES:


- EXISTING CONDITIONS AND TOPOGRAPHY WAS SURVEYED AND DRAWN BY FOUR POINTS SURVEYING AND ENGINEERING.
- EXISTING UTILITIES SHOWN ARE REPRESENTATIVE OF AS-BUILT DATA AND SURVEYED FIELD LOCATES. BURIED UTILITIES HAVE NOT BEEN VERIFIED WITH POT-HOLING.

**REVIEWED
FOR
CODE
COMPLIANCE**
01/12/2024

		410 S. Lincoln Ave, Unit 15 P.O. Box 775966 Steamboat Springs, CO 80487 (970)-871-6772 www.fourpointse.com	
		INT	
REVISIONS	DATE	NO.	
1	9/13/23	1	CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS
2	11/8/23	2	CSMP REVISIONS
HOLIDAY INN EXPRESS & HOTEL B CONSTRUCTION PLANS INDIAN MEADOWS F4 LOT 1 AND 2 STEAMBOAT SPRINGS, CO 80487			
OVERALL SITE PLAN			
HORIZONTAL SCALE 0 20' 40' SCALE: 1" = 20' CONTOUR INTERVAL = 1 FT DATE: 11-17-2023 JOB #: 1448-005 DRAWN BY: AP/DSC/AAC DESIGN BY: AP/DSC/AAC/WMM REVIEW BY: FPSE IF THIS DRAWING IS PRESENTED IN A FORMAT OTHER THAN 24" X 36", THE GRAPHIC SCALE SHOULD BE UTILIZED.			
DRAWING:			
SHEET NO.			
C3			

STONE DRAIN INLET SCHEDULE

ITEM	DESCRIPTION	QUANTITY
A1	24" NYLOPLAST INLET WITH DOME GRATE	1
A2	24" NYLOPLAST INLET WITH DOME GRATE	1
A3	24" NYLOPLAST INLET WITH DOME GRATE	1
A4	24" NYLOPLAST INLET WITH DOME GRATE	1
A5	24" NYLOPLAST INLET WITH DOME GRATE	1
A6	24" NYLOPLAST INLET WITH DOME GRATE	1
A7	24" NYLOPLAST INLET WITH DOME GRATE	1
A8	24" NYLOPLAST INLET WITH DOME GRATE	1
A9	24" NYLOPLAST INLET WITH DOME GRATE	1
A10	24" NYLOPLAST INLET WITH DOME GRATE	1
A11	24" NYLOPLAST INLET WITH DOME GRATE	1
A12	24" NYLOPLAST INLET WITH DOME GRATE	1
A13	24" NYLOPLAST INLET WITH DOME GRATE	1
A14	24" NYLOPLAST INLET WITH DOME GRATE	1
A15	24" NYLOPLAST INLET WITH DOME GRATE	1
A16	24" NYLOPLAST INLET WITH DOME GRATE	1
A17	24" NYLOPLAST INLET WITH DOME GRATE	1
A18	24" NYLOPLAST INLET WITH DOME GRATE	1
A19	24" NYLOPLAST INLET WITH DOME GRATE	1
A20	24" NYLOPLAST INLET WITH DOME GRATE	1



**REVIEWED
FOR
CODE
COMPLIANCE**
01/12/2024

PROJECT TOTAL EARTHWORK QUANTITIES:

AREA OF DISTURBANCE: 121,150 SQ. FT.
TOPSOIL STRIPPING: 2,250 CU. YDS.
TOTAL CUT: 75 CU. YDS.
TOTAL FILL: 8,075 CU. YDS.
NET (FILL): 8,000 CU. YDS.

NOTES:

1. TOPSOIL STRIPPING VOLUME ASSUMES AN AVERAGE TOPSOIL DEPTH OF 0.5 FEET
2. THE TOTAL CUT VOLUME INCLUDES TOPSOIL STRIPPING.
3. A FILL FACTOR OF 1.10 WAS USED FOR CUT-FILL VOLUME CALCULATIONS.
4. FILL VOLUME INCLUDES NATIVE MATERIAL AND ALL IMPORT MATERIALS. (I.E. GRAVEL, ASPHALT, CONCRETE, ETC.)

410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointse.com

INT	REVISIONS	DATE	NO.
	CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	9/13/23	1
	CSMP REVISIONS	11/8/23	2

**HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS**

**INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487**

HORIZONTAL SCALE
0 20' 40'
SCALE: 1" = 20'

CONTOUR INTERVAL = 1 FT

DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/WMM
REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A FORMAT OTHER THAN 24" X 36", THE GRAPHIC SCALE SHOULD BE UTILIZED.



**GRADING &
DRAINAGE PLAN**

DRAWING: SHEET NO. **C4**


DRAWING FILE: P:\1448-005 LOT 1 INDIAN MEADOWS F3 HOTELS\FPSE\CONSTRUCTION PLANS\1448-005 640 PLANNING

PLOT DATE: 11/17/2023 9:03 AM BY: RICHIE SOROKA

CTB: FPSE-BN/CTB



REVIEWED
FOR
CODE
COMPLIANCE
01/12/2024



410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointse.com

No.	DATE	REVISIONS		INT
		CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	CSMP REVISIONS	
1	9/13/23			
2	11/8/23			

HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS
INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487

HORIZONTAL SCALE

DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/WNM
REVIEW BY: FPSE
IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36", THE
GRAPHIC SCALE SHOULD BE UTILIZED.



STORM SEWER
PROFILES

DRAWING:


SHEET NO.

C5







BIORETENTION FACILITY #1




BIORETENTION FACILITY #2




BIORETENTION FACILITY #3



BIORETENTION FACILITY #4



BIORETENTION FACILITY #5

BIORETENTION FACILITY #6

**REVIEWED
FOR
CODE
COMPLIANCE**
01/12/2024



**410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointssse.com**

NO.	DATE	REVISIONS	INT
1	9/13/23	CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	
2	11/8/23	CSMP REVISIONS	RS

**HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS**

**INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487**

HORIZONTAL SCALE



CONTOUR INTERVAL = 1 FT

DATE: 11-17-2023

JOB #: 1448-005

DESIGN BY: AP/DSC/AAC/WNM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36", THE
GRAPHIC SCALE SHOULD BE UTILIZED.

WING:

**BIORETENTION
PLAN & PROFILE**

SHEET NO.

C6



PROFILE SCALES:
HORIZONTAL: 1" = 40'
VERTICAL: 1" = 2'

BIORETENTION NOTES:

TERMINOLOGY:

THE TERM BIORETENTION REFERS TO THE TREATMENT PROCESS ALTHOUGH IT IS ALSO FREQUENTLY USED TO DESCRIBE A BMP THAT PROVIDES BIOLOGICAL UPTAKE AND FILTRATION OF THE POLLUTANTS FOUND IN STORMWATER RUNOFF.

DESCRIPTION:

BIORETENTION IS A BEST MANAGEMENT PRACTICE (BMP) THAT UTILIZES BIORETENTION AS AN ENGINEERED, DEPRESSED LANDSCAPE AREA DESIGNED TO CAPTURE AND FILTER OR INFILTRATE THE WATER QUALITY CAPTURE VOLUME (WCQV). BMPs THAT UTILIZE BIORETENTION ARE FREQUENTLY REFERRED TO AS RAIN GARDENS OR POROUS LANDSCAPE DETENTION AREAS (PLDs).

THE DESIGN OF A BIORETENTION OR RAIN GARDEN SYSTEM MAY PROVIDE DETENTION FOR EVENTS EXCEEDING THAT OF THE WCQV. THERE ARE GENERALLY TWO WAYS TO ACHIEVE THIS. THE DESIGN CAN PROVIDE THE FLOOD CONTROL VOLUME ABOVE THE WCQV OR THE DESIGN CAN PROVIDE AND SLOWLY RELEASE THE FLOOD CONTROL VOLUME IN AN AREA DOWNSTREAM OF ONE OR MORE BIORETENTION SYSTEMS. SEE THE STORAGE CHAPTER IN VOLUME 2 OF THE URBAN STORM DRAINAGE CRITERIA MANUAL (USDGM) FOR ADDITIONAL INFORMATION.

SITE SELECTION:

THIS BMP ALLOWS WCQV TREATMENT WITHIN ONE OR MORE AREAS DESIGNATED FOR LANDSCAPE. IT IS AN EXCELLENT ALTERNATIVE TO EXTENDED DETENTION BASINS FOR SMALL SITES WITH LIMITED AVAILABLE AREA. A TYPICAL BIORETENTION SYSTEM SERVES A TRIBUTARY OR SUBBASIN AREA OF ONE IMPERVIOUS ACRE OR LESS. ALTHOUGH THEY CAN BE DESIGNED FOR LARGER TRIBUTARY AREAS, MULTIPLE INSTALLATIONS CAN BE USED WITHIN LARGER SITES. BIOFILTRATION SHOULD NOT BE USED WHEN A BASEFLOW IS ANTICIPATED OR WHEN GROUNDWATER HAS BEEN OBSERVED IN CLOSE PROXIMITY TO EXISTING GRADE ELEVATIONS. THE SYSTEMS ARE TYPICALLY SMALL AND MAY BE INSTALLED IN LOCATIONS SUCH AS:

- PARKING LOT ISLANDS
- STREET MEDIANS
- LANDSCAPE AREAS BETWEEN THE ROAD AND A DETACHED SIDEWALK
- PLANTER BOXES THAT COLLECT ROOF DRAINS

BIORETENTION REQUIRES A STABLE WATERSHED. DURING PHASED CONSTRUCTION, PROPER EROSION PREVENTION AND SEDIMENT CONTROL MEASURES SHALL BE INSTALLED TO ENSURE LAIDEN SEDIMENT DOES NOT DIRECTLY DISCHARGE INTO ADJACENT WATERBODIES.

THE SURFACE OF A RAIN GARDEN SHOULD BE PRIMARILY FLAT. HOWEVER, TERRACED APPLICATION OF THESE FACILITIES HAVE BEEN SUCCESSFUL IN THE PAST. WHEN BIORETENTION SYSTEMS ARE LOCATED ADJACENT TO BUILDINGS OR PAVEMENT AREAS, PROTECTIVE MEASURES SHOULD BE IMPLEMENTED TO AVOID ADVERSE IMPACTS TO THESE STRUCTURES.

MAINTENANCE:

SEE THE OPERATIONS AND MAINTENANCE PLAN INCLUDED AS PART OF THE DRAINAGE REPORT.

ON-SITE SOIL CONDITIONS:

NORTHWEST COLORADO CONSULTANTS (NWCC) PRODUCED A GEOTECHNICAL STUDY FOR THE PROJECT ON MARCH 31, 2022. THE GEOTECHNICAL STUDY INCLUDED THE LOGGING OF FOUR TEST HOLES AND SIX TEST PITTS. SOILS WERE OBSERVED ON-SITE AND LATER SAMPLED AND LAB TESTED FOR ADDITIONAL EVALUATION.

BASED ON THE ANTICIPATED GEOLOGIC SITE CONDITIONS, NWCC RECOMMENDED THAT A **SITE CLASS C** DESIGNATION SHOULD BE USED IN STRUCTURAL DESIGN CALCULATIONS IN ACCORDANCE WITH TABLE 20.3-1 IN CHAPTER 20 OF ASCE 7.

THEREFORE, FOUR POINTS SURVEYING AND ENGINEERING OPTED TO ELIMINATE THE POTENTIAL FOR INFILTRATING BMPs AS A RESULT OF THE GEOTECHNICAL STUDY FINDINGS. ALL OF THE SEVEN PROPOSED BIORETENTION SYSTEMS WILL BE NON-INFILTRATING AND WILL RELY ON UNDER-DRAIN SYSTEMS TO CAPTURE AND CONVEY STORMWATER TO THE INTENDED DESIGN OUTFALLS AND OFF-SITE DISCHARGE LOCATIONS.

NON-INFILTRATING BIORETENTION SYSTEMS:

NON-INFILTRATING BIORETENTION SYSTEMS INCLUDE AN UNDER-DRAIN AND AN IMPERVIOUS LINER THAT PREVENTS INFILTRATION OF STORMWATER INTO THE SUBGRADE SOILS. NON-INFILTRATING BIORETENTION SYSTEMS ARE APPROPRIATE FOR THIS PROJECT AS THE FACILITY IS LOCATED OVER POTENTIALLY EXPANSIVE SOILS OR BEDROCK THAT COULD SELL DUE TO INFILTRATION AND POTENTIALLY DAMAGE ADJACENT STRUCTURES (I.E. BUILDING FOUNDATIONS OR PAVEMENTS).

BASIN STORAGE VOLUME:

STORAGE VOLUMES ARE BASED ON A 12-HOUR DRAIN TIME. SEE THE ATTACHED BMP SIZING WORKSHEETS ATTACHED TO THIS DRAINAGE REPORT. DESIGN VOLUMES ARE CALCULATED FOLLOWING EQUATION B-1 OF THE USDGM MANUAL, VOLUME 3.

$$V = \left(\frac{60}{24}\right) \times A \quad \text{(EQ. B-1)}$$

WHERE:
V = DESIGN VOLUME (FT³)
A = AREA OF WATERSHED TRIBUTARY TO THE BIORETENTION SYSTEM (FT²)

BASIN GEOMETRY:

THE MAXIMUM PONDING DEPTH FOR THE PROJECT IS 12 INCHES. NYLOPLAST DOME GRATES WILL BE INSTALLED TO MANAGE OVERFLOW WITHIN THE PONDED AREA OF EACH BIORETENTION FACILITY. THIS WILL REDUCE THE POTENTIAL FOR EXCESS STORMWATER FROM OVERTOPPING THE CURBS AND BACKFLOWING INTO THE PROPOSED PARKING AREA. VERTICAL WALL GEOMETRIES WILL BE UTILIZED SEE FIGURE B-3 GEOMEMBRANE LINER/CONCRETE CONNECTION DETAIL FOR ADDITIONAL INFORMATION. CURB CUTS ARE PROPOSED TO ALLOW THE PARKING LOT TO SUCCESSFULLY DRAIN INTO EACH OF THE INTENDED BMP SYSTEMS. MINIMUM FILTER AREAS WERE CALCULATED USING THE FOLLOWING EQUATION:

$$A_f = 0.02A \quad \text{(EQ. B-2)}$$

WHERE:
AF = MINIMUM (FLAT) FILTER AREA (FT²)
A = AREA TRIBUTARY TO THE BIORETENTION SYSTEM (FT²)
I = IMPERVIOUSNESS OF TRIBUTARY AREA TO THE BIORETENTION SYSTEM (PERCENT EXPRESSED AS A DECIMAL).

GROWING MEDIUM:

PROVIDE A MINIMUM OF 18 INCHES OF GROWING MEDIUM TO ENABLE ESTABLISHMENT OF THE ROOTS OF THE VEGETATION. SEE THE SPECIFICATION TABLE BELOW FOR SPECIFICATIONS OF THE GROWING MEDIUM.

UNDER-DRAIN SYSTEM:

WHEN USING AN UNDER-DRAIN SYSTEM, PROVIDE A CONTROL ORIFICE TO DRAIN THE DESIGN VOLUME IN 12 HOURS OR MORE. USE A MINIMUM ORIFICE SIZE OF ¾ INCHES TO AVOID CLOGGING. THIS WILL PROVIDE DETENTION AND SLOW RELEASE OF THE WCQV, PROVIDING WATER QUALITY BENEFITS AND REDUCING IMPACTS TO DOWNSTREAM CHANNELS. SPACE UNDER-DRAIN PIPES A MAXIMUM OF 20 FEET ON CENTER. PROVIDE CLEANOUTS TO ENABLE MAINTENANCE OF THE UNDER-DRAIN SYSTEM. EACH NYLOPLAST INLET STRUCTURE WILL INCLUDE AN ORIFICE HOLE TO RELEASE EACH OF THE BIORETENTION SYSTEMS WITHIN THE 12 HOUR PERIOD. CALCULATIONS FOR THE ORIFICE SIZE HAVE BEEN PROVIDED IN THE ATTACHMENTS OF THE DRAINAGE REPORT.

THE UNDER-DRAIN SYSTEM SHOULD BE PLACED WITHIN A 6-INCH THICK SECTION OF CDOT CLASS B OR CLASS C FILTER MATERIAL MEETING THE GRADATION IN THE TABLE BELOW. USE SLOTTED (PERFORATED) PIPE THAT MEETS THE SLOT DIMENSIONS LISTED IN THE TABLE ON THE SPECIFICATIONS SHEET.

IMPERMEABLE GEOMEMBRANE LINER AND GEOTEXTILE SEPARATOR FABRIC:

FOR NON-INFILTRATING SYSTEMS, INSTALL A 30 MIL (MIN) PVC GEOMEMBRANE LINER, PER THE TABLE ON THE SPECIFICATIONS SHEET, ON THE BOTTOM AND SIDES OF THE BASIN, EXTENDING UP AT LEAST TO THE TOP OF THE UNDER-DRAIN LAYER. PROVIDE AT LEAST 9 INCHES (12 INCHES IF POSSIBLE) OF COVER OVER THE MEMBRANE WHERE IT IS TO BE ATTACHED TO THE WALL TO PROTECT THE MEMBRANE FROM UV DETERIORATION. THE GEOMEMBRANE SHOULD BE FIELD SEAMED USING A DUAL TRACK WELDER, WHICH ALLOWS FOR NON-DESTRUCTIVE TESTING OF ALMOST ALL FIELD SEAMS. A SMALL AMOUNT OF SINGLE TRACK IS ALLOWED IN LIMITED AREAS TO SEAM AROUND PIPE PERFORATIONS. TO PATCH SEAMS REMOVED FOR DESTRUCTIVE SEAM TESTING, AND FOR LIMITED REPAIRS. THE LINER SHOULD BE INSTALLED WITH SLACK TO PREVENT TEARING DUE TO BACKFILL, COMPACTION AND SETTling.

PLACE CDOT CLASS B GEOTEXTILE SEPARATOR FABRIC ABOVE THE GEOMEMBRANE TO PROTECT IT FROM BEING PUNCTURED DURING THE PLACEMENT OF THE FILTER MATERIAL ABOVE THE LINER. IF THE SUBGRADE CONTAINS ANGULAR ROCKS OR OTHER MATERIAL THAT COULD PUNCTURE THE GEOMEMBRANE, SMOOTH-ROLL THE SURFACE TO CREATE A SUITABLE SURFACE. IF SMOOTH-ROLLING THE SURFACE DOES NOT PROVIDE A SUITABLE SURFACE, ALSO PLACE THE SEPARATOR FABRIC BETWEEN THE GEOMEMBRANE AND THE UNDERLYING SUBGRADE. THIS SHOULD ONLY BE DONE WHEN NECESSARY BECAUSE FABRIC PLACED UNDER THE GEOMEMBRANE CAN INCREASE SEEPAGE LOSSES THROUGH PINHOLES OR OTHER GEOMEMBRANE DEFECTS. CONNECT THE GEOMEMBRANE TO PERIMETER CONCRETE WALLS AROUND THE BASIN PERIMETER, CREATING A WATERTIGHT SEAL BETWEEN THE GEOMEMBRANE AND THE WALLS USING A CONTINUOUS BATTEN BAR AND ANCHOR CONNECTION (SEE FIGURE B-3 OF USDGM). WHERE THE NEED FOR THE IMPERMEABLE MEMBRANE IS NOT AS CRITICAL, THE MEMBRANE CAN BE ATTACHED WITH A NITRILE-BASED VINYL ADHESIVE. USE WATERTIGHT PVC BOOTS FOR UNDERDRAIN PIPE PENETRATIONS THROUGH THE LINER (SEE FIGURE B-2) OR THE TECHNIQUE SHOWN IN PHOTO B-3 OF THE USDGM.

INLET AND OUTLET CONTROL:

INLET CONTROL WILL BE MAINTAINED BY CURB CUT OPENINGS THAT ARE ORIENTATED IN THE DIRECTION OF THE PARKING LOT FLOW.

OUTLET CONTROL WILL BE MAINTAINED BY THE INSTALLATION OF THE NYLOPLAST GRATES. THE NYLOPLAST GRATES WILL HELP CAPTURE EXCESS VOLUMES WITHIN THE BIORETENTION SYSTEMS (DURING LARGER STORM EVENTS) AND REDUCE THE POTENTIAL FOR BACKFLOW INTO THE PARKING LOT AREA.

VEGETATION:

THE UDFCD RECOMMENDS THAT THE FILTER AREA SHALL BE VEGETATED WITH DROUGHT TOLERANT SPECIES THAT THRIVE IN SANDY SOILS. SEE THE SPECIFICATION SHEET FOR ADDITIONAL INFORMATION.

MIX SEED WELL AND BROADCAST, FOLLOWED BY HAND RAKING TO COVER SEED AND THEN MULCH. HYDRO-MULCHING CAN BE EFFECTIVE FOR THE LARGER BIORETENTION SYSTEMS. DO NOT PLACE SEED WHEN STANDING WATER OR SNOW IS PRESENT OR IF THE GROUND IS FROZEN. WEED CONTROL IS CRITICAL IN THE FIRST TWO TO THREE YEARS, ESPECIALLY WHEN STARTING WITH SEED.

WHEN USING SOD, SPECIFY SAND-GROWN SOD. DO NOT USE CONVENTIONAL SOD. CONVENTIONAL SOD IS GROWN IN CLAY SOIL THAT WILL SEAL THE FILTER AREA, GREATLY REDUCING THE OVERALL FUNCTION OF THE BMP.

WHEN USING AN IMPERMEABLE LINER, SELECT PLANTS WITH DIFFUSE (OR FIBROUS) ROOT SYSTEMS, NOT TAPROOTS. TAPROOTS CAN DAMAGE THE LINER AND/OR UNDER-DRAIN PIPE. AVOID TREES AND LARGE SHRUBS THAT MAY INTERFERE WITH RESTORATIVE MAINTENANCE. PLANT THESE OUTSIDE OF THE AREA OF GROWING MEDIUM. USE A CUTOFF WALL TO ENSURE THAT ROOTS DO NOT GROW INTO THE UNDER-DRAIN OR PLACES TRESS AND SHRUBS A CONSERVATIVE DISTANCE FROM THE UNDER-DRAIN.

IRRIGATION:

ON-SITE IRRIGATION IN THE FORM OF SPRINKLER SYSTEMS ARE NOT PROPOSED FOR THIS PROJECT. PLANTINGS SHALL BE WATERED AT AN APPROPRIATED RATE TO MAINTAIN VEGETATIVE GROWTH WITHIN THE BMP SYSTEMS. ADJUST WATERING SCHEDULES DURING THE GROWING SEASON (SPRING AND SUMMER MONTHS) TO PROVIDE THE MINIMUM WATER NECESSARY TO MAINTAIN PLANT HEALTH AND TO MAINTAIN THE AVAILABLE PORE SPACE FOR INFILTRATION.

AESTHETIC DESIGN:

IN ADDITION TO EFFECTIVE STORMWATER QUALITY TREATMENT, BIOFILTRATION CAN BE ATTRACTIVELY INCORPORATED INTO A SITE WITHIN ONE OR SEVERAL LANDSCAPE AREAS. AESTHETICALLY DESIGNED BIOFILTRATION WILL TYPICALLY EITHER REFLECT THE CHARACTER OF THEIR SURROUNDING OR BECOME DISTINCT FEATURES WITHIN THEIR SURROUNDINGS. SEE THE USDGM FOR ADDITIONAL CRITERIA RELATING TO AESTHETICS.

CONSTRUCTION CONSIDERATIONS:

PROPER CONSTRUCTION OF BIOFILTRATION SYSTEMS INVOLVES CAREFUL ATTENTION TO MATERIAL SPECIFICATION, FINISHED GRADES, AND CONSTRUCTION DETAILS. IMPORTANT FACTORS TO IMPLEMENT INCLUDE:

- PROTECT AREAS FROM EXCESSIVE SEDIMENT LOADING DURING CONSTRUCTION. THIS IS THE MOST COMMON CAUSE OF CLOGGING OF BIOFILTRATION. THE PORTION OF THE SITE DRAINING TO THE RAIN GARDEN MUST BE STABILIZED BEFORE ALLOWING FLOW INTO THE RAIN GARDEN. THIS INCLUDES COMPLETION OF PAVING OPERATIONS.
- AVOID OVER COMPACTION OF AREA TO PRESERVE INFILTRATION RATES (NOT APPLICABLE TO NON-INFILTRATING SYSTEMS).
- PROVIDE CONSTRUCTION OBSERVATION TO ENSURE COMPLIANCE WITH DESIGN SPECIFICATIONS. IMPROPER INSTALLATION, PARTICULARLY RELATED TO FACILITY DIMENSIONS AND ELEVATIONS AND UNDER-DRAIN ELEVATIONS, IS A COMMON PROBLEM WITH BIORETENTION.
- WHEN USING AN IMPERMEABLE LINER, ENSURE ENOUGH SLACK IN THE LINER TO ALLOW FOR BACKFILL, COMPACTION, AND SETTling WITHOUT TEARING THE LINER.
- PROVIDE NECESSARY QUALITY ASSURANCE AND QUALITY CONTROL (QA/QC) WHEN CONSTRUCTION AN IMPERMEABLE GEOMEMBRANE LINER SYSTEM, INCLUDING BUT NOT LIMITED TO FABRICATION TESTING, DESTRUCTIVE AND NON-DESTRUCTIVE TESTING OF FIELD SEAMS, OBSERVATION OF GEOMEMBRANE MATERIALS FOR TEARS OR OTHER DEFECTS, AND AIR LACE TESTING FOR LEAKS IN ALL FIELD SEAMS AND PENETRATIONS. QA/QC SHOULD BE OVERSEEN BY THE OWNERS REPRESENTATIVE AND REPORTED TO A PROFESSIONAL ENGINEER. FIELD REPORTING AND INSPECTION LOGS ARE REQUIRED DURING THE LINER INSTALLATION PROCESS. ALL DOCUMENTS SHALL BE TRANSMITTED TO THE PROFESSIONAL ENGINEER.
- PROVIDE ADEQUATE CONSTRUCTION STAKING TO ENSURE THAT THE SITE PROPERLY DRAINS INTO THE BMP SYSTEM, PARTICULARLY WITH RESPECT TO SURFACE DRAINAGE AWAY FROM ADJACENT BUILDINGS.

MISCELLANEOUS:

ALL NOTES AND SPECIFICATIONS ARE REFERENCED TO THE URBAN DRAINAGE AND FLOOD CONTROL DISTRICT, URBAN STORM DRAINAGE CRITERIA MANUAL, VOLUME 3, LATEST ADDITION.

TABLE 3: PHYSICAL REQUIREMENTS FOR SEPARATOR FABRIC			
PROPERTY	CLASS B		TEST METHOD
	ELONGATION <50%	ELONGATION > 50%	
GRAB STRENGTH, N (lbs)	800 (180)	510 (115)	ASTM D 4632
PUNCTURE RESISTANCE, N (lbs)	310 (70)	180 (40)	ASTM D 4833
TRAPEZOIDAL TEAR STRENGTH, N (lbs)	310 (70)	180 (40)	ASTM D 4533
APPARENT OPENING SIZE, mm (US SIEVE SIZE)	AOS < 0.3 mm (US SIEVE SIZE NO. 50)		ASTM D 4751
PERMITTIVITY, SEC ⁻¹	0.02 DEFAULT VALUE. MUST ALSO BE GREATER THAN THAT OF SOIL		ASTM D 4491
PERMEABILITY, CM/SEC	K FABRIC > K SOIL FOR ALL CLASSES		ASTM D 4491
ULTRAVIOLET DEGRADATION AT 500 HOURS	50% STRENGTH RETAINED FOR ALL CLASSES		ASTM D 4355


TABLE 1: MATERIAL SPECIFICATION FOR BIORETENTION SYSTEMS

MATERIAL		SPECIFICATION		SUBMITTALS	TESTING	NOTES
BIORETENTION GROWING MEDIA	BIORETENTION SOIL	PARTICLE SIZE DISTRIBUTION 80-90% SAND (0.05 - 2.0 mm DIAMETER) 3-17% SILT (0.002 - 0.5 mm DIAMETER) 3-17% CLAY (<0.002 DIAMETER) CHEMICAL ATTRIBUTE AND NUTRIENT ANALYSIS pH = 6.8 - 7.5 ORGANIC MATTER <15% NITROGEN < 15 PPM PHOSPHOROUS < 15 PPM SALINITY < 6 MMHOS/CM		PARTICLE SIZE DISTRIBUTION AND NUTRIENT ANALYSIS REQUIRED		PERCENTAGES ARE IN WEIGHT.
	BIORETENTION ORGANICS	3 TO 5% SHREDDED MULCH (BY WEIGHT OF GROWING MEDIA)				BIORETENTION SOIL REQUIRED. AGED SIX MONTHS (MIN.).
LANDSCAPE MULCH		SHREDDDED HARDWOOD				AGED SIX MONTHS (MIN.). NO WEED FABRIC ALLOWED
UNDERDRAIN AGGREGATE	CDOT FILTER MATERIAL (CLASS B OR C)			MASS PERCENT PASSING SQUARE MESH SIEVE		
		SIEVE SIZE	CLASS B	CLASS C		
		37.5 mm (1.5")	100			
		19.0 mm (0.75")		100		
		4.75 mm (No. 4)	20-60	60-100	PARTICLE SIZE DISTRIBUTION REQUIRED.	
		1.18 um (No. 16)	10-30			
		300 um (No. 50)	0-10	10-30		
UNDERDRAIN PIPE		150 um (No. 100)		0-10		
		75 um (No. 200)	0-3	0-3		
		PIPE DIAMETER AND TYPE	MAXIMUM SLOT WIDTH (INCHES)	MINIMUM OPEN AREA (PER FOOT)		PIPE MUST CONFORM TO REQUIREMENTS OF ASTM DESIGNATION F949. THERE SHALL BE NO EVIDENCE OF SPLITTING, CRACKING, OR BREAKING WHEN THE PIPE IS TESTED PER ASTM TEST METHOD D2412 IN ACCORDANCE WITH F949 SECTION 7.5 AND ASTM F794 SECTION 8.5.
		4-INCH SLOTTED PVC/HDPE	0.032	1.90 IN²	REQUIRED	
		6-INCH SLOTTED PVC/HDPE	0.0320	1.98 IN²		
IMPERMEABLE LINER			THICKNESS 0.76 mm (30 mil)	TEST METHOD		
			THICKNESS, % TOLERANCE	±5	ASTM D 1593	
			TENSILE STRENGTH, kN/m (lb/in)	12.25 (70)	ASTM D8 82, METHOD B	
			MODULUS AT 100% ELONGATION, kN/m (lb/in)	5.25 (30)	ASTM D8 82 METHOD B	
			ULTIMATE ELONGATION, %	350	ASTM D8 82, METHOD B	
			TEAR RESISTANCE, N (lbs)	38 (8.5)	ASTM D 1004	
			LOW TEMPERATURE IMPACT, °C (°F)	-29 (-20)	ASTM D 1790	
			VOLATILE LOSS, % MAX.	0.7	ASTM D8 82, METHOD A	
			PINHOLES, NO. PER 8 m² (NO. PER 10 YD²)	1 (MAX)	N/A	
			BONDED SEAM STRENGTH, % OF TENSILE	80	N/A	
						THERMAL WELDING REQUIRED FOR FULLY LINED FACILITIES (NOT A CURTAIN). LEAK TESTING IN THE FIELD REQUIRED.

TABLE 2: NATIVE SEED MIX FOR BIO-RETENTION SYSTEMS

COMMON NAME	SCIENTIFIC NAME	VARIETY	PLS ² (LBS/ACRE)	OUNCES PER ACRE
SAND BLUESTEM	ANDROPOGON HALLII	GARDEN	3.5	
SIDEOATS GRAMA	BOUTELOUA CURIPENDULA	BUTTE	3	
PRAIRIE SANDREED	CALAMOVILFA LONGIFOLIA	GOSHEN	3	
INDIAN RICEGRASS	ORYZOPSIS HYMENOIDES	PALOMA	3	
SWITCHGRASS	PANICUM VIRGATUM	BLACKWELL	4	
WESTERN WHEATGRASS	PASCOPYRUM SMITHII	ARIBA	3	
LITTLE BLUESTEM	SCHIZACHYRIUM SCOPARIUM	PATURA	3	
ALKALI SACATON	SPOROBOLUS AIROIDES		3	
SAND DROPSEED	SPOROBOLUS CRYPTANDRUS		3	
PASTURE SAGE ¹	ARTEMISIA FRIGIDA			2
BLUE ASTER	ASTER LAEVIS			4
BLANKET FLOWER	GAILLARDIA ARISTATA			8
PRAIRIE CONEFLOWER	RATIBIDA COLUMNIFERA			4
PURPLE PRAIRIECLOVER	DALEA (PETALOSTEMUM) PURPUREA			4
SUB-TOTALS			27.5	22
TOTAL LBS PER ACRE				28.9

REVIEWED
FOR
CODE
COMPLIANCE
01/12/2024



410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointse.com

INT							
REVISIONS	CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE CHECK VALVE SPECS, EARTHWORK CALCS	RS					
		CSMP REVISIONS					
DATE							
1	9/13/23						
2	11/8/23						

HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS
INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487

HORIZONTAL SCALE

DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DS/CAAC
DESIGN BY: AP/DS/CAAC/WNM
REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A FORMAT OTHER THAN 24" X 36", THE GRAPHIC SCALE SHOULD BE UTILIZED.










DRAWING:
BIORETENTION
NOTES AND
SPECIFICATIONS

SHEET NO.


C7







REVIEWED
FOR
CODE
COMPLIANCE
01/12/2024



410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointsse.com

No.	DATE	REVISIONS	INT
1	9/13/23	CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	
2	11/8/23	CSPM REVISIONS	

HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS
INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487

HORIZONTAL SCALE
0 10' 20'
SCALE: 1" = 10'




DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/WNM
REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36", THE
GRAPHIC SCALE SHOULD BE UTILIZED.


DRAWING:
ACCESS ROAD
SECTION VIEWS

SHEET NO.
C9





**REVIEWED
FOR
CODE
COMPLIANCE**
01/12/2024



**410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointssse.com**


No.	DATE	REVISIONS	INT
1	9/13/23	CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	
2	11/8/23	CSMP REVISIONS	RS

**HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS**

**INDIAN MEADOWS FILL NO. 4
LOTS 1 AND 2**

STEAMBOAT SPRINGS, CO 80487

HORIZONTAL SCALE




DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/WNM
REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36", THE
GRAPHIC SCALE SHOULD BE UTILIZED.


UTILITY PLAN

SHEET NO.

C10



NOT FOR CONSTRUCTION



OPEN SPACE

PROPERTY LINE


LOT 1 OPEN SPACE: 26,800 SF

LOT 2 OPEN SPACE: 26,600 SF

REVIEWED
FOR
CODE
COMPLIANCE
01/12/2024

HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS
INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487

HORIZONTAL SCALE



SCALE: 1" = 20'

CONTOUR INTERVAL = 1 FT

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

OPEN SPACE PLAN

SHEET NO.

C12

DRAWING:

SHEET NO.

C12

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC

DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.

DATE: 11-17-2023


JOB #: 1448-005

DRAWN BY: AP/DSC/AAC


DESIGN BY: AP/DSC/AAC/WMM

REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD



NOT FOR CONSTRUCTION



PHASE 1 - HOLIDAY INN EXPRESS

PHASE 2 - HOTEL B

GENERAL NOTES:

1. SANITARY SERVICES PROVIDED TO BOTH HOLIDAY INN EXPRESS AND HOTEL B WILL BE DONE DURING PHASE 1
2. WATER SERVICES PROVIDED TO HOLIDAY INN EXPRESS WILL BE DONE DURING PHASE 1. WATER SERVICES PROVIDED TO HOTEL B WILL BE DONE DURING PHASE 2
3. ALL ELECTRICAL AND GAS SERVICES PROVIDED TO HOLIDAY INN EXPRESS WILL BE DONE DURING PHASE 1.
4. ALL ELECTRICAL AND HAS SERVICES PROVIDED TO HOTEL B WILL BE DONE DURING PHASE 2.
5. PARKING LOT WILL BE PAVED IN IT'S ENTIRETY DURING PHASE 1, BUT STRIPING WILL ONLY BE DONE FOR THE HOLIDAY INN EXPRESS' PORTION OF THE PARKING LOT DURING PHASE 1. STRIPING FOR HOTEL B WILL BE DONE DURING PHASE 2.
6. ALL STORMWATER IMPROVEMENTS WILL BE DONE DURING PHASE 1.

PHASE 1 PARKING:

PHASE 1 WILL INCLUDE PAVING OF THE ENTIRE PARKING LOT AND STRIPING FOR HOLIDAY INN'S SIDE OF THE PARKING LOT. PHASE 1 WILL PROVIDE 89 PARKING SPACES FOR HOLIDAY INN EXPRESS.

PHASE 2 PARKING:

PHASE 2 WILL INCLUDE STRIPING FOR HOTEL B'S SIDE OF THE PARKING LOT. PHASE 2 WILL PROVIDE 73 PARKING SPACES FOR HOTEL B. A TOTAL OF 162 PARKING SPACES WILL BE AVAILABLE WHEN PHASE 2 CONCLUDES.


**REVIEWED
FOR
CODE
COMPLIANCE**
01/12/2024

**HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS**

**INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2**

STEAMBOAT SPRINGS, CO 80487

HORIZONTAL SCALE



CONTOUR INTERVAL = 1 FT

DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/WNM
REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36", THE
GRAPHIC SCALE SHOULD BE UTILIZED

PHASING PLAN

DRAWING:

SHEET NO.

C13



**410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointsse.com**

No.	DATE	REVISIONS	INT
1	9/13/23	CURE INLET REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	
2	11/8/23	CSPM REVISIONS	RS



PROPERTY LINE

PROPOSED EASEMENTS

**REVIEWED
FOR
CODE
COMPLIANCE**
01/12/2024

The diagram illustrates the layout of various utility lines. A vertical line on the left represents the main utility corridor. Five horizontal lines branch off to the right, each representing a different utility service. Each service is identified by a set of markers (dots or dashes) and a text label. The services and their markers are: Gas Service (four dashes), Sewer Main, 8" (five dashes), Water Main (four dashes), Buried Electrical (three dashes), and Telecommunications (three dashes).

Utility Service	Marker Pattern
GAS SERVICE	— — — —
SEWER MAIN, 8"	— — — — —
WATER MAIN	— — — —
BURIED ELECTRICAL	— — —
TELECOMMUNICATIONS	— — —

1. ALL PROPOSED ACCESS EASEMENTS SHALL BE PRIVATE.
2. ALL PROPOSED UTILITY EASEMENTS SHALL BE PRIVATE.
3. ALL PROPOSED DRAINAGE EASEMENTS SHALL BE PRIVATE.

LOT 1 INDIAN MEADOWS, FILING 3, LOCATED IN THE SE 1/2 OF SECTION 28, TOWNSHIP 6 NORTH, RANGE 84 WEST OF THE 6TH P.M. CITY OF STEAMBOAT SPRINGS, COUNTY OF ROUTT, STATE OF COLORADO

CONTOUR INTERVAL = 1 FT

DATE: 11-17-2023

JOB #: 1448-005

DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/MNM

REVIEW BY: FPSE


IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36", THE


GRAPHIC SCALE SHOULD BE UTILIZED.

DRAWING:


SHEET NO.

C14





TYPICAL ROAD SECTION - 50' ROW
N.T.S.





STANDARD PAVEMENT SECTION
N.T.S.

ASPHALT SECTION DETAIL
N.T.S.

GENERAL NOTES

- ON CURVES 3 DEGREES OR SHARPER, CURBS AND/OR GUTTERS ARE TO BE PLACED ON THE ARC OF THE CURVE UNLESS OTHERWISE NOTED ON THE PLANS. A MAXIMUM CHORD LENGTH OF 10 FEET MAY BE USED WHEN THE DEGREE OF CURVE IS LESS THAN 3 DEGREES.
- CONCRETE SHALL BE CLASS B.
- PROFILE GRADE OF CURBS AND GUTTERS SHALL BE LOCATED AT THE FLOW LINE.
 - EXPANSION JOINTS SHALL BE INSTALLED WHEN ABUTTING EXISTING CONCRETE OR FIXED STRUCTURE. EXPANSION JOINT MATERIAL SHALL BE 1/2 IN. THICK AND SHALL EXTEND THE FULL DEPTH OF CONTACT SURFACE.
- GUTTER CROSS SLOPES SHALL BE 1/4 IN./FT. WHEN DRAINING AWAY FROM CURB AND 1 IN./FT. WHEN DRAINING TOWARD CURB.
- WHEN THE BARS ARE REQUIRED, THE GUTTER THICKNESS SHALL BE INCREASED TO THE PAVEMENT THICKNESS. BARS SHALL BE EPOXY-COATED #4 CONFORMING TO ASTM A 284M AND SPACED 2 FT.-6 IN. THEY SHALL BE INSERTED 1/2 AND 1/2 LENGTH INTO THE GUTTER.
- CONCRETE SHALL CONTAIN 1.5 POUNDS PER CUBIC YARD APPROVED POLYPROPYLENE FIBERS AND HAVE A NOMINAL AGGREGATE SIZE OF 3/8 IN.




PARKING PAVEMENT MARKINGS
NOT TO SCALE



R7-8




VAN ACCESSIBLE
R7-8 & R7-8P



Parking Sign Notes:

- Parking space identification signs must include the International Symbol of Accessibility: A profile view of a wheelchair with an occupant.
- Signs identifying van parking spaces must contain the designation "Van Accessible"
- The required "Van Accessible" designation is intended to be informative, not restrictive, in identifying those spaces that are better suited for van use.
- Enforcement of motor vehicle laws, including parking privileges, is a local matter.
- Signs must be 60" Min. above finished ground surface measured from bottom of the sign.



SEE GENERAL NOTES, PAGE D700-A790
FOR ALL CURB RAMP ALTERNATES (A, B, C)

ALTERNATE RAMPS "B" & "C" 740


Sidewalk Notes:

- Minimum Sidewalk width shall be 4'-0" for residential, 5'-0" for commercial, and 6'-0" clear width whenever attached to the curb.
- Sidewalk slope shall be maximum of 2% cross slope.
- Whenever the width of the sidewalk is less than 5'-0", a 5' x 5' passing area with a maximum 2% slope in any direction at intervals of 200' shall be installed.
- Whenever changing direction in a sidewalk, install a 5' x 5' passing area with maximum 2% slope in any direction.
- Objects such as tree branches, signs, water fountains, etc. shall not protrude into the sidewalk more than 4" at the heights between 27" and 80".


Ramps:

- When the rise in elevation is greater than 30" a series of ramps and landings will be required.
- Landing shall be 5'-0" in length and no greater than 2% in any direction.
 - The maximum of a run is determined by the rise (30" maximum) and slope, as shown in the following table

Max. Rise	Slope	Max. Length	Max. Rise	Slope	Max. Length
30 in.	1:12	30 ft.	30 in.	1:16	40 ft.
30 in.	1:13	32.5 ft.	30 in.	1:17	42.5 ft.
30 in.	1:14	35 ft.	30 in.	1:18	45 ft.
30 in.	1:15	37.5 ft.	30 in.	1:19	47.5 ft.



NOTE:
FOR MORE DETAILED PROFILES
SEE SHEET DR3 OF DRAINAGE REPORT



NOTES -- 790


General Notes:

- The standard curb-ramp lay-out shall be used whenever possible. Any deviation from the standard curb-ramp plans shall be approved by the City Engineer or designee on a case by case basis.
- The standard curb-ramp drawings supersede all previous drawings and shall be part of the new curb ramp standard drawings.
- All alternate ramps shall be approved by the City Engineer prior to construction.

Curb Ramp Notes:

- A curb ramp is defined as the entire concrete surface which includes the ramp & flared sides. The 4' - 0" wide center portion, including the detectable surface, shall have the sloped plane of 8.33% (1:12) maximum, and cross slope, not to exceed 2%. The "flared side" of the ramp shall lie on a slope of 10% (1:10) maximum measured along the curb. The curb ramp shall have a surface tolerance of 1/4" per 10 foot straight edge maximum.
- The ramp center line and path of travel must be parallel to the sidewalk. The full width of the ramp shall lie within the crosswalk area. It is desirable that the location of the ramp be as close as possible to the center of the crosswalk.
- The 4'-0" min. distance between flared sides of the two adjacent curb ramps may be reduced to 3'-0" with documentation of hardship indicating legal and or physical constraints provided to the City Engineer.
- Existing utility boxes and covers shall be adjusted flush with the curb ramp surface and shall not straddle any change in plane or material. Existing utility box frames and covers shall have matching surface finish on the entire frame and cover. New utility boxes shall not be placed within the detectable border.
- The surface of the curb ramp and detectable surface material shall be stable, firm and slip resistant. The concrete curb ramp surface shall be broom finished transverse to the axis of the ramp and shall be slightly rougher than the finish of the adjacent sidewalk surface.
- A level landing 4'-0" deep, with a 2% maximum slope in each direction shall be provided at the upper end of each curb ramp to allow safe egress from the ramp surfaces. The width of the level landing shall be at least as wide as the width of the ramp.
- When vertical obstructions are present near the curb at the end of the flared side or when the curb-ramp is diagonal to the curb which will result in an extremely long flared side surface, the affected flared side may be cut and terminated perpendicular to the curb, provided that the maximum slope of 10% is achieved on each of the resulting planes.
- The length of ramp may be constructed up to 30 feet long to achieve the slope requirement.
- Existing vertical utility poles or street light poles may be incorporated into the flared sides, if necessary. The vertical obstruction shall be a minimum of 6 inches away from the edge of the ramp. Pedestrian crosswalk push button poles, fire department call box poles and other poles with activated devices, may not be placed in the curb-ramp at any time. No new vertical obstructions may be located in the curb ramp or the grooved border.

REVIEWED
FOR
CODE
COMPLIANCE
01/12/2024



410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointse.com

INT	REVISIONS	DATE	No.
	CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	9/13/23	1
	CSMP REVISIONS	11/8/23	2

HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS
INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487

DETAILS N.T.S.

DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/WMM
REVIEW BY: FPSE

IF THIS DRAWING IS PRESENTED IN A FORMAT OTHER THAN 24" X 36" THE GRAPHIC SCALE SHOULD BE UTILIZED.


DETAILS (1)

DRAWING:

SHEET NO.


C15






NOTES:
A GUIDE FOR DESIRABLE TRENCH WIDTH (W) AT THE TOP OF THE PIPE SHALL BE THE NOMINAL DIAMETER OF THE PIPE PLUS 12 INCHES ON EACH SIDE OF THE PIPE.
A SECOND PAVEMENT CUT SHALL BE REQUIRED PRIOR TO PLACING THE ASPHALT PATCH. REMOVE ALL IRREGULAR ASPHALT EDGES A MINIMUM OF 12-INCHES BEYOND ANY DAMAGED SURFACE TO A CLEAN VERTICAL EDGE. APPLY A BITUMINOUS TACK COAT PRIOR TO PLACING THE ASPHALT PATCH.
THE ASPHALT PATCH SHALL BE PLACED IN A 4-INCH LIFT AND ROLLER COMPACTED TO MATCH THE ADJACENT ASPHALT EDGES.
SUB-BASE MATERIALS SHALL CONSIST OF 4-INCHES OF ROAD BASE ON 8-INCHES OF PIT-RUN. COMPACTION REQUIREMENTS SHALL EXCEED 95% MAXIMUM DRY DENSITY AS DETERMINED BY THE AASHTO T-180 TEST PROCEDURES.
PAY LIMIT WIDTH FOR ASPHALT PATCH SHALL BE MEASURED AS FOLLOWS: PAY WIDTH = W + 2 FT.



TRENCH CROSS SECTION DETAIL
N.T.S.




WATER SERVICE LINE DETAIL
N.T.S.




SERVICE LATERAL DETAIL
N.T.S.




SEWER SERVICE & FOUNDATION DRAIN CLEANOUT
N.T.S.



WATER AND SEWER CROSSING CONDITION DETAIL
NOT TO SCALE



THRUST BLOCK DETAILS
NOT TO SCALE



FIRE HYDRANT DETAIL
N.T.S.


City Of
Steamboat Springs
Water & Sewer

P.O. BOX 775088
STEAMBOAT SPRINGS, CO
(970) 879-2060 FAX (970) 879-8851

STANDARD DETAILS

Drawn by: GLB
Scale: N.T.S. Date: 2/24/00
Revision description:
Sheet number 7 of 17

REVIEWED
FOR
CODE
COMPLIANCE
01/12/2024



410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointse.com

INT	RS	CSMP REVISIONS	REVISIONS	DATE	No.
			CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	9/13/23	1
			CSMP REVISIONS	11/8/23	2

HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS
INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487

DETAILS N.T.S.

DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/IDSC/AAC
DESIGN BY: AP/IDSC/AAC/WNM
REVIEW BY: FPSE
IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36" THE
GRAPHIC SCALE SHOULD BE UTILIZED.


DETAILS (2)

DRAWING:

SHEET NO.

C16





1. THIS PLAN SHALL BE KEPT ON SITE AT ALL TIMES AND UPDATED TO REFLECT ANY CHANGES.
2. CONCRETE WASTE AND WASHOUT WATER FROM MIXING TRUCKS SHALL BE CONTAINED ON SITE, REMOVED FROM THE SITE, AND PROPERLY DISPOSED. MATERIALS SHOULD NOT ENTER STATE WATERS.
3. CONTRACTOR IS RESPONSIBLE FOR INSTALLING AND MAINTAINING TEMPORARY EROSION AND SEDIMENT CONTROL DURING CONSTRUCTION AND ESTABLISHING ANY REQUIRED PERMANENT BEST MANAGEMENT PRACTICES (BMPs).
4. CONTRACTOR IS RESPONSIBLE FOR COMPLYING WITH ALL LOCAL, STATE, AND FEDERAL LAWS. IN ADDITION CONTRACTOR MUST OBTAIN REQUIRED PERMITS.
5. CLEARING OR GRADING SHALL NOT BEGIN UNTIL ALL SEDIMENT CONTROL DEVICES HAVE BEEN INSTALLED.
6. THE CONTRACTOR SHALL PROMPTLY REMOVE ALL SEDIMENT, MUD, AND CONSTRUCTION DEBRIS THAT MAY ACCUMULATE IN THE RIGHT OF WAY, PRIVATE PROPERTY, OR WATERWAYS AS A RESULT OF THE CONSTRUCTION ACTIVITIES.
7. ALL INGRESS, EGRESS POINTS AND VEHICLE ACCESS POINTS ONTO DISTURBED SITE MUST BE STABILIZED WITH A VEHICLE TRACKING CONTROL PAD. ACCESS SHALL ONLY BE VIA APPROVED LOCATIONS AS SHOWN ON APPROVED CSMP.
8. SOIL STABILIZATION MEASURES SHALL BE IN PLACE AND AREAS ARE TO BE REVEGETATED: (1) FOR STOCKPILES, IF INACTIVE FOR MORE THAN 30 DAYS (2) FOR AREAS OF LAND DISTURBANCE WITHIN ONE GROWING SEASON.
9. INLET PROTECTION SHALL BE INSTALLED IN CONJUNCTION WITH STORM DRAIN INLETS WHERE DRAINAGE AREA IS NOT VEGETATED.
10. BMPs SHALL BE USED, MODIFIED, AND MAINTAINED WHENEVER NECESSARY TO REFLECT CURRENT CONDITIONS. BMPs SHALL BE INSPECTED WEEKLY AND AFTER EVERY PRECIPITATION EVENT. ACCUMULATED SEDIMENT SHALL BE REMOVED FROM BMPs WHEN THE SEDIMENT LEVEL REACHES $\frac{1}{2}$ THE HEIGHT OF THE BMP.
11. EMERGENCY ACCESS MUST BE KEPT OBSTACLE FREE AND PASSABLE AT ALL TIMES.
12. FOR ANY WORK TO BE DONE IN THE RIGHT OF WAY, COORDINATE WITH THE CITY CONSTRUCTION SITE MANAGER REGARDING SPECIAL PERMITTING.
13. WHERE REQUIRED AS PART OF THE ROW PERMIT OR WHERE SITE WORK AFFECTS THE PEDESTRIAN OR VEHICLE TRAVEL WAY, TRAFFIC CONTROL SHALL BE INSTALLED. ALL TRAFFIC CONTROL SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION.
14. SIDEWALKS ADJACENT TO CONSTRUCTION SITES SHALL BE MAINTAINED, FOR PUBLIC USE, BY THE CONTRACTOR. IN AREAS WHERE CONSTRUCTION IS TAKING PLACE NEXT TO THE SIDEWALK AND OVERHEAD HAZARDS ARE POSSIBLE, SITE IS RESPONSIBLE FOR INSTALLING AND MAINTAINING SIDEWALK PROTECTION.
15. NO TRUCK DELIVERIES PRIOR TO 8:00 A.M. AND AFTER 5:00 P.M., MONDAY THROUGH FRIDAY.

REVIEWED
FOR
CODE
COMPLIANCE
01/12/2024

No.	DATE	REVISIONS	INT
1	9/13/23	CURB INLET'S REPLACED WITH CURB CUTS, INLET, SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	
2	11/8/23	CSPM REVISIONS	RS





INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487

7

STORMWATER MANAGEMENT PLAN



C17





PIPE DIAMETER, D _o (INCHES)	DISCHARGE, Q (CFS)	APRON LENGTH, L _a (FT)	RIPRAP D50 DIAMETER MIN (INCHES)
8	2.5	5	4
	5	10	6
	10	10	6
12	5	10	4
	10	13	6
	10	16	6
18	20	23	9
	30	26	12
	40	26	16
24	30	16	9
	40	26	9
	50	26	12
	60	30	16

RIPRAP OUTLET PROTECTION
NOT TO SCALE



CONCRETE WASHOUT DETAILS
NOT TO SCALE



REVIEWED
FOR
CODE
COMPLIANCE
01/12/2024

410 S. Lincoln Ave, Unit 15
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointssse.com

NO.	DATE	REVISIONS	INT
1	9/13/23	CURB INLETS REPLACED WITH CURB CUTS, INLET SCHEDULE, CHECK VALVE SPECS, EARTHWORK CALCS	RS
2	11/8/23	CSMP REVISIONS	

HOLIDAY INN EXPRESS & HOTEL B
CONSTRUCTION PLANS
INDIAN MEADOWS FIL. NO. 4
LOTS 1 AND 2
STEAMBOAT SPRINGS, CO 80487

DETAILS N.T.S

DATE: 11-17-2023
JOB #: 1448-005
DRAWN BY: AP/DSC/AAC
DESIGN BY: AP/DSC/AAC/WNM
REVIEW BY: FPSE
IF THIS DRAWING IS PRESENTED IN A FORMAT OTHER THAN 24" X 36", THE GRAPHIC SCALE SHOULD BE UTILIZED.

DRAWING:

SHEET NO.

C18