



For Pool Pros

AQUATIC SYSTEMS

[PRODUCTS](#) | [PENTAIR PARTNERS](#) | [DEALER RESOURCES](#) | [MANUALS](#) | [BROCHURES](#) | [RECALLS/DRAIN SAFETY](#) | [SAVE ENERGY](#) | [IMAGE LIBRARY](#) | [NEWS](#)
[Home >> Pool Pros >> Products >> Filters >> Sand >> Triton® II Side Mount Filters](#)

Products [-]

 Click on [+] to expand list
 Click on [-] to collapse list
[Aboveground Systems \[+\]](#)[Automation \[+\]](#)[Cleaners \[+\]](#)[Commercial](#)


Filters [-]

[Cartridge \[+\]](#)[D.E. \[+\]](#)

Sand [-]

[Cristal-Flo II Top-Mount Filters](#)[Sand Dollar Top Mount Filter](#)[Sand Dollar Top Mount Filter with ClearPro Technology](#)[System 3 Sand Filters](#)[Tagelus Top Mount Filter](#)[Tagelus Top Mount Filters with ClearPro Technology](#)➔ [Triton II Side Mount Filters](#)[Triton II Side Mount with ClearPro Technology](#)[Filter Kits \[+\]](#)[Heaters & Heat Pumps \[+\]](#)[Lighting \[+\]](#)[Maintenance & Safety](#)[Equipment \[+\]](#)[Pumps \[+\]](#)[Sanitizers \[+\]](#)[Valves \[+\]](#)[Water Features \[+\]](#)[White Goods \[+\]](#)

Replacement Parts [+]

 Click on [+] to expand list
 Click on [-] to collapse list


TRITON® II

Side Mount Filters

Fiberglass Sand Filter without Valves

The original and still the industry standard. Our unique process creates a one-piece, fiberglass reinforced tank with UV-resistant surface finish for years of unequaled strength and durability. This unique method locks in fiberglass, preventing fibers from "blooming" under harsh conditions.

Features

Heavy-duty closure provides easy inspection, and features an easy-to-read pressure gauge with air relief valve

Swing-away diffuser allows instant access to sand and all internal parts

All internal parts are threaded for ease of service

Internal air bleed

Bulkhead connectors are threaded for easy installation and service

Combination sand and water drain makes servicing and winterizing fast and easy

Maximum Operating Pressure 50 psi

[Manuals](#)[Brochures](#)[Specs](#)[More](#)

Product Specifications

		TRITON II SAND FILTERS											
		Turnover Capacity (Gallons)											
Product Model		Effective Filtration Area (Sq Ft)	Flow Rate (GPM)	Flow Rate (GPM Comm)	8 Hour	10 Hour	12 Hour	Filter Media Pea Gravel Required (Lbs)	Filter Media Sand Required (Lbs)	All Sand Required (Lbs)	Carton Qty	Carton Wt (Lbs)	
140236	TR 40	1.92	38	38	18240	22800	27360	50	125	175	1	25	
140249	TR 50	2.46	49	49	23520	29400	35280	50	175	225	1	34	
140264	TR 60	3.14	63	63	30240	37800	45360	75	250	325	1	40	
140210	TR 100	4.91	98	74	47040	58800	70560	150	450	600	1	65	
140243	TR 140	7.06	141	106	67680	84600	101520	275	650	925	1	75	

TRITON II VALVE OPTIONS¹

Product	Description	Carton Qty	Carton Wt (Lbs)
261173	1-1/2 in. MPV, for sand filters (SM 10-3)	1	6
261049	2 in. HiFlow valve, no plumbing	1	7
261050	2 in. HiFlow valve w/plumbing, for sand filters	1	11
261055	2 in. MPV, for sand filters (SM 20-3)	1	10
263064	Push Pull 7.5" Center Valve, Almond PVD	1	5

1: Valves must be purchased separately.

Certifications



NSF Certified

[SIGN UP FOR ENEWSLETTER](#) | [WHERE TO BUY](#) | [ABOUT US](#) | [TERMS OF USE](#) | [SITE MAP](#) | [CONTACT US](#) | [PENTAIR.COM](#)

Copyright 2013 Pentair Ltd. All Rights Reserved.

[Aboveground Systems](#) | [Automation](#) | [Cleaners](#) | [Commercial](#) | [Filters](#) | [Heaters & Heat Pumps](#) | [Lighting](#) | [Maintenance & Safety Equipment](#) | [Pumps](#) | [Sanitizers](#) | [Valves](#) | [Water Features](#) | [White Goods](#)

<http://www.pentairpool.com/pool-pro/products/filters-sand-triton-ii-side-mount-filters-183...> 7/13/2013