THE ASTRI Steamb	D, 2410 S BOAT SPRIN				
ž.	STEAN	CLIENT IBOAT ESC	: QUIAR, LP.	SH	HEET INDE
8-1015	~		,	NO.	DESCRIPTION
- Ski Time Square Dr					1 COVER SHEET
				C-02	2 GENERAL NOTES
PROJECT LOCATION LAT: 40.457588 LONG: -106.799540				C-03	3 SITE PLAN
EUNG100.799540				C-04	4 PROFILE VIEWS
				C-05	5 PROFILE VIEWS
				C-06	6 SECTION VIEWS
Sto Trail Ln pomate				C-07	7 SECTION VIEWS
				C-08	8 SECTION VIEWS
				C-09	9 SECTION VIEWS
				C-10	0 SELF-DRILLING S
© 2024 Microsoft Corporation © 2024 TomTom				C-1	1 SOLID BAR SOIL
© 2024 Microsoft Corporation © 2024 TomTom				C-12	2 NAIL SCHEDULE
(NOT TO SCALE)				C-13	3 NAIL SCHEDULE
SHEET REVISIONS PROJECT NAME:					
DATE DESCRIPTION NO 05/08/24 ISSUED FOR PERMIT IFP THE ASTRID, 24	410 SKI TRA	IL LANE -	BUILDING	7	
SHEET TITLE:	COVER S				<b>GeoStabilizat</b>
	UVER S	ΠΕΕΙ			4475 E 74 Commerce C
THIS DRAWING IS FURNISHED SOLELY FOR THE USE OF OR IN CONNECTION WITH THIS PROJECT AND THE PROPRIETARY INFORMATION SHOWN HEREON IS NOT TO BE TRANSMITTED TO ANY OTHER ORGANIZATION WITHOUT SPECIFIC AUTHORIZATION BY	D BY: DATE:	PURSUIT NUMBER:	PROJECT NUMBER:	SHEET	Phone: 855.579.05 www.geos

# NS

# DEX

TES

VS STA 0+00 TO STA 1+25

VS STA 1+25 TO STA 2+47

NS STA 0+00 TO STA 0+39

VS STA 0+39 TO STA 0+72 AND STA 1+10 TO STA 1+65

NS STA 0+72 TO STA 1+10 AND STA 1+81 TO STA 2+30

NS STA 1+65 TO STA 1+81 AND STA 2+30 TO STA 2+47

G SOIL NAIL DETAILS

DIL NAIL DETAILS







### CONSTRUCTION SEQUENCE/WORK SCHEDULE

THE CONTRACTOR WILL PROVIDE AND INSTALL THE SPECIFIED SOIL NAILS AND SLOPE SURFACE TREATMENT PER THE CONSTRUCTION DOCUMENTS. THE ANTICIPATED CONSTRUCTION SEQUENCE IS AS FOLLOWS:

- DELINEATE LIMITS OF STABILIZATION. NOTIFY LOCAL UTILITIES PROVIDERS TO LOCATE AND MARK POTENTIAL UNDERGROUND FACILITIES. DAYLIGHTING OF UTILITIES IN POTENTIAL CONFLICT, AS NECESSARY. BY OTHERS
- 2. PREPARE THE WORK AREA FOR STABILIZATION CONSTRUCTION. BY OTHERS
- ESTABLISH TRAFFIC CONTROL, BY OTHERS. 2.1
- PREPARE SITE ACCESS, BY OTHERS. 2.2.
- EXCAVATE, REMOVE, AND DISPOSE OF SPOILS MATERIAL GENERATED DURING 3 EXCAVATION BY OTHERS
- MARK THE LOCATIONS OF THE PROPOSED SOIL NAILS WITH SURVEY MARKING PAINT. 5. INSTALLATION OF SOIL NAILS. NAILS WILL BE GROUTED DURING DRILLING UNLESS
- DIRECTED OTHERWISE BY GSI ENGINEER.
- 6. INSTALL SURFACE TREATMENT PER THE CONSTRUCTION DOCUMENTS.

### HOUSE KEEPING

THE SITE WILL BE ORGANIZED AND CLEAR OF ANY TRASH OR DEBRIS. ALL TRASH WILL BE PLACED IN A PROPER CONTAINER AND REMOVED AT THE END OF EACH WORK DAY.

#### SAFETY:

- ALL SAFETY PLANS FOR LIFTING, HEARING, DUST CONTROL, PPE ETC. WILL BE IN PLACE AND FOLLOWED ACCORDINGLY. PPE INCLUDES SAFETY VEST, STEEL TOED SHOES, HARD HAT, SAFETY GLASSES, RESPIRATOR DURING DUST PRODUCING ACTIVITIES, AND GLOVES.
- ALL FIELD PERSONNEL SHALL ATTEND SITE SPECIFIC ORIENTATION PRIOR TO BEING ON SITE, AS REQUIRED.
- DAILY PRE/POST JOB BRIEFINGS WILL BE HELD AND DOCUMENTED; ALL ON SITE PERSONNEL WILL BE REQUIRED TO REVIEW AND SIGN.

#### GENERAL DESIGN NOTES:

- TEMPORARY SHORING SHOTCRETE FACING AND SOIL NAILS DESIGNED IN GENERAL ACCORDANCE WITH FHWA-NHI-14-007, SOIL NAIL WALLS REFERENCE MANUAL, DATED FEBRUARY 2015
- GLOBAL STABILITY MODELED IN ROCSCIENCE SLIDE2 SOFTWARE FOR GLOBAL FACTOR OF SAFETY OF 1.3. CONSERVATIVE SOIL STRENGTH PARAMETERS WERE SELECTED BASED ON SUBSOIL AND FOUNDATION INVESTIGATION. THE ASTRID. 2410 SKI TRAIL LANE, STEAMBOAT SPRINGS, COLORADO, DATED DECEMBER 22, 2022. TRAFFIC SURCHARGE OF 250 PSF USED WHERE APPLICABLE.

#### SIZE AND TYPE OF NAILS:

- THE SOIL NAIL ELEMENTS SHALL CONSIST OF SELF-DRILLING SOIL NAILS. SACRIFICIAL DRILL BITS WILL BE ATTACHED TO THE SOIL NAIL PRIOR TO INSTALLING THE NAIL IN THE GROUND
- SACRIFICIAL DRILL BITS ARE NOT PERMANENTLY INCORPORATED INTO THE PROJECT AND MAY BE REMOVED AFTER DRILLING OR LEFT AT THE PROJECT FOR THE CONTRACTOR'S CONVENIENCE. SACRIFICIAL DRILL BITS ARE NOT END PRODUCTS. SACRIFICIAL DRILL BITS ARE NOT PRODUCED IN THE UNITED STATES.
- SOIL NAILS WILL BE CONSTRUCTED USING NON-DOMESTIC HOLLOW BAR.
- GSI ENGINEER MAY ELECT TO MODIFY THE NAIL TYPE, LENGTH OR INSTALLATION METHOD, DEPENDING ON ACTUAL DRILLING CONDITIONS.

#### SIZE AND TYPE OF ROCK ANCHOR:

- THE ROCK ANCHOR ELEMENTS SHALL CONSIST OF EPOXY COATED GRADE 75 #8 ALL-THREAD OF DOMESTIC MANUFACTURE.
- ROCK ANCHORS WILL BE GROUTED IN A 4" HOLE.

#### FACING AND DRAINAGE SYSTEM:

- DRAIN STRIPS WILL BE PROVIDED AND INSTALLED BETWEEN THE SOIL NAILS ALONG THE FACE OF THE EXCAVATION. THE DRAIN STRIPS SHALL BE PLACED WITH THE GEOTEXTILE SIDE AGAINST THE GROUND. DRAIN STRIPS WILL BE CONTINUOUS AND ANY SPLICES SHALL BE MADE WITH A ONE-FOOT MINIMUM OVERLAP SUCH THAT THE FLOW OF WATER IS NOT IMPEDED. DRAIN STRIPS SHALL EXTEND BEYOND THE FACE OF THE SHOTCRETE AT THE DOWNHILL FACE.
- DRAIN STRIPS SHALL BE MINIMUM 12" WIDE. ٠

### REINFORCING STEEL PLACEMENT:

- WELDED WIRE MESH WILL BE PLACED ALONG THE FACE OF THE EXCAVATION WITH A SEPARATION BETWEEN THE WIRE MESH AND THE SOIL AS CALLED OUT IN THE DETAILS.
- NO. 4 REBAR WILL BE TIED TO THE WIRE MESH. VERTICAL BARS WILL EXTEND FOR APPROXIMATELY 36" AND THE HORIZONTAL BARS WILL BE CONTINUOUS (WITH A MINIMUM OF 24" OVERLAP SPLICES) IN THE SHOTCRETE.

### BEARING PLATE PLACEMENT:

STEEL BEARING PLATES WILL BE PLACED OVER THE NAILS AND ATTACHED WITH A HEX NUT TO SECURE THE WIRE MESH AND REBAR DURING SHOTCRETE PLACEMENT. IF THE SOIL NAILS EXTEND BEYOND THE HEX NUTS OR WELDED PLATES, THEY WILL BE TRIMMED

### SHOTCRETE APPLICATION:

SHOTCRETE WILL BE PLACED FROM THE LOWER PART OF THE AREA UPWARDS TO PREVENT ACCUMULATION OF REBOUND. THE NOZZLE WILL BE ORIENTED A PROPER DISTANCE FROM AND APPROXIMATELY PERPENDICULAR TO THE WORKING FACE SO THAT REBOUND WILL BE MINIMAL AND COMPACTION WILL BE MAXIMIZED. CARE WILL BE TAKEN WHILE ENCASING REINFORCING STEEL AND MESH TO KEEP THE FRONT FACE OF THE REINFORCEMENT CLEAN DURING PLACEMENT OPERATIONS, SO THAT SHOTCRETE BUILDS UP FROM BEHIND, TO ENCASE THE REINFORCEMENT AND PREVENT VOIDS OR POCKETS FROM FORMING.

#### GROUT MIX DESIGN:

- BY GSI ENGINEER

#### SHOTCRETE MIX DESIGN:

- •

### GSI STANDARD SHOTCRETE MIX DESIGN:

MATERIAL 3/8" ROCK SAND CEMENT WATER FLY ASH

#### AIR ENTRAINMENT 0.40 TO 0.50 WATER/CEMENT RATIO

MATERIAL
3/8" ROCK
SAND
CEMENT
WATER
FLY ASH
AIR ENTRAINMENT
0.40 TO 0.50 WATER

DATE 05/08/24	SHEET REVISIONS DESCRIPTION ISSUED FOR PERMIT	NO IFP	PROJECT NAME:		ID, 2410	SKI TRA	IL LANE -	BUILDING	F 7	-
			SHEET TITLE:		GEN	IERAL	NOTES			<b>GeoStabili</b> 4475 E Commerce
PROJECT TRANSMITT GEOS	ING IS FURNISHED SOLELY FOR THE USE OF OR IN CONNECTION T AND THE PROPRIETARY INFORMATION SHOWN HEREON IS N TED TO ANY OTHER ORGANIZATION WITHOUT SPECIFIC AUTHO STABILIZATION INTERNATIONAL. (GSI). THE DESIGN IS ONLY V UCTED AND SUPERVISED BY GSI OR ITS AUTHORIZED SUBCON	IOT TO BE RIZATION BY ALID IF	DRAWN BY: FHT	DESIGNED BY: FHT	CHECKED BY: EL/MWL	DATE: 05/08/2024	PURSUIT NUMBER: 166127629	PROJECT NUMBER: 240057CO0N	SHEET C-02	Phone: 855.579 www.g

DESIGN 28 DAY COMPRESSIVE STRENGTH = 3.000 PSI

GROUT SLURRY SHALL CONSIST OF A NEAT CEMENT MIXTURE OF CLEAN WATER AND PORTLAND CEMENT. NO ADDITIONAL ADMIXTURES SHALL BE USED UNLESS APPROVED

THE W/C SHALL RANGE BETWEEN 0.5 AND 0.6 AS DETERMINED BY A MUD BALANCE SP. GR. VALUE BETWEEN 1.83 AND 1.74.

SHOTCRETE SHALL COMPLY WITH THE REQUIREMENTS OF ACI 506.2, "SPECIFICATIONS FOR MATERIALS, PROPORTIONING AND APPLICATION OF SHOTCRETE", EXCEPT AS OTHERWISE SPECIFIED. SHOTCRETING CONSISTS OF APPLYING ONE OR MORE LAYERS OF CONCRETE CONVEYED THROUGH A HOSE PNEUMATICALLY PROJECTED AT A HIGH VELOCITY AGAINST A PREPARED SURFACE.

THE WET-MIX PROCESS CONSISTS OF THOROUGHLY MIXING ALL THE INGREDIENTS, INTRODUCING THE MIXTURE INTO THE DELIVERY EQUIPMENT AND DELIVERING IT, BY POSITIVE DISPLACEMENT, TO THE NOZZLE. AIR JET THE WET-MIX SHOTCRETE FROM THE NOZZLE AT HIGH VELOCITY ONTO THE SURFACE.

GSI STANDARD SHOTCRETE MIX DESIGN SHALL BE USED UNLESS SHOTCRETE TEMPERATURES ARE ANTICIPATED TO REACH AND/OR EXCEED 85°F. IN THIS EVENT, GSI HOT WEATHER MIX MAY BE USED. SET TIME CONTROLLING ADDITIVES (I.E. HYDRATION STABILIZERS, RETARDERS) MAY BE USED PER THE MANUFACTURER SPECIFICATIONS AND UNDER THE DIRECTION OF A GSI ENGINEER.

WEIGHT PER CUBIC YARD 650 LBS 1800 LBS 750 LBS 300 LBS 150 LBS 6% (1.6 FT<sup>3</sup>)

GSI HOT WEATHER SHOTCRETE MIX DESIGN:

WEIGHT PER CUBIC YARD 600 LBS 1,800 LBS 700 LBS 315 LBS 300 LBS 6% (1.6 FT<sup>3</sup>) 0.40 TO 0.50 WATER/CEMENT RATIO





### ISSUED FOR PERMIT



74th Ave, Suite 100 e City, CO 80022 USA .0536 | Fax: 970.245.7737 eostabilization.com








### NOTES:

1. NAIL LOCATIONS SHOWN ARE APPROXIMATE.

### LEGEND:


- **18' EMBEDMENT SOIL NAIL**



### NOTES:

1. NAIL LOCATIONS SHOWN ARE APPROXIMATE.

### LEGEND:




NOTES: 1. EXCAVATE SLOPE AT 1H:12V.

4	周	闔	崮








1. EXCAVATE SLOPE AT 1H:12V.








1. EXCAVATE SLOPE AT 1H:12V.








1. EXCAVATE SLOPE AT 1H:12V.

闔	崮	凒	闔	Ä	Ë

### **REVIEWED** FOR CODE COMPLIANCE 04/01/2025






- 1. LAP SPLICE LENGTH
- NO. 4 REBAR 24" MINIMUM
- NO. 5 REBAR 30" MINIMUM
- 2. WELDED WIRE MESH TO HAVE A MINIMUM OF 8" OVERLAP (2 SQUARES OVERLAP FOR 4 x 4 MESH).
- 3. REBAR CHAIRS OR EQUIVALENT TO BE USED TO ENSURE SUFFICIENT CONCRETE COVER BETWEEN GROUND SURFACE AND **REINFORCEMENT. 2 TO 3 DOBIES PER** 5' x 10' SHEET OF MESH, TYPICAL.
- 4. HORIZONTAL WALERS ARE CONTINUOUS







	1. 1.	<u>TES:</u> LAP SPLICE LENGTH 1. NO. 4 REBAR - 24" MINIMUM 2. NO. 5 REBAR - 30" MINIMUM
	2.	WELDED WIRE MESH TO HAVE A MINIMUM OF 8" OVERLAP (2 SQUARES OVERLAP FOR 4 x 4 MESH).
/ELDED (185) RADE 60 BARS E OF NAIL	3.	REBAR CHAIRS OR EQUIVALENT TO BE USED TO ENSURE SUFFICIENT CONCRETE COVER BETWEEN GROUND SURFACE AND REINFORCEMENT. 2 TO 3 DOBIES PER 5' x 10' SHEET OF MESH, TYPICAL.
. 4 RIZONTAL	4.	HORIZONTAL WALERS ARE CONTINUOUS
EL PLATE	5.	INSTALL CENTRALIZERS ALONG THE LENGTH OF THE SOIL NAIL AT INTERVALS NOT GREATER THAN 8' (2.5m) FROM EACH OTHER. THE CENTRALIZERS ON THE ENDS OF THE NAIL SHALL BE INSTALLED 1.5' (0.5m) FROM THE COLLAR OF THE HOLE AND





	DATE		EMBEDMENT LENGTH (ft)				DATE	EMBEDMENT	EMBEDMENT LENGTH (ft)	
NAIL ID	DRILLED	GROUTED	SOIL	ROCK		) DRILLE	ED GROUTED	SOIL	ROCK	NAIL ID
1					48					95
2					49					96
3					50					97
4					51					98
5					52					99
<u>6</u> 7					53 54					100
8					55					101 102
9					56					102
10					57					103
11					58					105
12					59					106
13					60					107
14					61					108
15					62					109
16					63					110
17					64					111
18					65					112
19					66					113
20 21					<u> </u>					<u> </u>
21					69					116
23					70					117
24					71					118
25					72					119
26					73					120
27					74					121
28					75					122
29					76					123
30					77					124
31					78					125
32					79					126
33 34					80					127 128
34					81					128
36					83					129
37					84					131
38					85					132
39					86					133
40					87					134
41					88					135
42					89					136
43					90					137
44					91					138
45					92					-
46					93					-
47			1		94					
	EET REVISIO		PROJECT NAME	:						
	DESCRIPTION	NO		UE ACTD	חו אר סו	SKITDA	II I ANE	BUILDING	<b>7</b>	
05/08/24 ISSUED F0		IFP	11	IL ASIN	ID, 2410	SKI IKA	IL LANL -	DUILDINC	J /	
			1							
┠───┼────										
			SHEET TITLE:							
			-		λι Α Τ	I CCU				6eoStabili
<b>├</b> ──			1		IVAL.	LICH	EDULE			4475 E
			1							Commerc
										Phone: 855.579
PROJECT AND THE PROPE	SOLELY FOR THE USE OF OR RETARY INFORMATION SHOW	N HEREON IS NOT TO BE	DRAWN BY:	DESIGNED BY:	CHECKED BY:	DATE:	PURSUIT NUMBER:	PROJECT NUMBER:	SHEET	WWW.g
GEOSTABILIZATION INT	R ORGANIZATION WITHOUT SP ERNATIONAL. (GSI). THE DES	IGN IS ONLY VALID IF	FHT	FHT	EL/MWL	05/08/2024	166127629	240057CO0N	C-12	vv vv .c
CONSTRUCTED AND SUPER	RVISED BY GSI OR ITS AUTHOR	RIZED SUBCONTRACTOR.				00/00/2024	10012/029	240037 COUN	0-12	

	DA	TE	EMBEDMENT LENGTH (ft)					
	DRILLED	GROUTED	SOIL	ROCK				
_								
+								
+								
+								
_								
+								
-								
+								
_								
+								
+								
-								
-								
-								
+								
				VIEWED				
+				FOR				
				CODE				
+				IPLIANCE				
+			04	/01/2025				



	D	ATE	EMBEDME	NT LENGTH (ft)			DATE	EMBEDMENT	LENGTH (ft)	
NAIL ID	DRILLED	GROUTED	SOIL	ROCK		D DRILL	ED GROUTE	D SOIL	ROCK	
139					186					
140					187					-
141					188					
142 143					189 190					-
143					190					
145					192					
146					193					
147					194					
148					195					
149					196					MUD BALAN
150 151					<u> </u>					
152					199					DATE
153					200					
154					201					
155					202					
156										-
157										]
158 159										
160					_					*APPROXIMATE NAIL ** SAMPLE SHALL BE
161										SAIVIFLE SI IALL DE
162										
163										
164										
165										
166 167					_					
167										
169										
170										
171										
172										
173										
174 175										
175										
177					_					
178					_					
179										
180										
181										
182 183					_					
184										
185										
	EET REVISIO	NS	PROJECT NAME							
DATE	DESCRIPTION	NO	-							
05/08/24 ISSUED F	OR PERMIT	IFP	T	HE ASTR	ID. 2410	SKI TRA	IIL LANE -	· BUILDINC	77	
					,	~				
			SHEET TITLE:							
			-							
					NAI	LSCH	EDULE			GeoStabiliz
			1							4475 E 7
			1		-				-	Commerce
PROJECT AND THE PROP	D SOLELY FOR THE USE OF OF RIETARY INFORMATION SHOW	N HEREON IS NOT TO BE	DRAWN BY:	DESIGNED BY:	CHECKED BY:	DATE:	PURSUIT NUMBER:	PROJECT NUMBER:	SHEET	Phone: 855.579.
GEOSTABILIZATION IN	ER ORGANIZATION WITHOUT SE ITERNATIONAL. (GSI). THE DES ERVISED BY GSI OR ITS AUTHO	IGN IS ONLY VALID IF	FHT	FHT	EL/MWL	05/08/2024	166127629	240057CO0N	C-13	www.ge
CONSTRUCTED AND SUPE	LIVISED BT GSLUK ITS AUTHO	NIZED SUBCONTRACTOR.	I 1111	1 1 1 1		00/00/2024	10012/029	24003700011	0-13	

### NCE TESTING - SPECIFIC GRAVITY (ASTM D4380)

NAIL ID*	READING - SP. GR. (1.75-1.84, TYP GSI)**

NUMBER GROUTED WITH SAMPLED BATCH. TAKEN FROM END OF GROUT HOSE.



