


FABRICATION SPECIFICATIONS 1 PAN CHANNEL LOGO FRAME SIGNCOMP RETURN DEPTH 5" PER COLOR KEY RETURN COLOR FLEXFACE **FACE MATERIAL** VINYL COLOR PER COLOR KEY **BACKS** .040 ALUMINUM ILLUMINATION WHITE LED 2 PAN CHANNEL 3/16" WHITE ACRYLIC (#2447) **FACE MATERIAL** LETTERS TRIM CAP SIZE TRIM CAP COLOR PER COLOR KEY **RETURN** .050 ALUMINUM **RETURN DEPTH** PER COLOR KEY **RETURN COLOR BACKS** 3MM ACM **ILLUMINATION** WHITE LED 3 PAN CHANNEL 3/16" WHITE ACRYLIC (#2447) **FACE MATERIAL** TRIM CAP SIZE TAGLINE TRIM CAP COLOR PER COLOR KEY **RETURN** .050 ALUMINUM **RETURN DEPTH RETURN COLOR** PER COLOR KEY **BACKS** 3MM ACM **ILLUMINATION** WHITE LED

GENERAL NOTES

COLOR KEY PAINT | PMS 288c BLUE VINYL WHITE BLOCKOUT VINYL TO MATCH 3M 3630-8538 BLUE

SHIPPING LIST MATERIAL QTY. TOUCH-UP PAINT **INSTALL PATTERN** T-CAN/DISCONNECT SWITCH/SAFETY PLATE GE 24V 100W POWER SUPPLY ELECTRICAL PASS-THRU 1/2" FLEX CONDUIT 1/2" FLEX CONNECTORS

ELECTRICAL REQUIREMENTS					
VOLTS	120	AMP	CIRCUIT	1	



INSTALL

- A. Non-Corrosive Securement Using **Appropriate Mounting Hardware Painted** to Match Background.
- B. Disconnect Switch at Transformer Can.
- C. 1/4"Ø Drain Holes Required in Letters Returns & Retainers w/ Baffles as required.
- D. 1/2" (MFG) Plastic Pass-Through.
- E. 20 amp 120 V. Circuits Required (Brought to within 6' of sign BY OTHERS).
- F. 6'-0" x 1/2" Flexible Conduit for External Switch.
- G. Grounded/Bonded Wire Connection from Letter to T-Can.

APPROVED FASTENER SCHEDULE				
-	3/8" - 1/2" LAG SCREW	FOR USE WITH WOOD OR EIFS WALL SYSTEMS. 1 1/2" MIN PENETRATION (EXCLUDING TIP)		
	1/4" - 3/8" THREADED ROD	FOR USE WITH WOOD, CONCRETE BLOCK OR EIFS WALL SYSTEMS		
	3/8" RED HEAD L.D.T. (LARGE DIAMETER TAPCON)	FOR USE WITH CONRETE BLOCK, BRICK OR CONCRETE. EMBED A MIN. OF 2 1/2".		
	3/8" DIA. HILTI HIT ROD WITH HY150 MAX ADHESIVE	FOR USE WITH CONRETE. EMBED A MIN. OF 2"		
4	3/8" DIA. HILTI HIT ROD WITH HY20 ADHESIVE	FOR USE WITH MASONRY AND BRICK. EMBED A MIN. OF 3 3/8"		
	3/8" DIA. HILTI HIT ROD WITH HY20 ADHESIVE	FOR USE WITH CONCRETE BLOCK. EMBED A MIN. OF 2"		
el == :	3/8" DIA. HILTI HCL SLEEVE ANCHOR	FOR USE WITH CONCRETE, MASONRY AND BRICK. EMBED A MIN. OF 3 3/8".		
dinama.	3/8" DIA. LAG WITH 3/8" SHIELD & WASHER	FOR USE WITH CONCRETE, MASONRY AND BRICK - EMBED A MIN. OF 2"		
	#10 (3") HEX SCREW W/ FENDER WASHER INTO PLASTIC WALL ANCHOR	USE WITH CONCRETE, MASONRY & BRICK. FOR USE WITH SMALL/LIGHTWEIGHT LETTERS & CABINETS		

It is the intent and purpose of this color rendering to provide a basic color representation of your sign finish and color. Existing painted surfaces will have a perceptible difference in shade and printed solors will vary from actual paint finish and color. Existing painted surfaces will have a perceptible difference in shade and printed solors will vary from actual paint finish and color. Existing painted surfaces will have a perceptible difference in shade and printed solors.

'CUSTOM' DESCRIPTION



imagenational.com

UN DERWRITERS NAMPA PLANT - UL #433195.00 UL #433195-001

U.S. & P.R. - All signs conform to UL-48/2161 labeled accordingly) & must comply with UL-41.1 install procedures. Canada - all signs must be CAS compliant. This sign(s) is intended to be installed in accordance with requirements of article 600 of the National Electrical Code and/or applicable local codes. This includes proper grounding and bonding **Client: HOLIDAY INN EXPRESS**

OPAQUE LOGO CABINET

Site: # SBSSS 3350 S. LINCOLN AVE. STEAMBOAT SPRINGS, CO 80487

File: HIE-SBSSS-STEAMBOAT SPRINGS CO-BuildingSignage-060325 Date: 06/03/25 Reviewed by: Designer: Sb Account Manager: WG | Engineer:

Haliday Inn Express

DETAILS

Page No.