GENERAL PROJECT DATA

PROJECT DESCRIPTION:

RENOVATION OF EXISTING RESTAURANT SPACE AND KITCHEN SPACE.

ZONING DISTRICT:

G-2

APPLICABLE CODES:

ADAAG 2010

2018 IBC 2018 IEBC 2018 IECC 2018 IMC 2018 IPC 2018 IFGC NEC 2020 CITY OF STEAMBOAT CDC ICC/ANSI A117.1 (2003)

SHEET INDEX

ARCHITECTURAL

| AG001 | PROJECT COVER SHEET |
|-------|--------------------------|
| AG002 | CODE REVIEW |
| AD111 | FLOOR PLANS - DEMOLITION |
| A111 | FLOOR PLANS - PROPOSED |
| A191 | REFLECTED CEILING PLANS |
| | |
| | |

MECHANICAL

| M000 | HVAC COVER SHEET |
|------|------------------|
| M111 | HVAC PLANS |
| M300 | HVAC SCHEDULES |
| M400 | HVAC DETAILS |
| M401 | HVAC DETAILS |
| M402 | HVAC DETAILS |
| M403 | HVAC DETAILS |
| M404 | HVAC DETAILS |
| M405 | HVAC DETAILS |
| | |

PROJECT TEAM

OWNER:

STEAMBOAT SKI & RESORT CORPORATION 2305 MT. WERNER CIRCLE STEAMBOAT SPRINGS, CO 80487 PH: (970) 879-5381 JIM SCHNEIDER JSCHNEIDER@STEAMBOAT.COM

ARCHITECT:

ERIC SMITH ASSOCIATES, P.C. 1919 7th STREET BOULDER, CO 80302 (303) 442-5458 KATE LEGGETT KATE@ESAPC.COM

MECH ENGINEER:

THE BALLARD GROUP, INC. 2525 S. WADSWORTH BLVD., STE 200 LAKEWOOD, CO 80227 (303) 988-4514 ERIC BAALMAN EBAALMAN@THEBALLARDGROUP.COM

BID/PERMIT SET

FOR

STEAMBOAT SKI & RESORT CORPORATION

LAST TRACKS AT **TORIAN PLUM BUILDING C**

AT: 1847 SKI TIME SQUARE DR #C2C

LEGAL DESCRIPTION:


UNIT C-2C BLDG C TORIAN PLUM CONDO AMENDED


COUNTY OF ROUTT, STATE OF COLORADO

GENERAL NOTES

- . DO NOT SCALE DRAWINGS. VERIFY ALL DIMENSION AND CONDITIONS IN FIELD. DISCREPANCIES IN DIMENSIONS, EXISTING CONDITIONS AND FIELD MEASUREMENTS ARE TO BE BROUGHT TO THE ATTENTION OF THE ARCHITECT PRIOR TO THE COMMENCEMENT OF THE WORK.
- 2. DIMENSIONS ARE FROM FINISHED FACE TO FINISHED FACE OF WALL UNLESS NOTED OTHERWISE
- 3. THE GENERAL CONTRACTOR SHALL ENSURE THAT ALL CONSTRUCTION MEETS OR EXCEEDS APPLICABLE CODES AND STANDARD PRACTICES, INCLUDING ALL FEDERAL STATE AND LOCAL BUILDING REQUIREMENTS.
- 4. CONTRACTOR TO VERIFY TEMPERED GLAZING PROVIDED AT NEW DOORS AND WINDOWS PER CODE.
- 5. CONTRACTOR TO VERIFY MANUFACTURES INSTRUCTIONS AND PROCEDURES FOR INSTALLATION OF ALL MATERIALS & EQUIPMENT.
- 6. ALL WORK CONNECTED WITH THIS PROJECT BY ANY TRADE INVOLVED SHALL BE DONE IN A WORKMANSHIP TYPE MANNER IN ACCORDANCE WITH THE BEST PRACTICE OF THE TRADE.
- CONTRACTOR SHALL PROVIDE JOB SITE CLEAN UP. SORT AND RECYCLE JOBSITE DEBRIS TO THE FULLEST EXTENT POSSIBLE INCLUDING CARDBOARD, STEEL, WOOD, ACOUSTICAL TILE, GLASS AND GYPSUM BD. CLEAN AND REMOVE CONSTRUCTION DEBRIS FROM THE SITE ON A DAILY BASIS. UPON JOB COMPLETION, LEAVE THE SITE IN A NEAT AND ORDERLY CONDITION. PROVIDE TRASH REMOVAL FOR PROJECT RELATED WORK BY SUBCONTRACTORS, ETC.
- ALL PERMITS (OCCUPANCY, ELECTRICAL, PLUMBING AND ALL OTHERS) REQUIRED BY STATE AND LOCAL CODES, EXCEPT THOSE ACQUIRED BY SUBCONTRACTORS, ARE TO BE SECURED BY THE GENERAL CONTRACTOR WITH COPIES TO OWNER WITHOUT EXTRA CHARGE. ALL PERMITS ACQUIRED BY SUBCONTRACTORS SHALL BE SUBMITTED TO THE GENERAL CONTRACTOR FOR RECORD.
- 9. EACH TRADE SHALL VERIFY ALL REQUIREMENTS PERTAINING TO WORK PERFORMED IN THE PROJECT AND ANY REQUIRED PERMITS. ALL SUBCONTRACTORS SHALL DIRECT QUESTIONS, CHANGES OR REQUESTS THROUGH THE GENERAL CONTRACTOR. THE GENERAL CONTRACTOR SHALL SUBMIT ALL REQUESTS, CHANGES OR QUESTIONS TO THE ARCHITECT IN WRITING.
- 10. NO UTILITY OR DATA SERVICES MAY BE DISCONNECTED WITHOUT FIRST CONTACTING THE FACILITY MANAGER IN ADVANCE FOR AUTHORIZATION.
- 11. ALL EGRESS PATHS SHALL REMAIN OPEN AND AVAILABLE TO OWNER AND GUESTS. 12. IF UNANTICIPATED MECHANICAL, PLUMBING, ELECTRICAL, STRUCTURAL ELEMENTS OR
- ANY OTHER CONDITIONS ARE ENCOUNTERED WHICH MIGHT CONFLICT WITH THE INTENDED FUNCTION OF THE RENOVATION CONTACT THE ARCHITECT IMMEDIATELY FOR CLARIFICATION. COORDINATE ACTIVITIES WITH THE FACILITY MANAGER IN ADVANCE OF DOING WORK.
- 13. COORDINATE WORK OF DISCIPLINES, (ARCH., STRUCT., ELECT., MECH., PIPING, ETC.) WITH EXISTING CONDITIONS, SPECIAL REQUIREMENTS AND CONSTRUCTION SCHEDULE.
- 14. PROVIDE, ERECT AND MAINTAIN TEMPORARY WORK AS MAY BE REQUIRED FOR PROTECTION OF THOSE IN OR ABOUT THE BUILDING.
- 15. PROVIDE BARRICADES, PLASTIC COVERS, DUST BARRIERS, WARNING SIGNS, FIRE EXTINGUISHERS AND OTHER NECESSARY EQUIPMENT FOR THE PROTECTION AND SAFETY OF PERSONNEL, MATERIALS AND EQUIPMENT IN THE AREA.
- 16. EACH CONTRACTOR SHALL INCLUDE COST OF MATERIAL AND LABOR NECESSARY TO PROVIDE ALL REQUIRED SUPPORTS, BEAMS, ANGLES, HANGERS, RODS, BASES, BRACES, CHANNELS, ETC. TO PROPERLY SUPPORT HIS CONTRACT WORK.
- 17. PROVIDE ADEQUATE SUPPORTING BLOCKING AT ALL OF THE FOLLOWING LOCATIONS BUT NOT LIMITED TO: T.V. MOUNTING LOCATIONS, HOOKS, MIRRORS, CASEWORK, FAUCETS, SHELVES, TOILET PARTITIONS, ETC.

VICINITY MAP





202


<u>о</u>

BMI

ЧIТ

Ē

3ID/P



THE COMMERCIAL KITCHEN APPLIANCES WILL REQUIRE TYPE 1 HOOD, WHICH SHALL BE "ZERO CLEARANCE" UL RATED TO PASS THROUGH THE UPPER FLOOR AND ROOF STRUCTURE OF THE BUILDING AND WILL COMPLY WITH 2018 IMC. THE HOOD WILL INCLUDE A FIRE

4678 SF 682 SF 444 SF 2345 SF 237 SF 8386 SF 1084 SF 1984 SF 3068 SF 11,454 SF

 Σ

3ID

AGU

SED ARCH NOTICE: DUTY OF COOPERATION Release of these plans contemplates further cooperation among the owner, his contractor and the architect. Design and construction are complex. Although the architect and his consultants have performed their services with due care and diligence, they cannot guarantee perfection. Communication is imperfect and every contingency cannot be anticipated. Any ambiguity or discrepancy discovered by the use of these plans shall be reported immediately to the architect. Failure to notify the architect compounds misunderstanding and increases construction costs. A failure to cooperate by a simple notice to the architect shall relieve the architect from responsibility for the consequences. Changes made from the plans without consent of the architect are unauthorized and shall relieve the architect of responsibility for all consequences arriving out of such changes. All design, documents and data prepared by Eric Smith Associates, P.C. as instruments of service shall remain property of Eric Smith Associates, P.C. and shall not be copied, changed or disclosed in any form whatsoever without first obtaining the express written consent of Eric Smith Associates, P.C. Eric Smith Associates, P.C REVISIONS Description Date \bigcirc $\bigcirc \cap$ C N ЧС \frown $\Box O$ m S $\boldsymbol{\wedge}$ (5 1 SQU **D B** TIME (AT SP ΔO **AB** SRC S \sim 84 E⊿ **⊣** , S S 202 21027 Ū Job Number: 5/14/21 Date: Author **Drawn By:** Checked By: Checker Project Phase m BID/PERMIT SUBMITTAL S Sheet Title CODE REVIEW Sheet Number

OF COL


ERID P.


SMITH


MAY 17 2021 B-11





- A REMOVE EXISTING WALL. PATCH ADJACENT WALLS AND FLOORS FOR NEW FINISHES.
- B REMOVE EXISTING DOOR AND HARDWARE
- C REMOVE EXISTING WINDOW.
- D REMOVE EXISTING PARTIAL HEIGHT WALL, CASEWORK, COUNTERTOP AND/OR EQUIPMENT COMPLETE.
- E EXISTING WINDOW TO REMAIN
- F EXISTING DOOR TO REMAIN
- G EXISTING WALL TO REMAIN
- H REMOVE PORTION OF EXISTING WALL FOR NEW OPENING. SALVAGE EXISTING STONE VENEER FOR RE-INSTALLATION ON THIS WALL.
- I REMOVE EXISTING CEILING AND LIGHTING
- REMOVE EXISTING FLOOR FINISH AND BASE. PREP FOR J NEW FINISHES. (HATCHED REGION)
- K ADJUST EXISTING POWER, LIGHTING, HVAC, AND FIRE ALARM SYSTEM TO ACCOMMODATE NEW SPACE LAYOUT.
- L EXISTING STRUCTURE TO REMAIN. WHEREVER EXISTING STRUCTURE IS FOUND IN EXISTING WALLS BEING REMOVED, STRUCTURE IS TO REMAIN.
- TO REMAIN.
- DUCT. COORDINATE FINAL LOCATION WITH HOOD MANUFACTURER AND FLOOR JOIST LAYOUT. PATCH
















<<u>11</u>>











FSD

| | | <u>мес</u> | CHANICAL HVAC INSULATION NOTES AND SPECIFICATIONS |
|--|--|------------|--|
| HVAC | LEGEND | 1. | ALL CONCEALED ROUND AND RECTANGULAR DUCTWORK SHALL BE WRAPPED WITH 1-½" DUCT WRAP WITH VAPOR BARRIER JACKET, MINIMUM R-6. |
| - | | 2. | FLEXIBLE DUCTWORK SHALL BE WRAPPED WITH FIBERGLASS INSULATION WITH VAPOR BARRIER JACKET, MINIMUM R-6. |
| SYMBOL | DESCRIPTION | 3. | EXTERIOR RECTANGULAR MAKE-UP AIR SUPPLY DUCTWORK SHALL BE WRAPPED WITH 3" RIGID INSULATION WITH VAPOR BARRIER JACKET, MINIMUM R-13 WITH ALUMINIMUM JACKETING. |
| | MAKE-UP AIR UNIT | 4. | REFRIGERANT SUCTION PIPING SHALL BE INSULATED WITH MINIMUM 1/2" THICK CLOSED CELL INSULATION, OR AS RECOMMENDED BY EQUIPMENT MANUFACTURER. NOTE THAT BOTH REFRIGERANT |
| | SUPPLY FAN | | LIQUID AND SUCTION LINES SHALL BE INSULATED FOR VRF AND DUCTLESS SPLIT SYSTEMS. |
| | EXHAUST FAN | MEC | CHANICAL HVAC NOTES AND SPECIFICATIONS |
| | UNIT HEATER | 1. | DUCTWORK DIMENSIONS LISTED ON THE DRAWINGS ARE CLEAR, INSIDE DIMENSIONS. WHEN DUCT LINER IS REQUIRED, INCREASE SHEET METAL DIMENSIONS ACCORDINGLY. |
| | CABINET UNIT HEATER | 2. | FLEXIBLE DUCTWORK SHALL BE THE SAME SIZE AS THE NECK OF THE AIR DEVICE. FLEXIBLE DUCTWORK SHALL NOT EXCEED 8'-0" IN LENGTH. PROVIDE RIGID ROUND DUCTWORK FOR TAKEOFFS IN EXCESS OF |
| | BASEBOARD RADIATION | 3. | 8'-0". UNLESS INDICATED OTHERWISE, BRANCH TAKEOFFS ARE TO BE THE SAME SIZE AS THE DIFFUSER NECK |
| | SUPPLY REGISTER | | SIZE INDICATED. |
| | SUPPLY GRILLE | 4. 5. | PROVIDE DUCT TRANSITIONS FROM EQUIPMENT CONNECTIONS TO DUCT SIZES INDICATED AS REQUIRED. PROVIDE A FLEXIBLE CONNECTION TO THE INTAKE AND DISCHARGE OF ALL MECHANICAL EQUIPMENT |
| | RETURN GRILLE | 6. | HAVING ROTATING PARTS. FLEXIBLE CONNECTION SHALL COMPLY WITH ALL APPLICABLE CODES. ALL DUCTWORK SHALL BE A MINIMUM 26 GAUGE SHEETMETAL, OR AS REQUIRED BY ALL APPLICABLE |
| | EXHAUST REGISTER | | CODES. ALL DUCTWORK CROSSING RATED CORRIDORS SHALL BE A MINIMUM 24 GAUGE SHEETMETAL. DUCT GAUGES SHALL MEET OR EXCEED SMACNA STANDARDS. |
| | EXHAUST GRILLE | 7. | ALL SUPPLY DUCTWORK SHALL BE SEALED AIRTIGHT WITH DUCT SEALANT (SMACNA SEAL CLASS "A") ALONG ALL SEAMS AND JOINTS. |
| | TRANSFER GRILLE | 8. | ALL UNLINED DUCTWORK THAT IS VISIBLE THROUGH THE AIR DEVICE SHALL BE PAINTED FLAT BLACK. |
| | SUPPLY AIR RETURN AIR | 9. | MAINTAIN A MINIMUM 10'-0" SEPARATION FROM OUTSIDE AIR INTAKES TO EXHAUST TERMINATIONS AND FLUE OUTLETS. |
| | EXHAUST AIR | 10. 11. | MAINTAIN A MINIMUM OF 15'-0" FROM OUTSIDE AIR INTAKES TO PLUMBING VENTS. MAINTAIN A MINIMUM 3'-0" SEPARATION FROM EXHAUST TERMINATIONS TO OPERABLE WINDOWS AND |
| | OUTSIDE AIR | | DOORS. |
| | TRANSFER AIR | 12. | ALL MOTORIZED ROOF MOUNTED EQUIPMENT SHALL BE LOCATED AT LEAST 10'-0" FROM THE EDGE OF THE ROOF OR PROVIDED WITH A MEANS FOR EQUIPMENT TIE-OFFS. |
| | MAKE-UP AIR | 13. | ALL ELBOWS, BOTH HORIZONTAL AND VERTICAL, SHALL BE LONG RADIUS ELBOWS WHEREVER POSSIBLE, OR SHALL HAVE TURNING VANES WHERE SHOWN. |
| | MANUAL VOLUME DAMPER | 14. | BRANCH FITTINGS SERVING GRILLES AND DIFFUSERS SHALL BE CONICAL (OR 45° TAKEOFFS AS SHOWN ON DRAWINGS). PROVIDE WITH MANUAL VOLUME DAMPERS UNLESS THE AIR TERMINAL IS PROVIDED WITH AN OBD. |
| ۲ | FIRE DAMPER | 15. | ALL JOB SITE DUCTWORK PRIOR TO INSTALLATION SHALL BE COVERED AND PROTECTED FROM DIRT, DUST, AND DAMAGE PER SMACNA STANDARDS. OPENINGS IN INSTALLED DUCTWORK DURING |
| | COMBINATION MOTORIZED FIRE/SMOKE DAMPER | | CONSTRUCTION SHALL BE SEALED CLOSED WITH PLASTIC TO PREVENT DUST AND DEBRIS INTRUSION INTO DUCTWORK SYSTEMS. |
| \$ | WALL SWITCH | 16. | COMPLETELY FILL ALL ROOFTOP UNIT ROOF CURBS WITH UNFACED BATT INSULATION. LAYER INSULATION IN A NEAT WORKMANSHIP LIKE MANNER. |
| Ū | THERMOSTAT | 17. | COORDINATE LOUVER, WALL CAP, AND AIR DEVICE PLACEMENT WITH BRICK OR BLOCK COURSING WHERE APPLICABLE. |
| VFD | VARIABLE FREQUENCY DRIVE | 18. | COORDINATE THE LOCATION AND ELEVATION OF ALL EXPOSED DUCTWORK WITH THE ARCHITECT AT THE JOB SITE PRIOR TO INSTALLATION. |
| | SUPPLY DUCT UP & DOWN | 19. | KITCHEN GREASE EXHAUST DUCTWORK SHALL BE PRE-MANUFACTURERED BY CAPTIVEAIRE FOR SPECIFIED USE WITH TYPE I KITCHEN HOODS. PROVIDE DOUBLE WALL FACTORY BUILT GREASE |
| | RETURN/EXHAUST DUCT UP & DOWN | | DUCTWORK CONFORMING TO NFPA-96 AND MAINTAIN ALL REQUIRED CLERANCES TO COMBUSTIBLES. MC TO VERIFY ALL DUCTWORK SIZES AND FITTINGS WITH VENDOR PRIOR TO ORDER. |
| | ROUND SUPPLY DUCT UP & DOWN | | |
| | DUCT ELBOW WITH TURNING VANES | | |
| | SQUARE TO ROUND TRANSITION | | |
| | OFFSET DUCT UP / DOWN IN DIRECTION OF ARROW | | |
| | CONICAL SPIN-IN FITTING WITH MANUAL VOLUME DAMPER | | |
| | CONICAL SPIN-IN FITTING WITHOUT MANUAL VOLUME DAMPER | | |
| | 45° TAKEOFF | | |
| | STANDARD RADIUS ELBOW | | |
| + 10x8 + | NEW RECTANGULAR DUCTWORK - WIDTH x DEPTH | | |
| δ 10"ø | NEW ROUND DUCTWORK - DIAMETER | | |
| δ <u>10x8ø</u> δ | NEW OVAL DUCTWORK - WIDTH / DEPTH | | |
| (E)10x8 | EXISTING DUCTWORK TO REMAIN | | |
| | EXISTING DUCTWORK TO BE REMOVED | | |
| | CEILING DIFFUSER (FOUR WAY THROW PATTERN) | | |
| | RETURN OR EXHAUST REGISTER OR GRILLE | | |
| | RETURN GRILLE WITH SOUND BOOT | | |
| XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX | FLEXIBLE DUCTWORK | | |
| ▲ _∕\ | AIRFLOW - RETURN/EXHAUST | | |
| | AIRFLOW - SUPPLY | | |

SHEET INDEX

| SHEET NUMBER | MECHANICAL, PLUMBING & FIRE PROTECTION SHEET TITLE | SHEET SCALE |
|-----------------|---|----------------|
| | | |
| M000 | HVAC COVER SHEET | NONE |
| M111 | HVAC PLANS | 1/8" = 1'-0" |
| M300 | HVAC SCHEDULES | NONE |
| M400 | HVAC DETAILS | NONE |
| M401 | HVAC DETAILS | NONE |
| M402 | HVAC DETAILS | NONE |
| M403 | HVAC DETAILS | NONE |
| M404 | HVAC DETAILS | NONE |
| M405 | HVAC DETAILS | NONE |

MECHANICAL DEMOLITION GENERAL NOTES AND SPECIFICATIONS

- THE MECHANICAL CONTRACTOR SHALL INSPECT SITE TO BECOME FAMILIAR WITH THE SCOPE OF THE WORK. THESE DOCUMENTS DO NOT REFLECT AS-BUILT CONDITIONS. ANY DISCREPANCIES BETWEEN THESE DOCUMENTS AND THE ACTUAL CONDITIONS SHALL BE REPORTED TO THE ARCHITECT/ENGINEER FOR RESOLUTION PRIOR TO BID PRICING. NO EXTRAS WILL BE ALLOWED DUE TO LACK OF KNOWLEDGE OF THE EXISTING CONDITIONS.
- THE MECHANICAL CONTRACTOR SHALL COORDINATE THE LOCATION OF ALL ABOVE CEILING EQUIPMENT, DUCTWORK, AND CEILING MOUNTED AIR DEVICES WITH EXISTING ARCHITECTURAL, STRUCTURAL, ELECTRICAL, AND MECHANICAL CONDITIONS. APPROXIMATE LOCATIONS OF NEW WORK ARE SHOWN AND SHOULD BE FOLLOWED AS CLOSELY AS EXISTING CONDITIONS WILL ALLOW.
- COORDINATE DEMOLITION REQUIREMENTS WITH THE GENERAL CONTRACTOR.
- COORDINATE EXTENT OF DEMOLITION WITH THE NEW CONSTRUCTION AS SHOWN IN THESE 4 DOCUMENTS.
- EXISTING MECHANICAL WORK IS SHOWN LIGHT. 5.
- ALL MECHANICAL ITEMS INDICATED TO BE DEMOLISHED SHALL BE INSPECTED FOR SALVAGE BY THE 6. OWNER. ALL NON-SALVAGEABLE ITEMS SHALL THEN BE IMMEDIATELY REMOVED FROM THE SITE BY THE MECHANICAL CONTRACTOR.
- ALL UNUSED TEMPERATURE CONTROL WIRING, WIRE MOLD, PNEUMATIC TUBING AND CONTROL 7. COMPONENTS SHALL BE REMOVED.
- ALL UNUSED HANGERS AND SUPPORTS SHALL BE REMOVED. 8
- THE REMOVAL OR INSTALLATION OF CONTROLS, PIPES, DUCTS, AND EQUIPMENT MAY REQUIRE THE REMOVAL OF EXISTING WALLS AND CEILINGS. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR REPAIRING AND PAINTING THESE WALLS AND/OR CEILINGS SO THEY MATCH THE EXISTING WHERE NOT REPLACED UNDER THE ARCHITECTURAL DOCUMENTS. THE GENERAL CONTRACTOR SHALL REVIEW THE MECHANICAL DRAWINGS TO IDENTIFY THESE LOCATIONS PRIOR TO BID PRICING.
- THE GENERAL CONTRACTOR SHALL PATCH AND PAINT WALLS TO MATCH EXISTING AT THE DEMOLISHED 10. CONTROLS.
- THE GENERAL CONTRACTOR SHALL PATCH AND SEAL UNUSED ROOF PENETRATIONS AT DEMOLISHED 11. MECHANICAL TO MATCH EXISTING CONDITIONS.
- THE GENERAL CONTRACTOR SHALL PATCH THE CEILING, ROOF, AND WALLS TO MATCH EXISTING AT 12. DEMOLISHED HANGERS AND SUPPORTS.
- THE GENERAL CONTRACTOR SHALL MAKE REPAIRS TO ALL EXISTING BUILDING COMPONENTS THAT HAVE 13. BEEN AFFECTED BY THE DEMOLITION OF MECHANICAL SYSTEMS.
- PORTIONS OF THIS BUILDING WILL BE OCCUPIED DURING THIS CONSTRUCTION PROJECT. THE MECHANICAL CONTRACTOR SHALL COORDINATE THE SCHEDULING OF THEIR WORK WITH THE GENERAL 14 CONTRACTOR. CLEAN UP AT THE END OF EACH DAY.

MECHANICAL GENERAL NOTES AND SPECIFICATIONS

- THESE DOCUMENTS ARE DIAGRAMMATIC IN NATURE AND ARE NOT INTENDED TO BE UTILIZED AS SHOP DRAWINGS NOR NECESSARILY SCALED FOR EXACT MEASUREMENTS. ANY DISCREPANCIES BETWEEN THESE DOCUMENTS AND THE ACTUAL CONDITIONS SHALL BE REPORTED TO THE ARCHITECT/ENGINEER FOR RESOLUTION PRIOR TO INSTALLATION.
- MECHANICAL WORK SHALL COMPLY WITH ALL APPLICABLE CODES. VERIFY ALL REQUIREMENTS PRIOR 2 TO SUBMITTING BID OR COMMENCING WORK. MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ANY ADDITIONAL COORDINATION OR 3.
- MODIFICATIONS THAT MAY BE REQUIRED DUE TO THE USE OR INSTALLATION OF EQUIPMENT OTHER THAN THAT OF THE BASIS OF DESIGN MANUFACTURERS LISTED ON THE DRAV
- THE MECHANICAL CONTRACTOR SHALL COORDINATE WORK WITH OTHER TRADES PRIOR TO AND DURING CONSTRUCTION. THE MECHANICAL SYSTEMS SHOWN SHALL BE RUN AS HIGH AS POSSIBLE UNLESS NOTED OTHERWISE.
- REFER TO THE ARCHITECTURAL REFLECTED CEILING PLANS FOR EXACT LOCATION OF ALL CEILING AIR DEVICES AND ACCESS PANELS. OBTAIN CLARIFICATION FROM THE ARCHITECT, IF EXACT LOCATIONS ARE NOT SHOWN.
- REFER TO THE ARCHITECTURAL DRAWINGS FOR ROOFING DETAILS SPECIFIC TO THIS PROJECT. 6.
- THE MECHANICAL CONTRACTOR SHALL COORDINATE THERMOSTAT, SENSOR, AND SWITCH LOCATIONS WITH OWNER PRIOR TO INSTALLATION. ALL THERMOSTATS, SENSORS, AND SWITCHES SHALL BE LOCATED 48" AFF UNLESS INDICATED OTHERWISE. WHERE EXISTING CONDITIONS REQUIRE EXPOSED CONTROL WIRING, SUCH WIRING SHALL BE CONCEALED WITH WIRE MOLD. WIRE MOLD COLOR SHALL BE SELECTED BY THE ARCHITECT.
- PROVIDE EQUIPMENT LABELS FOR ALL MAJOR EQUIPMENT, INCLUDING BUT NOT LIMITED TO AIR 8. HANDLING SYSTEMS, FANS, CONTROLS, AND DAMPERS. LABELS SHALL BE AFFIXED OR ADHERED DIRECTLY TO EQUIPMENT. EQUIPMENT TO BE LABELED WITH ENGRAVED PLASTIC LAMINATE SIGNS.
- BALANCE AIR SYSTEMS TO THE QUANTITIES SHOWN AND SUBMIT BALANCE REPORT TO THE ARCHITECT/ENGINEER FOR REVIEW. FAN SYSTEMS TO BE BALANCED WITHIN PLUS 10 PERCENT OR MINUS 5 PERCENT OF LISTED VALUES. AIR INLETS AND OUTLETS TO BE BALANCED WITH PLUS 10 PERCENT TO MINUS 5 PERCENT OF LISTED VALUES.
- SUBMIT TO THE ARCHITECT/ENGINEER ELECTRONIC PDF FILES OF MECHANICAL SUBMITTALS FOR 10. REVIEW OF ALL MAJOR EQUIPMENT AS LISTED ON DRAWING EQUIPMENT SCHEDULES, AS WELL AS DUCTWORK ACCESSORIES AND CONTROLS. ENGINEER ASSUMES NO RESPONSIBILITY FOR EQUIPMENT OR INSTALLATION COORDINATION THAT HAS NOT BEEN SUBMITTED FOR REVIEW.
- CONTRACTOR SHALL WARRANTY WORK, EQUIPMENT, MATERIALS, AND PROPER OPERATION FOR A 11. PERIOD OF ONE YEAR FROM THE DATE OF ACCEPTANCE OF BUILDING BY OWNER. THIS GUARANTEE SHALL NOT INCLUDE NORMAL MAINTENANCE REQUIRED BY THE OWNER AS DESCRIBED IN 0&M MANUALS.
- PROVIDE TWO SETS OF OPERATION AND MAINTENANCE (O&M) MANUALS FOR OWNER AT COMPLETION 12. OF PROJECT TO THE ARCHITECT/ENGINEER FOR REVIEW. DOCUMENTATION SHALL CONSIST OF MANUFACTURER'S INFORMATION, SPECIFICATIONS AND RECOMMENDATIONS, PROGRAMMING PROCEDURES AND DATA POINTS, NARRATIVES, AND OTHER MEANS OF ILLUSTRATING TO THE OWNER HOW THE BUILDING, EQUIPMENT, AND SYSTEMS ARE INTENDED TO BE INSTALLED, MAINTAINED, AND OPERATED. REQUIRED REGULAR MAINTENANCE ACTIONS FOR EQUIPMENT AND SYSTEMS SHALL BE CLEARLY STATED ON A READILY VISIBLE LABEL. THE LABEL SHALL INCLUDE THE TITLE OR PUBLICATION NUMBER FOR THE OPERATION AND MAINTENANCE MANUAL FOR THAT PERTICULAR MODEL AND TYPE OF PRODUCT.
- CONTRACTOR SHALL MAINTAIN A COMPLETE AND ACCURATE SET OF RECORD DRAWINGS SHOWING 13. ACTUAL INSTALLED LOCATIONS OF WORK. SUBMIT THESE DRAWINGS AS PART OF THE OPERATION AND MAINTENANCE MANUALS AT COMPLETION OF PROJECT.
- ACCESS DOORS SHALL BE INSTALLED IN ORDER TO PROVIDE ACCESS TO MECHANICAL SYSTEMS 14. REQUIRING ACCESS FOR SERVICING OR ADJUSTMENT LOCATED ABOVE INACCESSIBLE CEILINGS, WHETHER OR NOT SHOWN ON THE DRAWINGS. ACCESS DOORS SHALL BE FURNISHED BY THE MECHANICAL CONTRACTOR AND INSTALLED BY THE GENERAL CONTRACTOR. ACCESS DOOR LOCATIONS SHALL BE APPROVED BY THE ARCHITECT PRIOR TO INSTALLATION. PROVIDE 12"x12" ACCESS DOORS FOR HAND ACCESS (VALVES AND DAMPERS) AND 24"x24" ACCESS FOR HEAD AND SHOULDER ACCESS FOR OTHER EQUIPMENT.

NOTICE: DUTY OF COOPERATION Release of these plans contemplates further cooperation among the owner, his contractor and the architect. Design and construction are complex. Although the architect and his consultants have performed their services with due care and diligence. they cannot guarantee perfection. Communication is imperfect and every contingency cannot be anticipated. Any ambiguity or discrepancy discovered by the use of these plans shall be reported immediately to the architect. Failure to notify the architect compounds misunderstanding and increases construction costs. A failure to cooperate by a simple notice to the architect shall relieve the architect from responsibility for the consequences. Changes made from the plans without consent of the architect are unauthorized and shall relieve the architect of responsibility for all consequences arriving out of such changes. All design, documents and data prepared by Eric Smith Associates, P.C. as instruments of service shall remain property of Eric Smith Associates, P.C. and shall not be copied, changed or disclosed in any form whatsoever without first obtaining the express written consent of Eric Smith Associates, P.C. Eric Smith Associates, P.C. REVISIONS No. Description Date \bigcirc \cap $O \cap$ C \mathcal{O} \cap $\Box O$ m S SQL Ω S Ē ΣÕ Ш S \bigcirc M 4 ωЩ S S S **Job Number:** 20013.00 5/17/21 Date: EAB **Drawn By:** Checked By: EAB Project Phase BID/PERMIT SUBMITTAL Sheet Title HVAC COVER SHEET Sheet Number

 \sim

 $\overline{\mathbf{O}}$

 \sim


Ы С


 \mathbf{m}


S

Ш

 \cap








| PLAN | | | GRILLES, REGISTERS & DIFFUSERS SCHEDULE | | | | | | | | | | | | | |
|--------|---------------------------------|---------|---|------------|--------|----------|----------|--------|---------|--|--|--|--|--|--|--|
| | MANUFACTURER | TYPE & | NECK | FACE | VOLUME | | MOUNTING | | REMARKS | | | | | | | |
| CODE | & MODEL NO. | SERVICE | SIZE | SIZE | DAMPER | MATERIAL | TYPE | FINISH | | | | | | | | |
| | | | | | (OBD) | | | | | | | | | | | |
| CD-1 | PRICE PDDR | SUPPLY | AS NOTED | 24"x24" | NO | STEEL | LAY-IN | WHITE | NOTE: 1 | | | | | | | |
| SG-1 | PRICE 520 | SUPPLY | AS NOTED | NECK+1.75" | NO | STEEL | SURFACE | WHITE | NOTE: 2 | | | | | | | |
| | | | | | | | | | | | | | | | | |
| NOTES: | IFACTURER TO PROVIDE SUPPLY PLE | | | | | I I | | I | | | | | | | | |

| | ELECTRIC CEILING HEATER SCHEDULE | | | | | | | | | | | | | | |
|--------|-------------------------------------|----------------------|------------|------------|--------|--------|-----|------|-----|-------|---|-------|---------|-----------|--|
| PLAN | PLAN MANUF. CAP. ELEMENT ELECTRICAL | | | | | WEIGHT | | | | | | | | | |
| CODE | & MODEL NO. | LOCATION | (MBH) | KW | VOLTS | Ø | CFM | EAT | FLA | VOLTS | Ø | (LBS) | CONTROL | REMARKS | |
| ECH-1 | QMARK FFCH 548 | KITCHEN | 6.8 | 2.0 | 208 | 1 | 300 | 55.0 | 9.6 | 208 | 1 | 25 | NOTE: 1 | NOTE: 2,3 | |
| | | | | | | | | | | | | | | | |
| NOTES: | | | | | | | | | | | | | | | |
| 1. | MANUFACTURER TO PROVIDE UNIT M | OUNTED THERMOSTAT. | | | | | | | | | | | | | |
| 2. | FLA (FULL LOAD AMPS) INCLUDES HEA | ATING ELEMENT AND MC | TOR CURREN | T REQUIREN | IENTS. | | | | | | | | | | |
| 3. | PROVIDE RECESSED LAY-IN CEILING | MOUNTING FRAME. | | | | | | | | | | | | | |



BID/PERMIT SUBMITTAL 5/17/2021

| 1/2" DIA. ALL THRE CONNECTED TO ROC THROUGH ANOTHER | F JOIST | 1/2" DIA. HEA ONE ABOVE AI HANGING ANGL | ND ONE BELOW | 1100 | | | | 0.0.4 | 000 | | | | | |
|---|---|--|---|------------|--------------------|--------------------------|----------------------------------|-------|-----------|----------------------|----------------|-----------------------|------------|------|
| ANGLE | | | | ноор | | MDDEL | MANUFACTURER | | 037 | MAX COOKING | TYPE | APPLIANCE | DESIGN | |
| | | | | | Statistic Solution | 6024 | | | | TEMP 600 | THE . | DUTY | CFM/FT | |
| | | | | 1 | KH-1 | ND-2 | | 1 | 1′0″ | DEG | I | HEAVY | 225 | 247 |
| | | | | ноо. | | ORMATIO | DN | F | ILTER(| S) | | | | Ī |
| ROD AND NUTS TO HANGING ANGLE IS | PRE-PUNCHED AT | | | | TAG | | TYPE | QTY | HEIGHT | LENGTH | | CIENCY @ 7 MICRONS | QTY | |
| HOOD STYLE | 450 DEGREES | 600 DEGREES | 700 DEGREES | 1 | KH-1 | CAPTRATE | SOLO FILTER | 8 | 20″ | 16″ | 85% | SEE FILTER SPEC | 6 | L |
| / MODEL | cfm/ft. | cfm/ft. | cfm/ft. | HOO. | D OPI | TONS | | | 2 | 1 1 | | | | |
| ND2 | 150 | 200 | 250 | | TAG | FIELD V | WRAPPER 18.00 |)″⊢ | D IIGH | IPTION FRONT, P | RIGHT. | | | |
| WITH END PANELS (15% reduction) SLOPED | 127.5 | 170 | 212.5 | | | BACKSPLAS | SH 122.00″ H ND STANDOFF (F | | | 3.00″ LDN 1″ WIDE | NG 4 | 30 SS VER 0" LONG | TICAL. | TFD. |
| SND-2 | 228 | 294 | - | 1 | KH-1 | INSULATIO | IN FOR TOP OF | HOOI | i, | | | | | |
| ISLAND ND-2WI | 269 | 300 | 350 | | | RISER SEN | NSOR INSTALL 3 | IN D | | | | | | |
| | | 422 NG DETA | 475 | | | | LL AS LND I AN | | | | | | | |
| EXHAUST C | FM=LENGTH OF HOC | OD X CFM/LIN.FT. (| .OAD) | | | | | | | | | | | |
| | M=EXHAUST CFM X JCT AREA=144 X | PERCENTAGE REQUI | RED | | | | | | | | | | | |
| DUCT LE | NGTH= | TOTAL DUCT AREA DUCT DEPTH S ARE CALCULATED (| ISING AN EVILAUS | ř | | | | | | | | | | |
| | 0-1800 FPM AND A | SUPPLY VELOCIT | | | | | | | | | | | | |
| | HOODS ARE I | BUILT IN COM | PLIANCE WIT | <u>[Hi</u> | | | | | | | | | | |
| | | | BUILT IN ACCORDANCE WITH NFPA | | | | | | | | | | | |
| #3054804-001 & #3054804-002 | STANDARD 710 | Intertek | No. 96 | | | | | | | | | | | |
| Listed under | | nber 3054804 | -001/002 | | | | | | | | | | | |
| 1/1995 - 510-5200 - 610-5200 | NUTER A DESCRIPTION OF A D | /E OPTIONAL CLE AILABLE AS FOLL | 2020(06240) | | | | | | | | | | | |
| | | AILABLE AS FOLL | 22 | | | | | | | | | | | |
| NON-COMBUSTIBLE | | E REQUIRED |)FF | | | | | | | | | | | |
| COMBUSTIBLE | 1" | NSULATED STANDOFF | | | | | | | | | | | | |
| CLEARAN | CE TO | COMBUS | TIBLES | | | | | | | | | | | |
| | AL "ELELD" CONNEC | CTIONS AND RELATED | | | | | | | | | | | | |
| 2. ALL PLUMBIN INTERCONNEC | TIONS BY ELECTRIC G "FIELD" CONNECT TIONS BY PLUMBING | AL CONTRACTORS. TIONS AND RELATED G CONTRACTORS. | | | | | | | | | | | | |
| PLANS. ALL INSTALLING C | OTHER HANGER MA | ID WELDED AS SHOV ATERIALS PROVIDED I E-AIRE DUCT PER | | | | | | | | | | | | |
| MECHANICAL 5. COOKING EQ | CONTRACTORS'S PL JIPMENT TO SHUTOF IS TO TURN ON IN | FF IN EVENT OF FIR | | | | | | | | | | | | |
| ARE FACTORY HOODS AND | PREWIRED. INTER TO SWITCHES BY EI | TALLED BY CAPTIVE- CONNECTIONS BETWI LECTRICAL CONTRACT INSTALLING CONTRA | CORS. | | | | | | | | | | | |
| 9. SEISMIC RES INSTALLING C | TAINTS ARE RESPON ONTRACTOR. | ISIBILITY OF | | | | | | | | | | | | |
| REPONSIBILIT DATA CONTAI ACCURACY, II CODE REQUI | Y FOR VERIFICATION NED ON THESE DOO NTEGRATION, AND AL REMENTS IN EFFECT | I OF DIMENSIONAL CUMENTS FOR DMINISTRATION OF PRIOR TO ANY | | | | | | | | | | | | |
| RELEASE FOR BALANCE | PRODUCTION OF E | EQUIPMENT SHOWN. | | | | | | | | | | | | |
| 12. KITCHEN SHA TO DINING A | LL BE NEGATIVE WI | | | | | | | | | | | | | |
| | PRESSURE. | | | | | | | | | | | | | |
| | | E PRECEDENCE OVE S OF THIS DOCUMEN TORY PRIOR TO | | | | | | | | | | | | |
| GENERAL | NOTES | | | | | | | | | | | | | |
| 100 | FILTER COLLECTI 2" Captrate Great | ON EFFICIENCY se-Stop Solo Filter | | | | | | | | | | | | |
| 90 | | | | | | | | | | | | | | |
| NCY (%) | | | | | | | | | | | | | | |
| N EFFICIENCY | | | | | | | | | | | | | | |
| 0 10 NOTRATION | | | | | | | ONS, CALL | | | | | | | |
| 10 | | | | 73 | | lton Way, # PHENE: () | #5B, Centennial 720) 570-0981 | | | | | | | |
| 0.1 | PARTICLE | DIAMETER (µm) | 10 | | | | 9) 227-5999 | | | | | | | |
| | | | | [[| | | | | | · | | | | |
| | | | | AL | 1 | ** N∐I LLS ANI | <u>e ***</u>) structur | 2ES | | | *** | | *** | |
| | | | | | | | HIN 18″ OF METAL STU | DS | | • | | NUFACT NDS NE | | |
| | | | | I AN | D SHE | EETROCK | . WOOD STU COMBUSTIBL | JDS | | | | Y DIFF | | 2S |
| ETL Listed | | acting Filters | | i MA | TERIA | AL WITHI Lowed | IN 18″ DF H | | D | IN A | HIN 1 All 1 | lo feet directi | UF DNS. | HDD |
| made Fr | om 430 Stain | uess steel | | įL | | | | | | <u>iL</u> | | | | |
| FILTER [| | | | | | | | | | | | | | |

| | TOTAL EXH CFM | | | EXHA | UST P | | | HOOD CONFIG | | | |
|-------|------------------|-------|------|--------|-------|------|------|-------------|-------------------------|-------|-------|
| ISIGN | | | | F | RISER | 14 | HOOD | END TO | | | |
| M/FT | | WIDTH | LENG | HEIGHT | DIA | CFM | VEL | SP | CONSTRUCTION | END | ROW |
| 225 | 2475 | | | 4″ | 16″ | 2475 | 1773 | -0.872″ | 430 SS WHERE EXPOSED | ALONE | ALONE |

| | | LIGHT(S) | | UTILITY CABINET(S) | | | | | | | |
|-----|-----|----------------|-------|--------------------|-------------|--------------------------|-----------|------------|------------------|----------|-----------------|
| QTY | | | WIRE | LOCATION | SIZE | FIR | RE SYSTEM | ELECTRICAL | SWITCHES | FIRE | HOOD HANGING |
| | 2TY | TYPE | GUARD | | | TYPE | SIZE | MODEL # | QUANTITY | PIPING W | |
| | 6 | L55 SERIES E26 | ND | RIGHT | 12"×60"×24" | TANK FIRE SUPPRESSION | 4.0/4.0 | DC∨-1111 | 1 LIGHT 1 FAN | YES | 999 LBS |

| 1/2' - 13 TPI GRADE 5 (MINIMUM) STEEL HEX NUTS | SUPPLY PLENUM <u>HANGING ANGLE</u> (HARDWARE BY INSTALLER) |
|---|---|
| 1/2" GRADE 5 (MINIMUM) STEEL FLAT WASHER | |
| 1/2" - 13 TPI GRADE 5 (MINIMUM) STEEL ALL-THREAD | |
| 1/2" - 13 TPI GRADE 5 (MINIMUM) STEEL HEX NUT 1/2" GRADE 5 (MINIMUM) STEEL FLAT WASHER | SUPPLY PLENUM HANGING ANGLE (WEIGHT BEARING- ANCHOR POINT FOR SUPPLY PLENUM) |
| | 1/2" GRADE 5 (MINIMUM) STEEL FLAT WASHER 1/2" - 13 TPI GRADE 5 (MINIMUM) STEEL HEX NUT |
| | |

HANGING ANGLE MUST BE SUPPORTED WITH 1/2" - 13 TPI GRADE 5 (MINIMUM) ALL-THREAD, SANDWICH HANGING ANGLES AND CEILING ANCHOR POINTS WITH 1/2" GRADE 5 (MINIMUM) STEEL FLAT WASHERS AND 1/2" - 13 TPI GRADE 5 (MINIMUM) HEX NUTS AS SHOWN. MUST USE DOUBLED HEX NUT CONFIGURATION ABOVE CEILING ANCHORS. SINGLE HEX NUT BENEATH HANGING ANGLE IS ACCEPTABLE FOR PSP HANGING ANGLES. MAINTAIN 1/4" OF EXPOSED THREADS BENEATH BOTTOM HEX NUT. TORQUE ALL HEX NUTS TO 57 FT-LBS.

ASSEMBLY INSTRUCTIONS


<u>System Design Verification (SDV)</u>


If ordered, CAS Service will perform a System Design Verification (SDV) once all equipment has had a complete start up per the Operation and Installation Manual. Typically, the SDV will be performed after all inspections are complete.

Any field related discrepancies that are discovered during the SDV will be brought to the attention of the general contractor and corresponding trades on site. These issues will be documented and forwarded to the appropriate sales office. If CAS Service has to resolve a discrepancy that is a field issue, the general contractor will be notified and billed for the work. Should a return trip be required due to any field related discrepancy that cannot be resolved during the SDV, there will be additional trip charges.

During the SDV, CAS Service will address any discrepancy that is the fault of the manufacturer. Should a return trip be required, the general contractor and appropriate sales office will be notified. There will be no additional charges for manufacturer discrepancies.

| | *** NOTE *** |
|------|-------------------------|
| | MAKE-UP AIR SHALL BE |
| IS | DELIVERED INTO SPACE |
| | IN MANNER THAT WILL NOT |
| ID 🛛 | DISRUPT HOODS ABILITY |
| 1 | TO CAPTURE AND CONTAIN. |





 \sim

 \triangleleft

80

 $\langle \rangle$

ING

Ŷ


 $\langle \rangle$


 \vdash

 \triangleleft

AMBD,


 \vdash $\langle \rangle$






FIRE SYSTEM INFORMATION - JOB#4891037

| FIRE | | | | | FLOW | INSTALL | ATION |
|----------------------|--------|------------------|----------|---------------------|--------|--------------------|------------------|
| SYSTEM ND | TAG | TYPE | | SIZE | PDINTS | SYSTEM | LOCATION ON HOOD |
| 1 | FS-1 | CAS ELECTRIC WET | CHEMICAL | 4.0/4.0 | 9 | FIRE CABINET RIGHT | RIGHT, HOOD 1 |
| GAS V | ALVE(S | 5) | | | | | |
| FIRE SYSTEM ND | 1 TAG | TYPE | SIZE | SUPPLIED BY | | | |
| 1 | FS-1 | SC ELECTRICAL | 2.000 | CAPTIVEAIRE SYSTEMS | | | |





 \sim $\overline{}$


2


UB

S

BID/PERMIT

| TAN JNIT ND | TAG | QTY | | FAN UN | IIT MOD | EL # | MAN | UFACTURER | CFM | ESP | RPM | MDTD ENCL | | HP | BHP | PHASE | VOLT | FLA | | HARGE | | VEIGHT (LBS) | SONES | | | | | | | |
|-------------------|--------|--|--|---------------|------------------|-------------------|---------|------------------------|----------|-----------------------|--------------|---------------------|------|------------|----------|-------|----------------------------|---------|--|---------|------------|-----------------|------------------------------|-------------------------------|-------------|--------------------------------|------------------------------------|---------------------------------|----------------------------|---------|
| | KEF-1 | 1 | | DL | J180HFA | | CAF | PTIVEAIRE | 2475 | 1.500 | 1353 | DDP,PREI | MIUM | 2.000 | 1.2990 | 3 | 208 | 8.3 | 572 | PPM | | 185 | 20 | | | | | | | |
| UA | FAN | INFO | RMA I | 'ION - | - <i>JOE</i> | #48910 |)37 | | | | | | | | | | | | | | | | | | | | | | | |
| AN NIT ND | TAG | QTY | | FAN UN | IIT MOD | EL # | BL | OWER H | JUSING | MIN I CFM | ESIGN CFM | ESP I | RPM | MOT ENI | | HP | BHP | PHASE | VOLT | FLA | MCA | | EVAP LOW RATE (Gal/Hr) | EVAP COOL ENTERING TEMP | DB EN | AP COOLEF TERING WI TEMP | REVAP COOLER LEAVING DB TEMP | REVAP COOL LEAVING W TEMP | B (LBS) | SONE |
| 2 | MAU-1 | 1 | | A2-1 | D.250-2 | OD | 20MF | -2-MOD A2 | 2-D.250 | 2000 | 2475 | 1.250 1 | 548 | DDP,PR | EMIUM | 2.000 | 1.4680 | 3 | 208 | 6.1 | 7.7A | 15A | 3.56 | 90.0°F | | 55.0°F | 68.0°F | 55.0°F | 931 | 15.3 |
| vap | Flow R | ate is | varial | ole bas | ed on | water pr | ressure | | | 5 | | | | | | | | | | 8 | | 1 | | | 5 | | | 1 | | 3 |
| | FIRED | MAI | KE - U | P AIR | UNI | T(S) | | | | | | | _ | | | | | | | | | | | | | | | | | |
| 'AN NIT ND | TAG | INF BT | | UTPUT BTUs | TEMP | RISE | | IRED INPUT PRESSURE | GAS | GAS T | PE EFF | BURNER ICIENCY(7 | | | | | | | | | | | | | | | | | | |
| 2 | MAU-1 | 210 | 849 | 193521 | 95 | °F | 7 IN. V | W.C 14 I | N. W.C. | NATUR | AL | 92 | | | | | | | FAN | | 04FA - | EVHALIST | FAN (KEF-1 | N. | | | | | | |
| 4N | OPTIC | NS | | | | | | | | | | | | | | | | | | #1 DOIG | | LATHUST | | <u><</u> | | | | FE | ATURES: | |
| AN NIT | TAG | QTY | | | | | | DESCR | IPTION | | | | | | | | | | | | | | | | | | | - DIRF | CT DRIVE C | |
| ND | ing. | | | | ~ | | | DECON | | | | | | | | | | | | | | - | | - 37 3/8 | | | | - ROOF | F MOUNTED F | ANS. |
| 9 | | 1 | - | SE BOX | | | TNOTALL | | | | DUCTO | | | | - 12 | | | | | | | | \int | | | | | | FAURANT MOD 05 AND UL76 | |
| 1 | KEF-1 | | | | | | INSTALL | ED AT PLA | ANI - FL | K GREASE | DOC12. | | | | | | | | | | | | 1 | | \ | | | - VAR | IABLE SPEED | CONTR |
| | | 1 2 YEAR PARTS WARRANTY. 1 SIZE 2 DIRECT FIRED HEATER LOW CFM PROFILE PACKAGE. USED ON HEATERS UNDER 2500 1 CFM. | | | | | | | | | | | | | I | | 1 | - THEF | RNAL WIRINO RMAL D∨ERLO I HEAT DPER∕ | JAD PR | | | | | | | | | | |
| | | 1 | 1 INLET PRESSURE GAUGE, 0-35". | | | | | | | | | | | | | | | | | | | | | L | y | | - GREA | ASE CLASSIFI | | |
| | | 1 | 1 MANIFOLD PRESSURE GAUGE, -5 TO 15" WC. | | | | | | | | | | |] | | | | | | | | | | • | | | - NEMA | A 3R SAFETY | DISCE | |
| | | 1 CASLINK BUILDING MONITORING SYSTEM - INTERNET OR CELLULAR CONNECTION REQUIRED. | | | | | | | | | | | | | | | 33 374 | | | | | | 45 | | AL TEMPERAT | | | | | |
| | | 1 | 1 MOTORIZED BACKDRAFT DAMPER FOR A2-D HOUSING, MEETS AMCA CLASS 1A RATING. | | | | | | | | | | | - | | | | | | | | | 4 | |) | 22 5/8 | | UST FAN MUS E EXHAUSTIN | | |
| 5 | MAU-1 | 1 | 1 TOTAL CFM MONITORING FOR MUA UNITS. 1 FREEZESTAT. | | | | | | | | | | | | | | | | | | 1 | | | | | | | L ALL FAN P MAL EQUILIB | | |
| | | 1 | 1 IBT/MUA EVAP INTERLOCK. | | | | | | | | | | | | | | | | | | | | | | F | | DETE | RIDRATING E | FFECT | |
| | | 1 FREEZE PROTECTION DRAIN KIT FOR IBT/MUA WITH EVAPORATIVE COOLERS. | | | | | | | | | | | | | | | $\langle \rangle$ | GREA | SE DRAIN. | WOUL | D CAUSE UN | SAFE [| | | | | | | | |
| | | 1 | 1 SEPARATE 120V WIRING PACKAGE (REQUIRED AND USED ONLY FOR DCV OR PREWIRE WITH | | | | | | | | | | | | | | RMAL FLARE- | | | | | | | | | | | | | |
| | | ÷. | 1 2 1 1 2 1 1 2 1 1 1 1 | | | | | | | | | | | | | | UST FAN MUS E EXHAUSTIN | | | | | | | | | | | | | |
| | | 1 | | AR PAR | IS WAR | KRANTY, | | | | | | | | | _ | | | | | | | 1 | - | - 16 1/2 | - | | | | 00°F (316°C) NUTES WITH | |
| $\frac{4N}{1}$ | ACCES | SSOR | IES | | | | | | | | | | | | | | | | | | | | Ĩ | | | | | DAMA | GED TO ANY | EXTEN |
| AN | | | EX⊢ | AUST | | | SL | JPPLY | | | | | | | | | | | | | | | | | | | | AN U | NSAFE CONDI | TION. |
| INIT | TAG | 8 2 | | | | | | | | _ | | | | | | | | | | | | | - <u>-</u> | 26 | <u> </u> | - | | DPT | IONS | |
| ND | | GREA | | AVITY MPER M | | SIDE DISCHARGE | | TY MOTORIZ | | | | | | | | | | | | | | | | 22 | ļ. | - | | | ASE BOX. | |
| 1 | KEF-1 | YES | | | | | | | | | | | | | | | | | | | | F | 1 | - 28 - / | - | - | | PLA | N BASE CERAL | REASE 1 |
| 2 | MAU-1 | | _ | | | YES | | YES | | | | | | | | | | | | | | | 1 | $\vee \vee$ | | | | 2 1 | 'EAR PARTS ' | WARRAN |
| | ASS | | IES | | | XACONOM | | | W. | | | | | | | | | | | | | | | | | | | | | |
| | | | AG | | WEIG | нт | L | ТЕМ | | | | | SIZE | | | | | | | | | | | | | | | | | |
| U c | - HIN | | | | Sec. 2311 - 1-12 | - | | | | | | | | 10.000 D | ITCH | | ITED H | | - | | | | | - 37 3/8 — | | | | | | |
| F | # 1 | 175 | F _1 | | 041 | DC I | 0 | LIDD | 26 E00#1 | V OZ EGO | | | | | | | | | | | | | | | | | | | | |
| F | # 1 | KE | F-1 | 7 | 34 L 90 L | 100.02 | | /30314-5414 | 26.500"W | X 26.500 X 79.000* | | | | | | | 1000000 U | IINGED. | | | | H | 17 | - 28 | | | | | | |







- TION (NO BELTS/PULLEYS),
- C-S645
- ECTION (SINGLE PHASE).
- 0°F (149°C). TESTING.
- NECT SWITCH.

TE CONTINUOUSLY F 300°F (149°C) /E REACHED D WITHOUT ANY] THE FAN WHICH ERATION.

E CONTINUOUSLY GREASE VAPORS ERIOD OF FAN BECOMING THAT COULD CAUSE


_ - INSTALLED AT UCTS.







Sheet Number


M402







/17/2021 8:18:12 AM FILE: E:\20013.00 TERRY SPORTS BUILDING_










| ND TAG | PACKAGE # | <u> </u> | 0.050.560.000.4 | | SWITCHES | | | ΠP. | TION | |
|---|---|---|--|---|---|---|--|--|---|--|
| | | | | LOCAT 11 - SHIP L | DOSE W/ | QUANTITY 1 LIGHT | | | | |
| 1 ECP-1 | DC∨-1111 | UTILITY CAB | BINET RIGHT | ноо Наар | | 1 FAN | | SMART CON | NTROLS DC | V |
| | | | | | | | | | la la | MODEL NUM |
| Conr | minal Blocks for nection for Modb ired OR Field Wir | | | Field Con | nection Antennas | | JOB NO 4 | 891037 | | JOB NAME |
| | tion to Router_ thernet switch | | | Wired DR | Paddle | | BREAK | R PANEL TO | PRIMARY | CONTROL |
| | (of | | | - Cellular Module | | | 3 BREA | KER SIZE SHOW | ility: Elect N IS THE MA | |
| | | | Conpute n | | | | 4 BREAKER 19 5 120 V 5 15 A | | | Hot Neutral Ground IT WIRE |
| Unda | 62 | <u>nk Monitor</u> to support comm | | | | | 6 | TD GFCI DR BREAKER. 1ST HODD LIGHT CONTROL POWER. | BREAKER SHARED | |
| Management – Hood C monitor rea | System. ontrol Panel t l time parame | to allow cloud-b eters outlined as to allow cloud-b | based Building s MONITOR in | Management Sy the points list. | ystem to | | 7 BREAKER 31 208 V MCA= 10.4 A MDCP: 20 A | | | |
| control para – Hood C | emeters outlin ontrol Panel t SYSTEM ECON | ed as CONTROL to allow cloud-b OMIZER control | in the points based Building | list. Management Sy | ystem to | | 9 BREAKER 3 | | SM-1 QUICK СОММЕСТО —————— | IR <u>LINE</u> |
| | | ITORING AND | CONTROL PO | <u>INTS LIST</u> | | | 208 V 10 MCA: 7.6 A MDCP: 15 A | MAU-1 | SM-2 | <u>LINE</u> <u>Ground</u> |
| DCV Packages Room Temperature Duct Temperature(s) | М | unction ONITOR | SC Packages Room Tempero | ature(s) | Function MONITOR | | 11 | VIRE TO VFD G | QUICK CONNECTO | JR |
| Duct Temperature(s) MUA Discharge Temper Kitchen RTU Discharge | ature MC | ONITOR ONITOR ONITOR | Duct Temperat MUA Discharge Kitchen RTU L | | MONITOR MONITOR ure MONITOR | | 12 | Responsib | PANEL TO ility: Electi | |
| an Speed an Amperage | м | ONITOR ONITOR | Controller Fau Fan Faults | | MONITOR MONITOR | | 14 Load Wirin | 9 — | | FAN: 01 |
| 'an Power 'FD Faults | м | ONITOR ONITOR | Fan Status PCU Faults | | MONITOR MONITOR | | 15 SM-1 VIRE TO VFD QUICI CONNECTO | | | |
| Controller Faults Fan Faults | м | ONITOR ONITOR | PCU Filter Clo Fire Condition | í | MONITOR MONITOR | | 16 | | HAVE ITS DWN IT SHARE CONDU | |
| 'an Status PCU Faults PCU Filter Clog Percen | М | ONITOR ONITOR ONITOR | CORE Fire System Building Press Fans Button(s | sures | MONITOR MONITOR | ONTROL | SM-2 VIRE TO 18 VFD QUIC | | | 27 Visiting 1 |
| Fire Condition CORE Fire System | M | ONITOR ONITOR | Lights Button(s | • | MONITOR & CO MONITOR & CO MONITOR & CO | ONTROL | 19 IF VFD MU | R NIO | HAVE ITS OWN | |
| uilding Pressures Prep Time Button | М | ONITOR ONITOR & CONTROL | | | | | 20 VIRE SF 3 FRDM PANE ECPM03. FAN STAR | IGNAL DO NO | IT SHARE CONDU | וידנ |
| ans Button Aights Button | М | ONITOR & CONTROL | - | | | | 21 SIGNAL 21 TO MUA BOA | SECIO | 84VAC | |
| and the second se | | ONITOR & CONTROL | | | | | | | | |
| usn Dutton | 1.00 | UNITOR & CONTROL | 1 | | | | 22 | | | |
| | | | | | | | 23 | | | |
| <u>Wr</u> moo far <u>Lis</u> ano | <u>ID</u> CIN itten Sp dulates H ns runnir tings: Mo d complie | <u>ITROL</u> PA ecification fans base ng on high odels Elect es with UL | <u>ns:</u> The h ed on coc n speed o trical Col 508A Sta | ood contr oking load during coo ntrol Pan ndards ar | rol panel I. Modulat oking oper nel are ET nd CAN/CS | with dem tion allow ^ation. `L Listed SA C22.2, | LATION and contr s for en under fi No. 14-05 | rol ventilo ergy savi .e number Standar | ings cor 101754 ds. | utomat mpared 591CDL |
| H Wr mod far Lis and ECF 610 | <u>ID CIN</u> <u>itten Sp</u> dulates f hs runnir <u>tings</u> : Mo d complie PM03 Circ 10-1 Sta <u>quence c</u> | <u>ITROL</u> PA ecification fans base ng on high odels Elec | n <u>s:</u> The h ed on coo n speed o trical Coi 508A Sta d is ETL d CAN/CS/ | ood contr oking load during coo ntrol Pan ndards ar Listed un A C22.2, N | rol panel 1. Modulat oking oper nel are ET nd CAN/CS der file r lo. 61010-1 | with dem tion allow ration. TL Listed SA C22.2, number 10 Standar | LATION and controls for end under fi No. 14-05 00901773BC | rol ventili ergy savi .e number Standar X-001 anc | ngs cor 101754 ds. X compli | utomat mpared 591CDL es with |
| H Wn mod far Lis and ECF 610 Sec uni The | <u>D</u> CDN <u>itten Sp</u> Julates H ns runnir <u>tings</u> : Mc J complie PM03 Circ 10-1 Sta <u>quence c</u> t. | <u>ITROL</u> PA ecification fans base ng on high odels Elect s with UL cuit Board ndard and of Operati | <u>ns:</u> The h ed on coc speed o trical Col 508A Sta d is ETL 1 d CAN/CSf <u>ions:</u> The | ood contr oking load during coo ntrol Pan ndards ar Listed un A C22.2, N hood cor | rol panel 1. Modulat oking oper nel are ET nd CAN/CS der file r lo. 61010-1 ntrol pane | with dem tion allow ration. TL Listed SA C22.2, number 10 Standar el interlo | LATION and controls for end under fi No. 14-05 00901773BC ods. bocks the | rol ventili ergy savi Standar X-001 anc exhaust f | ngs cor 101754 ds. d compli fan with | utomat mpared 591CDL es with h make |
| H Wn mod far Lis and ECF 610 Sec uni The | D CON itten Sp dulates f s runnir tings: Mo d complie PM03 Circ 10-1 Sta quence c t. e hood c y given f <u>Automo</u> exhaus | <u>ITROL</u> PA ecification fans base ng on high odels Elect s with UL cuit Board ndard and of Operati | ns: The h ed on coo speed o trical Col 508A Sta d is ETL 1 d CAN/CS ions: The anel is co DCV hood henever | ood contr oking load during coo ntrol Pan ndards ar Listed un A C22.2, N hood cor apable of I control elevated | rol panel Modulat oking oper nel are ET nd CAN/CS der file r lo. 61010-1 ntrol pane operating package temperat | with dem tion allow ration. EL Listed SA C22.2, number 10 Standar el interlo g in one is design ures are | LATION and controls for end under fi No. 14-05 00901773BC ods. ocks the or more ed to the | rol ventili ergy savi Standar X-001 and exhaust f of the fo ermostation in the ex | ngs cor 101754 ds. d compli fan with ollowing cally ac chaust s | utomat mpared 591CDL es with h make state state |
| H Wn mod far Lis and ECF 610 Sec uni The | D CON itten Sp dulates f hs runnir tings: Mod complie PM03 Circ 10-1 Sta quence c t. e hood c y given f Automo exhaus 507.1.1 Once t hyster syster degree | <u>NTROL</u> PA <u>ecification</u> fans base ng on high odels Elect s with UL cuit Board ndard and <u>of Operation</u> time. <u>atic:</u> The I st hood w | <u>ns:</u> The h ed on coo speed o trical Coo 508A Sta d is ETL 1 d CAN/CSA ions: The anel is co DCV hood henever 508.1 by p temperat ced. The 1 the activ | ood contro- oking load during coo ntrol Pan ndards ar Listed un A C22.2, N hood cor apable of l control elevated providing sure react cycling of hysteresi ation set | rol panel Modulat oking oper nd CAN/CS der file r lo. 61010-1 ntrol pane operating package temperat a thermos hes the fans s is facto point. A | with dem tion allow ration. "L Listed SA C22.2, number 10 Standar el interlo g in one is design ures are stat(s) m activation s after ory set | LATION and controls for end under fi No. 14-05 00901773BC ods. ocks the or more ed to the esensed nounted in the cooki 2 degrees | rol ventile ergy savi Standar X-001 and exhaust f of the fo ermostation the duc the duc he exhaus ng appliar s and will | ings cor 101754 ds. d complie fan with ollowing cally ac chaust s cally ac chaust s | utomat mpared 591COL es with h make state state system ood ris s and ive bee the ex |
| H Wn mod far Lis and ECF 610 Sec uni The | D CON itten Sp dulates the s runnir tings: Mod complie PM03 Circo 10-1 Sta quence c t. e hood c y given to Automo exhaus 507.1.1 Once to hyster degree activator The po conditi | <u>ITROL</u> PA <u>ecification</u> fans base ng on high odels Elect s with UL cuit Board ndard and <u>of Operation</u> time. <u>atic:</u> The I and IMC 5 the duct resis to p n is reduce the duct | ns: The h ed on coo speed o trical Coi 508A Sta d is ETL 1 d CAN/CS ions: The anel is co DCV hood henever 508.1 by p temperat core temper ctory co | ood contro oking load during coo ntrol Pan ndards ar Listed un A C22.2, N hood cor apable of l control elevated providing sure react cycling of hysteresis ation set nature ris nfigured | rol panel Modulat oking oper nel are ET nd CAN/CS der file r lo. 61010-1 ntrol pane operating package temperat a thermos hes the o the fact point. A se, to shut o | with dem tion allow ration. "L Listed SA C22.2, number 1(Standar el interlo el interlo g in one is design ures are stat(s) m activation s after ory set hystere down sup | LATION and contros for environment under fi No. 14-05 00901773BC ds. ocks the or more ed to the consed nounted in the cooki 2 degrees sis timer | rol ventili ergy savi Standar X-001 and exhaust f of the fo ermostation the duc the duc he exhau: ng applian s and will also exist | ings cor 101754 ds. d complie fan with ollowing cally ac chaust so to ho st fans nces ha keep - ts to k the ex | utomat mpared 591COL es with h make state state system cod ris s and the ex the ex the ex |
| H Wn mod far Lis and ECF 610 Sec uni The | D CON itten Sp dulates to tings: Mod complie PM03 Circo 10-1 Sta quence co t. e hood co y given to Automo exhaus 507.1.1 Once to hyster degree activator The po conditi The Do automo | <u>ITROL</u> PA <u>ecification</u> fans base ng on high odels Elect s with UL cuit Board ndard and of Operation time. <u>atic:</u> The I and IMC 5 the duct resis to p n is reduce the duct resis to p n is reduce the duct resis to p n is reduce | ns: The h ed on coo speed o trical Coi 508A Sta d is ETL 1 d CAN/CS/ ions: The anel is co DCV hood henever 508.1 by p temperat corevent o the activ he temper ctory co down to it does | ood control during load during coo ntrol Pan ndards ar Listed un A C22.2, N hood cor apable of l control elevated providing sure react cycling of hysteresis ation set nature ris nfigured 20-25% o not sens | rol panel Modulat oking oper nel are ET nd CAN/CS der file r lo. 61010-1 ntrol pane operating package temperat a thermos hes the o the factor point. A se, to shut o f total e e a need | with dem tion allow ration. "L Listed SA C22.2, number 10 Standar el interlo g in one is design ures are stat(s) m activation s after ory set hystere down sup | LATION and contros for end under fi No. 14-05 00901773BC ds. ocks the or more ed to the cosensed nounted in the cooki 2 degrees sis timer oply fans, n prep mo | rol ventili ergy savi Standar X-001 and exhaust f of the fo ermostation in the exhaust the duc he exhaust he exhaust also exist turn on ode. The son, The | ings cor 101754 ds. d complie fan with ollowing cally ac chaust so to ho st fans nces ha keep - ts to k the ex system DCV will | utomat mpared 591COL es with h make state state state system cod ris s and the ex the ex the ex the ex the ust the ust |
| H Wn mod far Lis and ECF 610 Sec uni The | D CON itten Sp dulates for his runnin tings: Mo complie PM03 Circ 10-1 Sta quence c t. e hood c y given for Automa exhaus 507.1.1 Once t hyster degree activa The po conditi The DC automa and th In the detect Ansul panel building | <u>NTROL PA</u> <u>ecification</u> fans base ng on high odels Elec- es with UL cuit Board ndard and of Operation time. <u>atic:</u> The I and IMC 5 the duct resis to p n is reduce the duct resis to p n is reduce the duct ted by th anel is fac ion. CV turns atically if ne low spe e event of tion link in ation sign Automan w will send of g-initiating | ns: The h ed on coon speed of trical Col 508A Sta d is ETL 1 d CAN/CSA ions: The anel is co DCV hood henever 508.1 by p temperat brevent of ced. The 1 the activ he temper ctory co down to it does sed and A f a fire, h the hoo hal via th The DCV vill close a signal g switch | ood contro- bking load during coo ntrol Pan ndards an Listed un A C22.2, N hood cor apable of I control elevated providing of hysteresis ation set cycling of hysteresis ature reac cycling of hysteresis ature ris nfigured 20-25% o not sense high speed there ar of may me there ar of may me the mech to the sh can be us | rol panel Modulat oking oper nel are ET nd CAN/CS der file r no. 61010-1 ntrol pane operating package temperat a thermos hes the fans s is facto point. A se, to shut o f total e e a need d settings re two fo elt. The r vitch and n turn DN nanical gas hunted po sed to no | with dem tion allow ration. "L Listed SA C22.2, number 1(Standar el interlo g in one is design ures are stat(s) m activation s after ory set hystere: down sup exhaust i for hoo s are fu ms of a Ansul Au building- the exh s valve - otify the | LATION (and contros for end under fi No. 14-05 00901773BC ods. ocks the or more ed to the consed or more ed to the sensed nounted in the cooki 2 degrees sis timer oply fans, n prep mo d operation. toman tak initiating to close for the breck building of the breck | rol ventiliergy savi e number Standar X-001 and exhaust f of the fo ermostation the duc he exhaust the duc he exhaust for the fo ermostation exhaust the duc he exhaust for the solution con the | ings cor 101754 ds. d complie fan with ollowing cally ac chaust s to r ho st fans nces ha keep - ts to k the ex system DCV will ed on a chanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical | utomat mpared 591COL es with h make state state state state system od ris s and the ex the ex |
| H Wn mod far Lis and ECF 610 Sec uni The | D CON itten Sp dulates for his running tings: Mod complie PM03 Circo 10-1 Sta quence co t. e hood co y given for Automo exhaus 507.1.1 Dince t hyster degree activa The po conditi The DC automo and th In the detect Ansul panel building Manuali | <u>NTROL PA</u> <u>ecification</u> fans base ng on high odels Elec- es with UL cuit Board ndard and of Operation and IMC 5 the duct resis to p n is reduce the duct the duct th | ns: The h ed on coon speed of trical Con 508A Sta d is ETL 1 d CAN/CSA ions: The anel is co DCV hood henever 508.1 by p temperat brevent of revent | ood controling load during coor ntrol Pan ndards an Listed un A C22.2, N hood cor apable of l control elevated providing of hysteresis ation set cature ris nfigured 20-25% of not sense nigh speed there ar of may me the mech to the sh can be us ates base | rol panel Modulat oking oper hel are ET nd CAN/CS der file r no. 61010-1 ntrol pane operating package temperat a thermos hes the fans s is facto point. A se, to shut o f total e e a need d settings re two fo st. The r vitch and n turn DN nanical gas hunted po sed on hum | with dem tion allow ration. "L Listed SA C22.2, number 1(Standar el interlo g in one is design ures are stat(s) m activation s after ory set hystere: down sup exhaust i for hoo s are fu rms of a Ansul Au building- the exh s valve - ortion of otify the man input | LATION (and contros for end under fi No. 14-05 0901773BC ods. ocks the or more ed to the cosensed nounted in h point, t the cooki 2 degrees sis timer oply fans, n prep mo d operation. to prep mo d operation. to close f the bree building of from an | rol ventiliergy savi e number Standar X-001 and exhaust f of the fo ermostation in the exhaust the duc he exhaust the duc he exhaust for the fo ermostation exhaust the duc he exhaust for the solution con the so | ings cor 101754 ds. d complie fan with ollowing cally ac chaust : to r ho st fans nces ha keep - ts to k the ex system DCV will ed on c chanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical mechanical | utomat mpared 591COL es with h make state |
| H Wn mod far Lis and ECF 610 Sec uni The | D CON itten Sp dulates for his runnin tings: Mo complie PM03 Circ 10-1 Sta quence c t. e hood c given Automo exhaus 507.1.1 Dince t hyster degree activa The po conditi The DC automo and th In the detect Ansul panel building Manuali Schedu per do the sy mode o | <u>NTROL PA</u> <u>ecification</u> fans base ng on high odels Elec- es with UL cuit Board ndard and of Operation time. <u>atic:</u> The I and IMC 5 the duct resis to p n is reduce the duct resis to p n is reduce the duct ted by th anel is fac ion. CV turns atically if ne low spe e event of tion link in ation sign Automan w will send of g-initiating | ns: The h ed on coon speed of trical Con 508A Sta d is ETL 1 d CAN/CSA ions: The anel is co DCV hood henever 508.1 by p temperat orevent of revent | ood controling load during coor ntrol Pan ndards an Listed un A C22.2, N hood cor apable of l control elevated providing of hysteresis ation set cature ris nfigured 20-25% of not sension sture reach cycling of hysteresis ation set ation set ation set ation set sature ris nfigured 20-25% of not sension there ar of may me the mech to the sh can be us ates base dule can b solute to t | rol panel Modulat oking oper hel are ET nd CAN/CS der file r no. 61010-1 ntrol pane operating package temperat a thermos hes the fans s is facto point. A se, to shut of f total e e a need d settings re two fo elt. The r witch and n turn DN anical gas hunted po sed to no ed on hum be set to o set up heir need re algorit | with dem tion allow ration. "L Listed SA C22.2, number 1(Standar el interlo g in one is design ures are stat(s) r activation s after ory set hystere: down sup exhaust i for hoo s after ory set hystere: down sup exhaust i for hoo s are fu building- the exh s valve - ortion of otify the nan input a time t s. Any ti chm base | LATION and controls for end under fi No. 14-05 00901773BC ods. ocks the or more ed to the consection or more ed to the consection or more ed to the sensed n point, t the cooki 2 degrees sis timer oply fans, n prep mod d op and just activation. to close for the breat building of the that is su ime that is on temp | rol ventiliergy savi e number Standar X-001 and exhaust f of the for ermostation in the exhaust the duc he exhaust the duc he exhaust for the for sand will also exist turn on ode. The se turn on ode. The so turn on the shaust turn on the savit turn of the gas l the gas l the gas l the gas l the gas l the for the so the so | 101754 ds. 101754 ds. d complie fan with ollowing cally ac chaust : to r ho st fans nces ha keep - ts to k the ex system DCV will ed on c chanical mechanic n eithe ine or el to re the ine f the ine or el to re the ine | utomat mpared 591COL es with h make state |
| H Wn mod far Lis and ECF 610 Sec uni The | D CON itten Sp dulates for his runnin tings: Mo d complie PM03 Circ 10-1 Sta quence c t. e hood c y given for Automo exhaus 507.1.1 Dince t hyster degree activa The po conditi The DC automo and th In the detect Ansul panel building Manual Schedu per do the sy mode o an ext | <u>NTROL PA</u> <u>ecification</u> fans base ng on high odels Elec- es with UL cuit Board ndard and of Operation and IMC 5 the duct resis to p n is reduce the duct the duct resis to p n is reduce the duct the duc | ns: The h ed on coon speed of trical Con 508A Sta d is ETL 1 d CAN/CSA ions: The anel is co DCV hood henever 508.1 by p temperat orevent of ed. The 1 the activ he temper ctory co down to it does eed and A f a fire, n the hood at does eed and A f a fire, n the bCV vill close a signal g switch tem oper kly scheo w for th run suita t to pre | ood contro- bking load during coo ntrol Pan ndards an Listed un A C22.2, N hood cor apable of l control elevated providing of hysteresis ation set cature ris nfigured 20-25% of not sensi- hysteresis ation set sature ris nfigured 20-25% of not sensi- not sensi- ates base dule can k- ates base dule can k- ie user to able to to vent unin | rol panel Modulat oking oper- nel are ET nd CAN/CS der file r lo. 61010-1 ntrol pane operating package temperat a thermos hes the fans s is facto point. A se, to shut of f total e e a need d settings re two fo elt. The d vitch and n turn DN nanical gas heir need re algorit heir need re algorit heir need | with dem tion allow ration. "L Listed SA C22.2, number 1(Standar el interlo g in one is design ures are stat(s) r activation s after ory set hystere: down sup exhaust i for hoo s after ory set hystere: down sup exhaust i for hoo s are fu rms of c Ansul Au building- the exh s valve - ortify the han input a time t s. Any ti chm base ctivation | LATION and controls for end under fi No. 14-05 00901773BC ods. ocks the or more ed to the consection the cooki 2 degrees sis timer oply fans, n prep mod d op endition to close for the breat indicating in to close for the breat the breat indicating in to close for the breat the brea | rol ventiliergy savi e number Standar X-001 and exhaust f of the for ermostation the duc he exhaust the duc he exhaust the duc he exhaust the duc he exhaust the duc he exhaust for the for sand will also exist turn on ode. The se turn on ode. The so turn on turn on the gas turn of the gas the g | ings cor 101754 ds. d complie fan with ollowing cally ac chaust s t or ha st fans nces ha keep - ts to k the ex system DCV will ed on a chanical mechanical | utomat mpared 591COL es with h make state |

7/2021 8:18:13 AM FILE: E:\20013.00 TERRY SPORTS BUILDING V19



aust fans and make-up air for an ion will meet the requirements of IMC nse increased exhaust temperatures.

e activated. The controls also provide d off and the heat in the exhaust nning until the temperature falls 2 running for at least 30 min after being

I turn off the hood lights in a fire

curning down to 0% when operating fans it is controlling based on demand

ay be activated or the mechanical nd converts it to an electric CV will be electrically notified via the t and turn off the hood lights. The gas valve is used, the hood control om the cooking appliances. The

e day. There are three occupied times that is within the defined occupied time, me, the system will run at modulation g unoccupied time, the system will have system is not being occupied.

d-wired interlock)

ROOM TEMPERATURE SENSOR

The Room Temperature sensor is a 10K [hm Thermistor. The sensor provides constant room temperature to the controller. It should be installed on a wall somewhere in the space but not directly under the hood or close to an appliance so that the reading is not affected by heat.

Typically a system will have one room temperature sensor. However, systems configured with 2 fan zones have the option to be ordered with 2 room temperature sensors, one for each zone. They should be mounted in the space accordingly.

