

Wohnrade Civil Engineers, Inc.

April 22, 2022

Mr. Ben Beall
City Engineer
City of Steamboat Springs
Engineering Division
137 10th Street
Steamboat Springs, Colorado 80487

Subject: Final Summary of Findings
Hampton Inn & Holiday Inn Express
Walton Creek HEC-RAS Split Flow Analysis
Steamboat Springs, Colorado

Dear Mr. Beall:

Wohnrade Civil Engineers, Inc. (WCE) has completed a Final HEC-RAS analysis that reflects Existing and Proposed Project conditions along Walton Creek as it relates to the subject land development project and its impact on the Walton Creek base flood elevations.

This final hydraulic analysis is intended to model a split flow along Walton Creek, the location of which is located roughly 0.28 miles south of the subject site. The model also includes a proposed inline structure (overflow weir) located at the southwest corner of the Homewood Suites property. The weir is intended to limit the 100-yr peak discharge along the east side of Highway 40 and alleviate current downstream flooding issues.

The WCE HEC-RAS analysis includes the reach along Walton Creek between the bridge crossing at E. U.S. Highway 40 at the downstream end, and the Duplicate Effective HEC-RAS Cross-Section 7176.41 at the upstream end for a total length of approximately 0.70 miles. The subject project is located between Cross-Sections 4178.71 and 3742 at the upstream and downstream locations respectively. The Proposed Project analysis also models a future bridge crossing at Stone Lane that was originally designed by Owen Consulting in May 2015. See attached plan and profile sheet prepared by Owen Consulting in Appendix D.

HEC-RAS models have been prepared for both Existing Conditions and Proposed Project conditions using the improved topographic information. All hydraulic modeling has been performed using HEC-RAS analysis engine 5.0.7. and is referenced to the NGVD 29 vertical datum. A full and complete floodway analysis has not been performed and is beyond the scope of this project.

The peak discharge in the Existing Conditions and Proposed Project models varies from 1,883 cfs at the upstream end of the model to 1,984 cfs at the downstream end of the model adjacent to Highway 40.

A Split Flow analysis was performed due to conditions approximately 0.28-miles upstream of the project site. There are historic storm events, as well as topographic evidence to suggest that the flood flow departs the Walton Creek main channel and meanders to the northwest towards E. U.S. Highway 40. Flow to the northwest is facilitated by a myriad of braided wetlands channels. Once this split flow occurs (at river Station 6335) it is difficult for flows to return to the main channel which is located roughly 750-feet to the east. The split flow channel along the east side of Highway 40 is 3.12-feet higher than the thalweg of the Walton Creek main channel at Cross-Section 4571.82, which is located along the south property line of the Homewood Suites site.

Flood flows are conveyed from south to north in the east roadside ditch along Highway 40 beginning at the southwest corner of the Homewood Suites property and ending at the upstream side (east side) of the bridge crossing at Highway 40 and Walton Creek.

A 3,430-foot-long lateral weir was incorporated into the HEC-RAS model beginning at the upstream main channel Cross-Section 5893 (to the south), and ending at the downstream main channel Cross-Section 1789, which is located roughly 170' upstream of the Highway 40 bridge structure.

An inline structure was also incorporated into the Proposed Project model and is located just north of split flow Cross-Section 998.7 at the southwest corner of the Homewood Suites property. This structure is intended to limit the flow along the Highway 40 roadside ditch to a maximum peak discharge of 359 cfs. This maximum discharge is based on the capacity of the existing downstream culvert at the Holiday Inn drive entrance off Highway 40 (Cross-Section 996.45) and is based on a HW/D ratio of 1.5 for the 100-year event. See attached HY-8 output located in Appendix C.

Project Reference Documents

- 1) Homewood Suites Stone Lane Plan and Profile (.dwg format), received on May 23, 2015, from Owen Consulting Group, Inc.
- 2) Hampton Inn & Holiday Inn Express Final Grading Plan (.dwg format), received on February 8, 2022, from Four Points Surveying and Engineering, Inc.
- 3) HEC-RAS regulatory model for Walton Creek, received on June 19, 2015, from Michael Baker International.
- 4) Aerial topographic mapping and supplemental ground survey (.dwg format) received on February 7, 2022, from Four Points Surveying and Engineering.

HEC-RAS Effective Model

The Effective HEC-RAS project file entitled EYAMPA.prj was used as a basis for the HEC-RAS analysis, which was obtained from Michael Baker International on June 19, 2015. The HEC-RAS Plan entitled EYAMPA.p05 includes the 100-yr floodway run and was the only storm frequency analyzed.

FEMA's National Flood Hazard Layer (NFHL) Viewer was referenced on January 12, 2022, in order to verify that the effective FIRM mapping had not changed since obtaining the HEC-RAS model from

Michael Baker in 2015. The date of the effective FIRM is February 4, 2005, therefore the regulatory model obtained in 2015 could still be used as a basis for the Proposed Project hydraulic analysis. See Exhibit 1.

HEC-RAS Duplicate Effective Model

The Effective HEC-RAS project file entitled EYAMPA.prj was used as a basis for the Duplicate Effective model. The HEC-RAS Plan entitled WC 100-yr DE.p05 includes the 100-yr floodway run and was the only storm frequency analyzed. The river cross-sections and peak discharges in the Duplicate Effective model remained unchanged from the Effective model.

Output from the Duplicate Effective model can be found in Appendix A of this report.

HEC-RAS Existing Conditions Model

An Existing Conditions HEC-RAS model has been prepared as part of this final hydraulic analysis and includes improved topographic information along the study reach. The Duplicate Effective model has been used as a basis for the Existing Conditions model and improved topographic information has been applied to Cross-Sections 1578 through 7176.41.

The Existing Conditions model includes: a future bridge crossing at Stone Lane; a proposed inline overflow weir at the southwest corner of the Homewood Suites property; a lateral weir defined by the existing topography beginning at the Highway 40 bridge crossing and ending at the upstream split flow junction, and a new split flow channel that commences at a junction roughly 0.28 miles upstream of the subject site.

Although the inline weir and new 48" diameter culvert at Stone Lane are proposed improvements, they are included in the Existing Conditions model to reflect the modifications necessary to alleviate flooding of properties along the east side of Highway 40, which was a concern raised by staff at the City of Steamboat Springs.

Output from the Existing Conditions model can be found in Appendix B of this report.

HEC-RAS Proposed Project Model

The Existing Conditions HEC-RAS model was used as a basis for the Proposed Project model, which is entitled WaltonCreek-PP.prj. The Proposed Project model includes all the elements described in the Existing Conditions model and the placement of fill on the proposed Hampton Inn & Holiday Inn Express site.

Results from the final Proposed Project analysis show that roughly 74% of the flood flow remains in the Walton Creek main channel and overbanks, and the remaining 26% (138.97 cfs) will be conveyed in the east roadside ditch along Highway 40.

Prelim. Floodplain Analysis. The over-topping of Stone Lane needs further study and discussion. What is the overflow path?

Roughly 138.97 cfs passes over the inline structure located at the southwest corner of the Homewood Suites property, which has an overtopping elevation of 6762.0. See detail in Appendix E.

The 100-yr high water elevation at the upstream end of the two culverts (1-48" existing and 1-48" proposed) at Stone Lane is estimated to be 6760.77 with a road overtopping elevation of 6761.05. As per the Elevation Certificate dated November 2, 2018, the finished floor elevation of the Homewood Suites building is 6762.53. Without the additional 48" diameter culvert, Stone Lane will overtop during the 100-yr flood.

Output from the Proposed Project model can be found in Appendix C of this report.

CONCLUSIONS

Results of the Final HEC-RAS modeling indicate that an overflow weir at the southwest corner of the Homewood Suites property can effectively limit the discharge at the existing roadside ditch along the east side of Highway 40. The notch elevation of the weir would be set at 6762.00 (NGVD29) and is 1-foot high for a top elevation of 6763.00. The notch elevation is roughly 3.6-feet above the thalweg in the split flow channel-roadside ditch.

The dramatic difference in the water surface elevations beginning at Cross-Section 4667 can be attributed to the inline weir and berm that was constructed in 2020 along the south property line of the Homewood Suites site, which serves to back up the flood flows until it either overtops the weir or returns to the main channel. The dramatic decreases in the water surface elevations from Cross Section 5209 to 7577 can be attributed to the split flow which diverts roughly 500 cfs from the main channel to the split flow channel. Improved topographic mapping is also a factor.

When comparing the results of the Duplicate Effective versus Existing Conditions models, the net change in the 100-yr WSEL between Cross-Sections 3609 and 9027 is as follows.

Comparison of Duplicate Effective vs. Existing Conditions Models 100-yr Water Surface Elevations

River	River Station	Duplicate Effective Model WSEL (ft)	Existing Conditions Model WSEL (ft)	Difference in Elevation (ft)
Walton Creek	3609	6758.85	6758.67	-0.18
Walton Creek	3639	6759.08	6758.82	-0.26
Walton Creek	4667	6760.03	6761.92	+1.89
Walton Creek	5209	6764.84	6763.03	-1.81
Walton Creek	5550.12	6766.51	6763.91	-2.60
Walton Creek	5892	6766.74	6764.73	-2.01
Walton Creek	6375	6770.22	6767.46	-2.76
Walton Creek	7577	6771.11	6768.57	-2.54
Walton Creek	8070	6775.39	6775.39	0.0

Walton Creek	8402	6776.76	6776.76	0.0
Walton Creek	9027	6777.23	6777.23	0.0

When comparing the results of the Existing Conditions versus Proposed Project models, the net change in the 100-yr WSEL between Cross-Sections 3742 and 4178.71 is as follows.

**Comparison of Existing Conditions vs. Proposed Project Models
100-yr Water Surface Elevations**

River	River Station	Existing Conditions Model WSEL (ft)	Proposed Project Model WSEL (ft)	Difference in Elevation (ft)
Walton Creek	3742	6759.25	6759.26	+0.10
Walton Creek	3887.57	6759.32	6759.32	0.0
Walton Creek	4033.14	6759.70	6759.62	-0.08
Walton Creek	4178.71	6759.98	6759.95	-0.03


Cross Section 3742 is located along the north (downstream) side of the proposed Hampton Inn & Holiday Inn Express project and Cross-Section 4178.71 is located along the north right-of-way line of Stone Lane.

Results of both the Existing Conditions and Proposed Project models indicate that flood flows in the east roadside ditch along Highway 40 appear to stay contained within the channel with no road overtopping. This is a result of the proposed inline weir and additional 48" diameter culvert at Stone Lane.

Recommendations include:

1. Installation of an additional 48" diameter culvert at Stone Lane.
2. Installation of an overflow weir in the east roadside ditch along Highway 40 near the southwest corner of the Homewood Suites site.
3. Raise the top of berm along the south property line of the Homewood Suites property 2-feet to prevent overtopping of the 100-yr flood flow.

Sincerely,
WOHNRADE CIVIL ENGINEERS, INC.



Mary B. Wohnrade, P.E. - Principal
Registered Engineer - CO



National Flood Hazard Layer FIRMette



106°49'11"W 40°26'55"N



Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS		Without Base Flood Elevation (BFE) Zone A, V, A99
		With BFE or Depth Zone AE, AO, AH, VE, AR
		Regulatory Floodway
OTHER AREAS OF FLOOD HAZARD		0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X
		Future Conditions 1% Annual Chance Flood Hazard Zone X
		Area with Reduced Flood Risk due to Levee. See Notes, Zone X
		Area with Flood Risk due to Levee Zone D
OTHER AREAS		NO SCREEN Area of Minimal Flood Hazard Zone X
		Effective LOMRs
GENERAL STRUCTURES		Area of Undetermined Flood Hazard Zone D
		Channel, Culvert, or Storm Sewer
		Levee, Dike, or Floodwall
OTHER FEATURES		20.2 Cross Sections with 1% Annual Chance Water Surface Elevation
		17.5
		Coastal Transect
		Base Flood Elevation Line (BFE)
		Limit of Study
		Jurisdiction Boundary
		Coastal Transect Baseline
		Profile Baseline
MAP PANELS		Digital Data Available
		No Digital Data Available
		Unmapped


The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 10/2/2021 at 11:18 AM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

EXHIBIT 1



Wohnrade Civil Engineers

- Land Development
- Highway Design


- Floodplain Management
- Stormwater Management

- UAS Topographic Mapping
- UAS Orthomosaic Mapping

Project

Date: 4/20/2022

Page 1 of 1



Lot 1, Indian Meadows Filing No. 3
Walton Creek Preliminary
HEC-RAS Split Flow Analysis
April 22, 2022



Appendix A

Duplicate Effective Model Output

HEC-RAS HEC-RAS 5.0.7 March 2019
U.S. Army Corps of Engineers
Hydrologic Engineering Center
609 Second Street
Davis, California

```

X      X XXXXXX   XXXX      XXXX      XX      XXXX
X      X X        X      X      X X      X X      X
X      X X        X      X X      X X      X X      X
XXXXXXXX XXXX     X      XXX XXXX XXXXXXX XXXX
X      X X        X      X X      X X      X      X
X      X X        X      X X      X X      X      X
X      X XXXXXX   XXXX      X X      X X      XXXXX

```

PROJECT DATA

Project Title: WC 100-yr DE
Project File : WaltonCreek-DE.prj
Run Date and Time: 2/12/2022 10:35:54 AM

Project in English units

Project Description:

WaltonCreekDE.prj HEC-RAS version 5.0.7 model for Duplicate Effective Conditions

Includes the Yampa River and Tributaries Near Steamboat Springs,
CO

The Duplicate Effective Model Plan includes:

Plan 05: 100-yr Floodway
Run

PLAN DATA

Plan Title: WC 100-yr DE
Plan File : s:\2111_00_INM\04_DOCUMENTS\HEC-RAS\HOMWOOD SUITES MODELS\DUPLICATE EFFECTIVE\WaltonCreek-DE.p05

Geometry Title: WC 100-yr DE
Geometry File : s:\2111_00_INM\04_DOCUMENTS\HEC-RAS\HOMWOOD SUITES MODELS\DUPLICATE EFFECTIVE\WaltonCreek-DE.g04

Flow Title : WC 100-yr DE FW
Flow File : s:\2111_00_INM\04_DOCUMENTS\HEC-RAS\HOMWOOD SUITES MODELS\DUPLICATE EFFECTIVE\WaltonCreek-DE.f01

Plan Description:

This plan is the Duplicate Effective model for the 100-year event. The model extends from the confluence with the Yampa River (Cross Section 813, Lower Reach) to just upstream of County Road 24 (Cross Section 13645, Main Upper Reach).

The plan includes:

Geometry: WaltonCreek-DE.g04
Steady Flow:
WaltonCreek-DE.f01

Plan Summary Information:

Profile Output Table - Standard Table 1

Reach	River Sta	Profile	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
main upper	13645	100-yr	1883.00	6817.46	6824.21		6824.31	0.000941	3.06	1128.83	612.02	0.26
main upper	13145	100-yr	1883.00	6817.46	6822.35	6822.35	6823.10	0.011733	7.53	340.66	238.76	0.83
split	12570	100-yr	654.56	6807.40	6810.36		6810.55	0.008165	4.16	223.87	221.13	0.56
split	12514.2*	100-yr	654.56	6806.66	6809.64		6809.89	0.008173	4.46	203.65	207.00	0.59
split	12458.4*	100-yr	654.56	6805.92	6808.87		6809.19	0.008641	4.82	176.44	186.31	0.62
split	12402.6*	100-yr	654.56	6805.18	6808.46		6808.67	0.004214	3.86	222.58	205.11	0.46
split	12346.8*	100-yr	654.56	6804.44	6808.37		6808.46	0.001305	2.63	339.86	223.29	0.27
split	12291	100-yr	654.56	6803.70	6808.27	6805.86	6808.37	0.000826	2.52	259.59	226.78	0.23
split	12250		Bridge									
split	12202	100-yr	654.56	6803.70	6805.85	6805.85	6806.61	0.020076	6.98	93.72	60.95	0.99
split	12112	100-yr	654.56	6801.09	6806.04		6806.06	0.000287	1.13	576.89	236.68	0.13
main split	12570.	100-yr	1228.44	6807.23	6809.84	6809.77	6810.55	0.018247	6.78	181.53	116.58	0.95
main split	12291	100-yr	1228.44	6801.38	6807.81	6806.11	6808.40	0.004270	6.19	203.87	199.64	0.53
main split	12250		Bridge									
main split	12202	100-yr	1228.44	6801.65	6806.64	6805.69	6807.32	0.005683	6.71	191.69	167.21	0.61
main split	12112	100-yr	1228.44	6800.95	6806.63	6804.70	6806.85	0.001638	3.93	390.73	139.57	0.34
lower-DE	11692	100-yr	1883.00	6799.38	6804.48	6804.48	6805.22	0.008492	7.52	380.77	310.65	0.73
lower-DE	11280	100-yr	1883.00	6791.13	6795.21	6794.38	6795.65	0.010546	6.21	426.35	309.53	0.76
lower-DE	10714	100-yr	1883.00	6783.81	6790.43	6789.96	6790.75	0.007455	4.53	415.78	244.92	0.61
lower-DE	9997	100-yr	1883.00	6781.76	6785.56	6785.12	6785.95	0.008868	6.90	528.67	503.47	0.73
lower-DE	9471	100-yr	1883.00	6775.50	6780.79	6780.45	6781.44	0.006749	6.88	360.55	201.80	0.64
lower-DE	9027	100-yr	1883.00	6773.68	6777.23	6776.70	6778.03	0.009136	7.18	268.20	996.85	0.74
lower-DE	8734	100-yr	1883.00	6771.83	6777.12	6775.11	6777.21	0.000891	2.47	890.94	1784.04	0.24
lower-DE	8402	100-yr	1883.00	6772.45	6776.76	6775.66	6776.85	0.001415	2.79	953.02	1642.82	0.29
lower-DE	8070	100-yr	1883.00	6773.07	6775.39	6775.39	6775.75	0.018372	6.05	494.78	1391.90	0.93
lower-DE	7577	100-yr	1883.00	6765.79	6768.57	6767.68	6768.63	0.003756	2.91	1018.87	1277.80	0.43
lower-DE	7176.41	100-yr	1883.00	6764.97	6768.32	6766.75	6768.39	0.001070	2.26	955.69	821.63	0.25
lower-DE	6775.68	100-yr	1883.00	6765.16	6768.29	6768.29	6768.30	0.000259	1.14	2513.64	1128.41	0.12
lower-DE	6375	100-yr	1883.00	6764.27	6767.46	6767.11	6767.48	0.000487	1.44	2046.24	1063.99	0.17
lower-split	1001	100-yr	498.97	6763.00	6766.39	6766.39	6767.01	0.012218	6.69	97.83	693.65	0.81
lower-split	1000	100-yr	138.97	6763.04	6763.37		6763.37	0.000067	0.06	327.53	211.89	0.04
lower-split	999.6	100-yr	138.97	6761.26	6762.82	6762.77	6763.19	0.020959	5.14	29.75	36.31	0.93
lower-split	999	100-yr	138.97	6757.51	6763.02		6763.02	0.000051	0.51	474.67	368.24	0.05
lower-split	998.8	100-yr	138.97	6756.96	6763.01		6763.01	0.000008	0.27	731.30	246.74	0.02
lower-split	998.7	100-yr	138.97	6758.40	6762.98	6760.59	6763.01	0.000325	1.15	128.68	122.74	0.13
lower-split	998.6		Inl Struct									
lower-split	998.56	100-yr	138.97	6757.62	6760.78		6760.81	0.000761	1.29	107.96	75.68	0.19
lower-split	998.5	100-yr	138.97	6757.02	6760.77	6759.29	6760.78	0.000076	0.06	187.48	111.58	0.01
lower-split	998.46		Culvert									
lower-split	998.4	100-yr	138.97	6756.42	6759.29		6759.34	0.001387	1.62	86.83	71.10	0.25
lower-split	998.3	100-yr	138.97	6755.91	6759.24		6759.27	0.000897	1.26	110.33	89.09	0.20
lower-split	998.2	100-yr	138.97	6754.38	6759.19		6759.20	0.000216	0.84	164.93	83.38	0.11
lower-split	998	100-yr	138.97	6754.86	6759.16		6759.17	0.000159	0.81	172.03	77.53	0.09
lower-split	997.8	100-yr	138.97	6753.98	6759.16		6759.16	0.000052	0.53	262.40	89.92	0.05
lower-split	997	100-yr	138.97	6753.95	6759.00	6756.51	6759.09	0.001002	2.43	57.28	20.74	0.26
lower-split	996.45		Culvert									
lower-split	996	100-yr	138.97	6752.86	6758.14		6758.20	0.000725	1.94	71.78	24.14	0.20
lower-split	995.7	100-yr	138.97	6754.13	6757.87		6757.95	0.002220	2.29	60.77	39.37	0.32
lower-split	995.5	100-yr	138.97	6752.66	6757.68	6755.42	6757.75	0.000786	2.24	68.93	33.71	0.23
lower-split	995.45		Culvert									
lower-split	995.4	100-yr	138.97	6751.50	6756.56	6753.98	6756.62	0.000822	2.08	66.75	29.24	0.22
lower-split	995.2	100-yr	138.97	6752.33	6755.30	6755.30	6756.09	0.021464	7.13	19.49	12.65	1.01
lower-split	995	100-yr	138.97	6751.22	6755.42		6755.47	0.000544	1.82	91.27	41.77	0.19
lower-main split	5893	100-yr	1384.03	6764.64	6766.85		6767.01	0.003828	3.30	439.44	283.72	0.44
lower-main split	5892.9		Lat Struct									
lower-main split	5892.0	100-yr	1384.19	6761.21	6764.73	6764.73	6765.42	0.009892	7.30	258.00	201.32	0.77
lower-main split	5550.12	100-yr	1384.77	6761.21	6763.91		6764.07	0.006110	4.44	515.02	503.74	0.57
lower-main split	5209	100-yr	1391.43	6759.71	6763.03	6762.03	6763.16	0.003783	2.97	510.83	442.21	0.43
lower-main split	4667	100-yr	1430.43	6757.16	6761.92	6760.23	6761.95	0.000620	2.27	1142.16	647.82	0.20
lower-main split	4571.82	100-yr	1450.18	6757.22	6761.65	6760.34	6761.82	0.002055	4.24	511.15	239.12	0.37
lower-main split	4262.82	100-yr	1504.93	6754.54	6760.70	6760.03	6761.06	0.002927	5.59	411.61	555.76	0.45
lower-main split	4220.82		Bridge									
lower-main split	4178.71	100-yr	1504.93	6753.81	6759.95	6758.42	6760.07	0.001171	3.70	676.66	284.82	0.29
lower-main split	4033.14	100-yr	1509.71	6753.43	6759.62		6759.83	0.001617	4.30	520.30	252.76	0.34
lower-main split	3887.57	100-yr	1519.52	6752.84	6759.32		6759.57	0.001912	4.66	472.82	205.33	0.37

lower-main split	3742	100-yr	1529.98	6752.95	6759.26		6759.34	0.000837	3.26	792.42	284.55	0.25
lower-main split	3640	100-yr	1541.16	6752.89	6758.92	6757.50	6759.24	0.002439	4.90	407.70	187.57	0.41
lower-main split	3639	100-yr	1555.00	6752.65	6758.82	6756.42	6759.11	0.002014	4.36	359.23	88.30	0.37
lower-main split	3622		Bridge									
lower-main split	3609	100-yr	1555.00	6753.33	6758.67		6759.02	0.002916	4.77	330.93	133.33	0.44
lower-main split	3379	100-yr	1562.86	6752.32	6758.16	6756.23	6758.45	0.002080	4.66	440.62	542.36	0.38
lower-main split	3035	100-yr	1664.49	6751.55	6757.89	6755.57	6757.98	0.000774	2.85	788.91	671.95	0.23
lower-main split	2665	100-yr	1675.36	6747.30	6757.88		6757.89	0.000078	1.43	2087.69	538.07	0.08
lower-main split	2539	100-yr	1693.63	6747.21	6757.86	6750.84	6757.88	0.000093	1.23	1682.28	471.62	0.09
lower-main split	2528		Bridge									
lower-main split	2517	100-yr	1693.63	6747.41	6757.80		6757.85	0.000228	1.73	985.33	206.14	0.13
lower-main split	2294	100-yr	1730.72	6751.03	6757.53		6757.71	0.001190	3.71	583.36	174.54	0.29
lower-main split	2103	100-yr	1755.50	6750.42	6757.17		6757.42	0.001818	5.11	516.60	154.96	0.37
lower-main split	1790	100-yr	1782.93	6750.40	6757.03	6754.58	6757.27	0.001346	4.59	539.69	155.80	0.32
lower-main split	1789	100-yr	1845.03	6750.35	6756.86		6757.02	0.000824	3.44	631.49	164.48	0.25
lower-main split	1640.	100-yr	1845.03	6750.41	6754.71	6754.71	6756.55	0.014493	10.93	172.47	63.04	0.98
lower	1578	100-yr	1984.00	6744.57	6755.26	6749.30	6755.46	0.000551	3.55	559.48	385.01	0.21
lower	1516		Bridge									
lower	1455	100-yr	1984.00	6744.90	6755.04	6748.88	6755.22	0.000549	3.40	583.77	650.62	0.20

Profile Output Table - Standard Table 2

Reach	River Sta	Profile	E.G. Elev (ft)	W.S. Elev (ft)	Vel Head (ft)	Frctn Loss (ft)	C & E Loss (ft)	Q Left (cfs)	Q Channel (cfs)	Q Right (cfs)	Top Width (ft)
main upper	13645	100-yr	6824.31	6824.21	0.09	1.14	0.07	549.52	1097.81	235.67	612.02
main upper	13145	100-yr	6823.10	6822.35	0.75	7.95	0.01	316.24	1566.76		238.76
split	12570	100-yr	6810.55	6810.36	0.20	0.66	0.01		434.34	220.22	221.13
split	12514.2*	100-yr	6809.89	6809.64	0.25	0.69	0.01		507.12	147.44	207.00
split	12458.4*	100-yr	6809.19	6808.87	0.32	0.49	0.03		575.52	79.05	186.31
split	12402.6*	100-yr	6808.67	6808.46	0.21	0.18	0.03		578.05	76.51	205.11
split	12346.8*	100-yr	6808.46	6808.37	0.09	0.09	0.00	2.24	536.90	115.42	223.29
split	12291	100-yr	6808.37	6808.27	0.10	0.04	0.12		654.56		226.78
split	12250		Bridge								
split	12202	100-yr	6806.61	6805.85	0.76	0.08	0.37		654.56		60.95
split	12112	100-yr	6806.06	6806.04	0.02	0.76	0.07		654.56		236.68
main split	12570.	100-yr	6810.55	6809.84	0.71	2.09	0.06		1228.04	0.40	116.58
main split	12291	100-yr	6808.40	6807.81	0.59	0.14	0.12	10.60	1217.84		199.64
main split	12250		Bridge								
main split	12202	100-yr	6807.32	6806.64	0.68	0.24	0.24	13.64	1191.82	22.98	167.21
main split	12112	100-yr	6806.85	6806.63	0.21	1.57	0.05	157.42	1053.74	17.27	139.57
lower-DE	11692	100-yr	6805.22	6804.48	0.74	3.85	0.09	306.82	1575.97	0.21	310.65
lower-DE	11280	100-yr	6795.65	6795.21	0.43	4.86	0.03	2.11	1193.55	687.35	309.53
lower-DE	10714	100-yr	6790.75	6790.43	0.32	4.79	0.01		1883.00		244.92
lower-DE	9997	100-yr	6785.95	6785.56	0.39	4.48	0.03	1.20	856.95	1024.85	503.47
lower-DE	9471	100-yr	6781.44	6780.79	0.65	3.40	0.01	226.55	1656.45		201.80
lower-DE	9027	100-yr	6778.03	6777.23	0.80	0.61	0.21		1877.16	5.84	996.85
lower-DE	8734	100-yr	6777.21	6777.12	0.09	0.36	0.00	178.95	1702.00	2.05	1784.04
lower-DE	8402	100-yr	6776.85	6776.76	0.09	1.08	0.03	536.35	1341.43	5.22	1642.82
lower-DE	8070	100-yr	6775.75	6775.39	0.36	2.80	0.09	854.15	1028.85		1391.90
lower-DE	7577	100-yr	6768.63	6768.57	0.06	0.24	0.00	1539.37	343.63		1277.80
lower-DE	7176.41	100-yr	6768.39	6768.32	0.07	0.08	0.02	147.66	1729.88	5.46	821.63
lower-DE	6775.68	100-yr	6768.30	6768.29	0.01	0.05	0.00	1616.53	132.90	133.57	1128.41
lower-DE	6375	100-yr	6767.48	6767.46	0.01	0.45	0.01	1544.56	220.65	117.79	1063.99
lower-split	1001	100-yr	6767.01	6766.39	0.62	0.20	0.19	57.32	441.58	0.07	693.65
lower-split	1000	100-yr	6763.37	6763.37	0.00	0.14	0.04	137.66	0.06	1.25	211.89
lower-split	999.6	100-yr	6763.19	6762.82	0.38	0.06	0.11	16.81	122.16		36.31
lower-split	999	100-yr	6763.02	6763.02	0.00	0.01	0.00	68.19	42.99	27.79	368.24
lower-split	998.8	100-yr	6763.01	6763.01	0.00	0.00	0.00	37.99	29.64	71.34	246.74
lower-split	998.7	100-yr	6763.01	6762.98	0.02				137.76	1.21	122.74
lower-split	998.6		Inl Struct								
lower-split	998.56	100-yr	6760.81	6760.78	0.03	0.02	0.00		138.97		75.68
lower-split	998.5	100-yr	6760.78	6760.77	0.01			0.55	2.67	135.75	111.58
lower-split	998.46		Culvert								
lower-split	998.4	100-yr	6759.34	6759.29	0.04	0.07	0.00	2.46	136.51		71.10
lower-split	998.3	100-yr	6759.27	6759.24	0.02	0.06	0.00		138.97		89.09
lower-split	998.2	100-yr	6759.20	6759.19	0.01	0.03	0.00		138.97		83.38
lower-split	998	100-yr	6759.17	6759.16	0.01	0.01	0.00	0.66	137.77	0.54	77.53
lower-split	997.8	100-yr	6759.16	6759.16	0.00	0.06	0.01		138.97		89.92
lower-split	997	100-yr	6759.09	6759.00	0.09				138.97		20.74
lower-split	996.45		Culvert								
lower-split	996	100-yr	6758.20	6758.14	0.06	0.24	0.00		138.97		24.14
lower-split	995.7	100-yr	6757.95	6757.87	0.08	0.20	0.00		138.97		39.37
lower-split	995.5	100-yr	6757.75	6757.68	0.07				131.35	7.62	33.71
lower-split	995.45		Culvert								
lower-split	995.4	100-yr	6756.62	6756.56	0.07	0.45	0.07		138.97		29.24
lower-split	995.2	100-yr	6756.09	6755.30	0.79	0.21	0.22		138.97		12.65
lower-split	995	100-yr	6755.47	6755.42	0.04	0.00	0.02	4.67	113.17	21.13	41.77
lower-main split	5893	100-yr	6767.01	6766.85	0.16	1.53	0.05	53.29	1330.74		283.72
lower-main split	5892.9		Lat Struct								
lower-main split	5892.0	100-yr	6765.42	6764.73	0.69	1.09	0.16	216.98	1124.88	42.33	201.32
lower-main split	5550.12	100-yr	6764.07	6763.91	0.16	0.90	0.01	866.96	506.58	11.22	503.74
lower-main split	5209	100-yr	6763.16	6763.03	0.13	1.18	0.03	112.74	1278.69		442.21
lower-main split	4667	100-yr	6761.95	6761.92	0.04	0.12	0.01	915.56	463.15	51.72	647.82
lower-main split	4571.82	100-yr	6761.82	6761.65	0.17	0.75	0.02	768.22	655.63	26.33	239.12
lower-main split	4262.82	100-yr	6761.06	6760.70	0.35	0.09	0.15	14.39	1023.80	466.75	555.76
lower-main split	4220.82		Bridge								
lower-main split	4178.71	100-yr	6760.07	6759.95	0.12	0.21	0.03	383.24	699.39	422.31	284.82
lower-main split	4033.14	100-yr	6759.83	6759.62	0.21	0.26	0.00	288.06	1041.52	180.12	252.76
lower-main split	3887.57	100-yr	6759.57	6759.32	0.25	0.18	0.05	469.82	1038.14	11.56	205.33

lower-main split	3742	100-yr	6759.34	6759.26	0.08	0.07	0.02	724.63	437.16	368.18	284.55
lower-main split	3640	100-yr	6759.24	6758.92	0.32	0.12	0.01	219.40	1264.45	57.31	187.57
lower-main split	3639	100-yr	6759.11	6758.82	0.29	0.02	0.00	3.82	1551.18		88.30
lower-main split	3622		Bridge								
lower-main split	3609	100-yr	6759.02	6758.67	0.35	0.54	0.03	2.08	1552.91		133.33
lower-main split	3379	100-yr	6758.45	6758.16	0.28	0.40	0.06	279.42	1283.44		542.36
lower-main split	3035	100-yr	6757.98	6757.89	0.09	0.07	0.02	675.63	908.59	80.27	671.95
lower-main split	2665	100-yr	6757.89	6757.88	0.02	0.01	0.00	755.58	707.19	212.59	538.07
lower-main split	2539	100-yr	6757.88	6757.86	0.02	0.00	0.00	53.04	1484.78	155.81	471.62
lower-main split	2528		Bridge								
lower-main split	2517	100-yr	6757.85	6757.80	0.05	0.10	0.04	4.09	1689.54		206.14
lower-main split	2294	100-yr	6757.71	6757.53	0.18	0.28	0.01	45.76	1360.04	324.91	174.54
lower-main split	2103	100-yr	6757.42	6757.17	0.26	0.15	0.01	91.77	913.39	750.34	154.96
lower-main split	1790	100-yr	6757.27	6757.03	0.24	0.22	0.02	269.97	1157.78	355.19	155.80
lower-main split	1789	100-yr	6757.02	6756.86	0.17	0.31	0.17	165.07	1652.32	27.65	164.48
lower-main split	1640.	100-yr	6756.55	6754.71	1.84	0.00	0.82	0.20	1827.00	17.83	63.04
lower	1578	100-yr	6755.46	6755.26	0.20			1.30	1982.70		385.01
lower	1516		Bridge								
lower	1455	100-yr	6755.22	6755.04	0.18				1984.00		650.62

Profile Output Table - Culvert Only

Reach	River Sta		Profile	E.G. US. (ft)	W.S. US. (ft)	E.G. IC (ft)	E.G. OC (ft)	Min El Weir Flow (ft)	Q Culv Group (cfs)	Q Weir (cfs)	Delta WS (ft)	Culv Vel US (ft/s)	Culv Vel DS (ft/s)
lower-split	998.46	Culvert #1	100-yr	6760.78	6760.77	6760.46	6760.78	6761.13	63.71		1.47	5.34	5.77
lower-split	998.46	Culvert #2	100-yr	6760.78	6760.77	6760.43	6760.79	6761.13	75.26		1.47	7.73	6.80
lower-split	996.45	Culvert #1	100-yr	6759.09	6759.00	6758.68	6759.09	6759.99	138.97		0.86	6.33	5.18
lower-split	995.45	Culvert #1	100-yr	6757.75	6757.68	6757.20	6757.75	6758.94	138.97		1.12	6.11	6.01

Profile Output Table - Bridge Only

Reach	River Sta	Profile	E.G. US. (ft)	Min El Prs (ft)	BR Open Area (sq ft)	Prs O WS (ft)	Q Total (cfs)	Min El Weir Flow (ft)	Q Weir (cfs)	Delta EG (ft)	BR Sluice Coef
split	12250	100-yr	6808.37	6808.10	124.14		654.56	6809.51		1.75	
main split	12250	100-yr	6808.40	6810.72	272.88		1228.44	6811.29		1.08	
lower-main split	4220.82	100-yr	6761.06	6760.92	422.75		1504.93	6762.01		0.99	
lower-main split	3622	100-yr	6759.11	6761.55	514.49		1555.00	6759.51		0.09	
lower-main split	2528	100-yr	6757.88	6756.83	720.66		1693.63	6756.30		0.03	
lower	1516	100-yr	6755.46	6754.78	479.89	6755.26	1984.00	6757.54		0.24	

Profile Output Table - Inline Structure

Reach	River Sta	Profile	E.G. Elev (ft)	W.S. Elev (ft)	Q Total (cfs)	Q Weir (cfs)	Q Gates (cfs)	Q Culv (cfs)	Q Inline RC (cfs)	Q Outlet TS (cfs)	Q Breach (cfs)
lower-split	998.6	100-yr	6763.01	6762.98	138.97	138.97					

Profile Output Table - Lateral Structures

Reach	River Sta	Profile	Q US (cfs)	Q Leaving	Total (cfs)	Q DS (cfs)	Q Weir (cfs)	Q Gates (cfs)	Wr Top Wdth (ft)	Weir Max Depth (ft)	Weir Avg Depth (ft)	Min El Weir Flow (ft)	E.G. US. (ft)	W.S. US. (ft)	E.G. DS (ft)	W.S. DS (ft)
lower-main split	5892.9	100-yr	1384.03		-57996.44	1845.03	-57996.44		2905.36	11.16	3.90	6753.72	6766.89	6766.68	6757.11	6756.92

Lot 1, Indian Meadows Filing No. 3
Walton Creek Preliminary
HEC-RAS Split Flow Analysis
April 22, 2022



Appendix D

HY-8 Output

HY-8 Culvert Analysis Report

Crossing Discharge Data

Discharge Selection Method: Specify Minimum, Design, and Maximum Flow

Minimum Flow: 100.00 cfs


Design Flow: 359.00 cfs= HW/D= 1.48

Maximum Flow: 800.00 cfs

Table 1 - Summary of Culvert Flows at Crossing: Holiday Inn Exst. Culvert

Headwater Elevation (ft)	Total Discharge (cfs)	Culvert 1 Discharge (cfs)	Roadway Discharge (cfs)	Iterations
6757.45	100.00	100.00	0.00	1
6758.97	170.00	170.00	0.00	1
6760.29	240.00	240.00	0.00	1
6761.64	310.00	310.00	0.00	1
6762.68	359.00	359.00	0.00	1
6765.04	450.00	433.90	15.97	8
6765.59	520.00	451.16	68.81	4
6766.04	590.00	464.43	125.53	4
6766.44	660.00	476.50	183.48	4
6766.80	730.00	486.93	243.04	3
6767.14	800.00	496.30	303.66	4
6764.61	421.05	421.05	0.00	Overtopping

Rating Curve Plot for Crossing: Holiday Inn Exst. Culvert



Culvert Data: Culvert 1

Table 2 - Culvert Summary Table: Culvert 1

Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)	Tailwater Velocity (ft/s)
100.00 cfs	100.00 cfs	6757.45	3.64	1.957	1-S2n	2.35	2.69	2.36	0.77	9.66	16.34
170.00 cfs	170.00 cfs	6758.97	5.16	3.473	1-S2n	3.18	3.55	3.20	1.03	11.08	19.18
240.00 cfs	240.00 cfs	6760.29	6.48	5.159	5-S2n	3.98	4.24	3.99	1.24	12.01	21.21
310.00 cfs	310.00 cfs	6761.64	7.75	7.829	7-M2c	4.95	4.81	4.81	1.42	12.77	22.82

359.0 0 cfs	359.0 0 cfs	6762.6 8	8.69	8.86 6	7- M2 c	6.00	5.12	5.1 2	1.53	13.9 7	23.78
450.0 0 cfs	433.9 0 cfs	6765.0 4	10.2 8	11.2 28	7- M2 c	6.00	5.48	5.4 8	1.72	16.0 3	25.32
520.0 0 cfs	451.1 6 cfs	6765.5 9	10.6 7	11.7 84	7- M2 c	6.00	5.54	5.5 4	1.86	16.5 5	26.35
590.0 0 cfs	464.4 3 cfs	6766.0 4	10.9 9	12.2 34	7- M2 c	6.00	5.58	5.5 8	1.98	16.9 5	27.27
660.0 0 cfs	476.5 0 cfs	6766.4 4	11.2 8	12.6 27	7- M2 c	6.00	5.61	5.6 1	2.09	17.3 3	28.11
730.0 0 cfs	486.9 3 cfs	6766.8 0	11.5 4	12.9 88	7- M2 c	6.00	5.64	5.6 4	2.20	17.6 5	28.89
800.0 0 cfs	496.3 0 cfs	6767.1 4	11.7 8	13.3 26	7- M2 c	6.00	5.66	5.6 6	2.30	17.9 5	29.60

Culvert Barrel Data

Culvert Barrel Type Straight Culvert

Inlet Elevation (invert): 6753.81 ft,

Outlet Elevation (invert): 6752.73 ft


Culvert Length: 60.01 ft,

Culvert Slope: 0.0180

Inlet Throat Elevation: 6753.70 ft,

Inlet Crest Elevation: 0.00 ft


Culvert Performance Curve Plot: Culvert 1



Water Surface Profile Plot for Culvert: Culvert 1

Crossing - Holiday Inn Exst. Culvert, Design Discharge - 359.0 cfs

Culvert - Culvert 1, Culvert Discharge - 359.0 cfs



Site Data - Culvert 1

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 6753.81 ft

Outlet Station: 60.00 ft

Outlet Elevation: 6752.73 ft

Number of Barrels: 1

Culvert Data Summary - Culvert 1

Barrel Shape: Circular

Barrel Diameter: 6.00 ft

Barrel Material: Corrugated Steel

Embedment: 0.00 in

Barrel Manning's n: 0.0240

Culvert Type: Side-Tapered, Circular

Inlet Configuration: Beveled Edge Top and Side (45-90°) Wingwall (Ke=0.2)

Inlet Depression: None

Tailwater Data for Crossing: Holiday Inn Exst. Culvert

Table 3 - Downstream Channel Rating Curve (Crossing: Holiday Inn Exst. Culvert)

Flow (cfs)	Water Surface Elev (ft)	Velocity (ft/s)	Depth (ft)	Shear (psf)	Froude Number
100.00	6753.50	0.77	16.34	18.30	3.65
170.00	6753.76	1.03	19.18	24.49	3.79
240.00	6753.97	1.24	21.21	29.46	3.88
310.00	6754.15	1.42	22.82	33.71	3.95
359.00	6754.26	1.53	23.78	36.39	3.99
450.00	6754.45	1.72	25.32	40.87	4.05
520.00	6754.59	1.86	26.35	43.99	4.09
590.00	6754.71	1.98	27.27	46.88	4.12
660.00	6754.82	2.09	28.11	49.58	4.15
730.00	6754.93	2.20	28.89	52.13	4.17
800.00	6755.03	2.30	29.60	54.54	4.20

Tailwater Channel Data - Holiday Inn Exst. Culvert

Tailwater Channel Option: Trapezoidal Channel

Bottom Width: 6.00 ft

Side Slope (H:V): 2.50 (:1)

Channel Slope: 0.3800

Channel Manning's n: 0.0400

Channel Invert Elevation: 6752.73 ft

Roadway Data for Crossing: Holiday Inn Exst. Culvert

Roadway Profile Shape: Irregular Roadway Shape (coordinates)

Irregular Roadway Cross-Section

Coord No.	Station (ft)	Elevation (ft)
0	0.00	6764.86
1	10.82	6764.65
2	26.01	6764.61

Roadway Surface: Paved



Roadway Top Width: 36.00 ft

Lot 1, Indian Meadows Filing No. 3
Walton Creek Preliminary
HEC-RAS Split Flow Analysis
April 22, 2022



Appendix E



Reference Documents

[illegible]

Date:
Job No:
Drawn:
Design:
Checked:
Scale:

**HOMEWOOD SUITES
STEAMBOAT SPRINGS, COLORADO
PUBLIC IMPROVEMENT CONSTRUCTION PLANS**

Sheet:




440 S. Lincoln Ave, Suite 4A
P.O. Box 775966
Steamboat Springs, CO 80487
(970)-871-6772
www.fourpointssse.com

NO.	DATE	REVISIONS	PER 1ST DRT COMMENTS
1	4/19/22		PER 1ST DRT COMMENTS, 4/22/22

LOT 1 INDIAN MEADOWS
PHASE I DEVELOPMENT PLAN
LOT 1, INDIAN MEADOWS FILING NO. 3
STEAMBOAT SPRINGS, CO 80487

HORIZONTAL SCALE



CONTOUR INTERVAL = 2FT

DATE: 11/30/2021
JOB #: 1448-005
DRAWN BY: SDW
DESIGN BY: JLW
REVIEW BY: RL

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24\"/>

DRAWING:

SHEET NO.

C2



[illegible]

LOT 1 INDIAN MEADOWS
PHASE I DEVELOPMENT PLAN
LOT 1, INDIAN MEADOWS FILING NO. 3
STEAMBOAT SPRINGS, CO 80487

CONTOUR INTERVAL = 1 FT

IF THIS DRAWING IS PRESENTED IN A
FORMAT OTHER THAN 24" X 36", THE
GRAPHIC SCALE SHOULD BE RE-DESIGNED

C3.1



NOTE:

1. TRENCH FOR WEIR OUTLET STRUCTURE USING NATIVE GROUND AS FORM WORK. CONSTRUCT WEIR 8" MINIMUM THICKNESS. UPON COMPLETION OF TRENCHING, PLACE TEMPERED STEEL AND CONCRETE IMMEDIATELY. FORM TOP 4".
2. ELEVATIONS BASED ON NAVD88 DATUM.

WEIR SCHEDULE				
LOCATION	W (FT)	NOTCH ELEV.	TOP OF WEIR	BOTTOM OF WEIR
HOMEWOOD SUITES	83.5	6766.12	6767.12	6764.12

POND OVERFLOW WEIR

NOT TO SCALE

